

Intersection Traffic Control Feasibility Study

- ◆ CSAH 9 at Highview Avenue
- ◆ CSAH 9 at CSAH 60 (185th Avenue)

Prepared For:

Dakota County Transportation Department
Western Service Center
14955 Galaxie Avenue, 3rd Floor
Apple Valley, MN 55124



Prepared By:

Alliant Engineering, Inc.
233 Park Ave South, Suite 300
Minneapolis, MN 55415



Final Report
March 31, 2009

Table of Contents

| | |
|--|-----------|
| List of Figures | ii |
| List of Tables | ii |
| Executive Summary | 1 |
| 1.0 Introduction | 6 |
| 1.1 Purpose and Need | 6 |
| 1.2 Description of Location | 7 |
| 1.3 Technical Advisory Committee | 7 |
| 1.4 Elements of Study | 7 |
| 2.0 Existing Conditions | 9 |
| 2.1 Existing Roadway and Traffic Control Characteristics | 9 |
| 2.2 Right of Way | 9 |
| 2.3 Existing Traffic Volumes..... | 10 |
| 2.4 Existing Crash Experience | 13 |
| 2.5 Key Design Considerations..... | 14 |
| 3.0 Future Conditions | 15 |
| 3.1 ADT and Background Traffic Forecasts..... | 15 |
| 3.2 Forecast Peak Hour Intersection Traffic Volumes..... | 17 |
| 3.3 Forecast Hourly Approach Volumes | 18 |
| 4.0 Analysis of Alternatives | 22 |
| 4.1 Traffic Control Alternatives..... | 22 |
| 4.1.1 Signal Warrant Analysis | 22 |
| 4.1.2 Safety Analysis | 24 |
| 4.2 Concept Layout Alternatives | 26 |
| 4.3 Traffic Operations Analysis..... | 34 |
| 4.3.1 Analysis Tools | 35 |
| 4.3.2 Level of Service Definition..... | 36 |
| 4.3.3 Analysis Results..... | 36 |
| 4.4 Evaluation of Alternatives | 43 |
| 4.4.1 Traffic Control Change Timeline..... | 46 |
| 4.4.2 Selection of Preferred Alternative | 47 |
| 5.0 Recommendations | 50 |
| 5.1 CSAH 9 at Highview Avenue..... | 50 |
| 5.2 CSAH 9 at CSAH 60 | 50 |
| 6.0 Appendices | 51 |

List of Figures

| | |
|---|----|
| Figure 1. Project Location..... | 8 |
| Figure 2. Existing Lane Geometrics and Traffic Control | 11 |
| Figure 3. Existing Intersection Traffic Volumes | 12 |
| Figure 4. Forecast Year 2010 Intersection Traffic Volumes | 19 |
| Figure 5. Forecast Year 2030 (Without CSAH 60 Extension) Intersection Traffic Volumes..... | 20 |
| Figure 6. Forecast Year 2030 (With CSAH 60 Extension) Intersection Traffic Volumes..... | 21 |
| Figure 7. CSAH 9 at Highview Avenue – Concept Layout 1a..... | 28 |
| Figure 8. CSAH 9 at Highview Avenue – Concept Layout 2a..... | 29 |
| Figure 9. CSAH 9 at CSAH 60 – Concept Layout 1b | 30 |
| Figure 10. CSAH 9 at CSAH 60 – Concept Layout 2b | 31 |
| Figure 11. CSAH 9 at CSAH 60 – Concept Layout 3b | 32 |
| Figure 12. CSAH 9 at CSAH 60 – Concept Layout 4b | 33 |

List of Tables

| | |
|---|----|
| Table 1. Existing Year 2007 ADT Volumes..... | 10 |
| Table 2. 2005 - 2007 Crash Rate Summary | 13 |
| Table 3. Comparison of Background 2030 Forecast ADT Volumes..... | 16 |
| Table 4. Forecast Year 2010 and 2030 ADT Volumes..... | 16 |
| Table 5. Signal Warrant Analysis Result Summary – CSAH 9 at Highview Avenue..... | 23 |
| Table 6. Signal Warrant Analysis Result Summary – CSAH 9 at CSAH 60 | 23 |
| Table 7. Forecast Annual Crash Comparison – CSAH 9 at Highview Avenue | 24 |
| Table 8. Forecast Annual Crash Comparison – CSAH 9 at CSAH 60..... | 25 |
| Table 9. Crash Type and Crash Severity Comparison by Traffic Control Device | 25 |
| Table 10. Analysis Scenarios Summary – CSAH 9 at Highview Avenue..... | 34 |
| Table 11. Analysis Scenarios Summary – CSAH 9 at CSAH 60 | 34 |
| Table 12. LOS Definition | 36 |
| Table 13. Year 2007 Traffic Analysis Results Summary – CSAH 9 at Highview Avenue | 37 |
| Table 14. Year 2010 Traffic Analysis Results Summary – CSAH 9 at Highview Avenue | 37 |
| Table 15. Year 2030 Traffic Analysis Results Summary – CSAH 9 at Highview Avenue | 38 |
| Table 16. Year 2007 Traffic Analysis Results Summary – CSAH 9 at CSAH 60..... | 40 |
| Table 17. Year 2010 Traffic Analysis Results Summary – CSAH 9 at CSAH 60 (Without CSAH 60 Extension) | 40 |
| Table 18. Year 2030 Traffic Analysis Results Summary – CSAH 9 at CSAH 60 (Without CSAH 60 Extension)..... | 41 |

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Table 19. Year 2030 Traffic Analysis Results Summary – CSAH 9 at CSAH 60
(With CSAH 60 Extension)41

Table 20. Comparison Evaluation Matrix – CSAH 9 at Highview Avenue.....44

Table 21. Comparison Evaluation Matrix – CSAH 9 at CSAH 6045

Table 22. Preferred Alternative 2030 PM Peak Hour VISSIM Analysis – CSAH 9 at
Highview Avenue48

Executive Summary

The Dakota County Transportation Department (Dakota County) has identified a need to conduct an Intersection Traffic Control Feasibility Study for the following two intersections:

- County State Aid Highway (CSAH) 9 at Highview Avenue
- CSAH 9 at CSAH 60 (185th Avenue)

The purpose of this Intersection Traffic Control Feasibility Study is to:

- Document the existing geometric, traffic operation and safety characteristics.
- Document and develop the future year 2030 traffic forecasts based upon the Metropolitan Council, City of Lakeville Transportation Plan and the Dakota County Transportation Plan.
- Develop conceptual roadway alternatives to accommodate the forecast 2030 traffic demands at both the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections.
- Conduct a traffic operation analysis of each alternative.
- Develop a matrix comparing preliminary cost estimates, right of way and other factors to help determine the most optimal intersection lane geometrics and appropriate level of traffic control.
- Identify the preferred alternatives and document an implementation plan assessing the estimated year a traffic control device change is needed.

Elements of Study

The following elements are included in the Intersection Traffic Control Feasibility Study:

- Introduction (Section 1.0)
- Existing Conditions (Section 2.0)
- Future Conditions (Section 3.0)
- Analysis of Alternatives (Section 4.0)
- Recommendations (Section 5.0)
- Appendices (Section 6.0)

Alternatives Analysis

Traffic control alternatives and conceptual layouts were analyzed to coincide with the proposed CSAH 9 reconstruction project (year 2010) and a long term forecast horizon

(year 2030). The following documents the three traffic control alternatives considered at both the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections.

- All-way Stop Control.
- Traffic Signal Control.
- Roundabout.

A total of two concept layout alternatives were developed at the CSAH 9/Highview Avenue intersection:

- **Concept Layout 1a – Roundabout.** The CSAH 9/Highview Avenue Concept Layout 1a is illustrated in **Figure 7**.
- **Concept Layout 2a – Four-lane divided roadway with exclusive turn lanes.** Concept Layout 2a would employ either an all-way stop control or traffic signal system and is consistent with the Dakota County 2008-2012 Capital Improvement Plan project. The CSAH 9/Highview Avenue Concept Layout 2a is illustrated in **Figure 8**.

A total of four concept layout alternatives were developed at the CSAH 9/CSAH 60 intersection:

- **Concept Layout 1b – Interim.** Concept Layout 1b would employ either an all-way stop control or traffic signal system during the interim period before CSAH 60 is extended. The CSAH 9/CSAH 60 Concept Layout 1b is illustrated in **Figure 9**. It should be noted, a dual eastbound left turn lane would not be used in conjunction with an all-way stop control.
- **Concept Layout 2b – Four-lane divided roadway with double eastbound left turn.** Concept Layout 2b would employ a traffic signal system following the extension of CSAH 60. The CSAH 9/CSAH 60 Concept Layout 2b is illustrated in **Figure 10**.
- **Concept Layout 3b – Four-lane divided roadway with single eastbound left turn.** Concept Layout 3b would employ either an all-way stop control or traffic signal system following the extension of CSAH 60. The CSAH 9/CSAH 60 Concept Layout 3b is illustrated in **Figure 11**.
- **Concept Layout 4b – Roundabout.** The CSAH 9/CSAH 60 Concept Layout 4b is illustrated in **Figure 12**.

Preferred Alternatives

The preferred alternative at the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections were selected based upon; discussions with the TAC, results of the traffic

operation analysis and safety analysis, and consideration of the key objectives evaluated in the comparison matrix (see Section 4.4).

CSAH 9 at Highview Avenue

The preferred alternative selected at the CSAH 9/Highview Avenue intersection is the roundabout, Concept Layout 1a (refer to **Figure 7**). The roundabout intersection was selected based on the following:

- With the 2008-2012 Capital Improvement Plan project, the intersection is being re-aligned and fully reconstructed. This is the most cost-effective opportunity to build a roundabout. Based on the preliminary cost estimate, the roundabout is expected to result in a net comparable or even less initial cost than a traditional intersection. This is due to the overall less pavement area (approaching roadway segments are narrowed) and reduced right of way needs with the roundabout option. In addition, the long term cost of a roundabout is reduced as the annual maintenance and operation costs are less than a traffic signal.
- The roundabout option will require small triangles of additional right of way on the southwest, southeast and northwest quadrants. However, overall the right of way impact is less than a traditional intersection. Additional right of way along Highview Avenue, south of CSAH 9 will not be required to the same extent as Concept Layout 2a (see **Figure 8**).
- The roundabout alternative will require the lowering of the Highview Avenue and CSAH 9 alignment profiles (to reduce approach grades and to provide a level circle). However, since the intersection is being fully reconstructed, this same consideration would have been made for a traditional intersection.
- Emissions and air quality impacts are expected to be improved with the roundabout option. The traffic analysis found greatly reduced vehicle delays with the roundabout intersection over the traffic signal option. A reduction in motorist delay directly correlates with lowering vehicle emission and fuel consumption.
- The roundabout is expected to provide an immediate benefit and reduction in motorist delay. The roundabout also provides a an immediate and much improved 24-hour solution versus an all-way stop control or a traffic signal system, which was not found needed until year 2023.
- The CSAH 9/Highview Avenue intersection is isolated; therefore does not benefit from coordinated arterial operations. A system or network impact is not expected with the implementation of a roundabout.
- Based on the safety analysis, a roundabout is expected to result in less overall intersection crashes than a traffic signal.

CSAH 9 at CSAH 60

At the CSAH 9/CSAH 60 intersection, the following alternatives were selected:

- **Short Term:** The preferred short-term alternative is signalized intersection control with a dual eastbound left turn, Concept Layout 1b (see **Figure 9**).
- **Long Term:** The preferred long-term alternative (with CSAH 60 extension) is the traditional signalized intersection control with single left turn lanes, Concept Layout 3b (see **Figure 11**).

The signalized intersection control was selected based on the following:

- The traffic operation analysis shows the intersection is expected to need a traffic control change by year 2012. The installation of signalized intersection control prior to the CSAH 60 extension can be implemented with little or no impact to right of way and carry only the cost of the capital to install the signal and the recurring maintenance and operation costs. No additional environmental or utility impacts are expected. A roundabout would require full intersection reconstruction and may not be a feasible option to fund in the interim.
- The signalized intersection control and traditional intersection design maximizes the use of existing infrastructure and previous project investments.
- An existing traffic signal is in operation at Ipava Avenue (a quarter-mile to the west). The development of the CSAH 60 extension to the east is anticipated to result in a signalized arterial corridor. The installation of a traffic signal system at CSAH 60 is most consistent and best fits with the arterial and network characteristics of the corridor.
- The completed four-leg traditional intersection design and traffic signal system is expected to cost approximately 75 percent less than the roundabout option.
- The overall estimated right of way need between the traditional intersection and a roundabout are expected to be the same. The roundabout option could result in less right of way dedication on the east side of CSAH 9, depending upon how the corridor develops. However, at this time the corridor right of way width of 150 feet would accommodate both designs.

Recommendations

CSAH 9 at Highview Avenue

- Construct a multi-lane roundabout intersection. (See Concept Layout 1a, illustrated in **Figure 7**).

- Realign CSAH 9 to the north to develop 90 degree approach angles and appropriate approach deflection radii.
- Lower the roadway profile and approach grades on both CSAH 9 and Highview Avenue to reduce the vertical curves, balance earthwork and provide a level roundabout circle.
- Utilize the existing CSAH 9 pavement, abandoned with the realignment, to develop a short frontage road in re-establishing access to the private residential home on the southwest quadrant. The frontage road would access CSAH 9 (right-in/right-out) at a determined appropriate distance upstream from Highview Avenue.
- Acquire sufficient right of way on each intersection quadrant to allow for the flexibility to widen the Highview Avenue entrance/exit flares to two lanes each. This will provide potential and flexibility to extend the design life, if in the future, unforeseen land use changes or traffic patterns occur and additional capacity is found needed.

CSAH 9 at CSAH 60

- Prior to the extension of CSAH 60, program the installation of a traffic signal system. As part of the signal installation, the eastbound approach should be re-striped to include two eastbound left turn movements. (See Concept Layout 1b, illustrated in **Figure 9**).
- The traffic signal system should be designed and equipment located to require minimal hardware modifications when the future CSAH 60 extension is completed.
- Evaluate the need to obtain a small triangular piece of right of way on the southwest corner. The right of way need will be governed by the final pedestrian ramp and traffic signal pole locations.
- As part of the CSAH 60 extension project, the westbound leg should be constructed as a four-lane divided section with exclusive left and right turn lanes. A southbound left turn and northbound right turn lane should be constructed. (See Concept Layout 3b, illustrated in **Figure 11**).
- The final design should ensure acceptable approach sightlines are maintained.
- The intersection traffic signal phasing will be determined by Dakota County Staff through the final design process. It should be noted, Concept Layout 3b (see **Figure 11**) assumes eastbound/westbound protected/permissive left turn phasing. The installation of protected only left turn phasing is expected to necessitate a dual eastbound left turn lane, Concept Layout 2b (see **Figure 10**).

1.0 Introduction

The Dakota County Transportation Department (Dakota County) has identified a need to conduct an Intersection Traffic Control Feasibility Study for the following two intersections:

- County State Aid Highway (CSAH) 9 at Highview Avenue
- CSAH 9 at CSAH 60 (185th Avenue)

1.1 Purpose and Need

The *2025 Dakota County Transportation Plan*¹ and the *City of Lakeville Transportation Plan*² identify future capacity deficiencies and the need to improve CSAH 9 between the limits of 183rd Street and CSAH 23 (Cedar Avenue). Due to the poor roadway geometrics and operation of the current traffic control device, peak period congestion at the CSAH 9/Highview Avenue intersection currently exists. To address the immediate and future needs, the 2008-2012 Dakota County Capital Improvement Plan identifies the reconstruction of County State Aid Highway (CSAH) 9 (Dodd Boulevard) to a four-lane divided roadway between the limits of 183rd Street and Hayes Avenue. Dakota County is currently in the process of preparing the preliminary engineering documents for this project and anticipates construction will begin in 2010.

Although not currently programmed, the 2025 Dakota County Transportation Plan also identifies the extension of CSAH 60 to the east. In 2005, Dakota County reconstructed the CSAH 9/CSAH 60 intersection. The reconstruction project widened CSAH 9 to a four-lane divided roadway and re-built CSAH 60 (west of CSAH 9) to a width compatible with a future four-lane divided roadway extension. Dakota County is seeking to identify the appropriate future intersection design and traffic control device; and to also identify interim strategies to manage traffic growth at this intersection prior to the extension project.

The purpose of this Intersection Traffic Control Feasibility Study is to:

- Document the existing geometric, traffic operation and safety characteristics.
- Document and develop the future year 2030 traffic forecasts based upon the Metropolitan Council, City of Lakeville Transportation Plan and the Dakota County Transportation Plan.

¹ 2025 Dakota County Transportation Plan, July 2004

² City of Lakeville Transportation Plan, October 2008

- Develop conceptual roadway alternatives to accommodate the forecast 2030 traffic demands at both the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections.
- Conduct a traffic operation analysis of each alternative.
- Develop a matrix comparing preliminary cost estimates, right of way and other factors to help determine the most optimal intersection lane geometrics and appropriate level of traffic control.
- Identify the preferred alternatives and document an implementation plan assessing the estimated year a traffic control device change is needed.

1.2 Description of Location

The proposed roadway geometric and traffic control revisions are located at the intersections of CSAH 9 at Highview Avenue and CSAH 9 at CSAH 60 in the City of Lakeville, Dakota County, Minnesota. Generally, the study intersections are located east of Interstate (I)-35W, west of CSAH 23 (Cedar Avenue) south of CSAH 42 and north of CSAH 70. **Figure 1** illustrates the study intersections as well as their proximity to major roadways. The Metropolitan Council year 2007 population estimate for the City of Lakeville is 53,829.


1.3 Technical Advisory Committee

The project was guided by a Technical Advisory Committee (TAC) including representation from the City of Lakeville Engineering and the Dakota County Transportation Department. The role of the TAC was to assist in identifying the project issues, identification of alternatives, provide input on the alternatives analysis and to provide input regarding the preferred alternatives and recommendations. Three TAC meetings were held over the course of the project.

1.4 Elements of Study

The following elements are included in the Intersection Traffic Control Feasibility Study:

- Existing Conditions (Section 2.0)
- Future Conditions (Section 3.0)
- Analysis of Alternatives (Section 4.0)
- Recommendations (Section 5.0)
- Appendices (Section 6.0)



Study Intersections

Intersection Traffic Control Feasibility Study



Alliant Engineering

**Figure 1
Project Location**

2.0 Existing Conditions

The following sections document the existing conditions.

2.1 Existing Roadway and Traffic Control Characteristics

The existing roadway characteristics are summarized below:

- **CSAH 9.** CSAH 9 serves as an “A Minor Expander” roadway and generally consists of an undivided two lane section. CSAH 9 has a rural roadway design with an approximate six foot paved shoulder. Exclusive right turn lanes are provided at most major street intersections. At CSAH 60, CSAH 9 has been widened to a four-lane undivided roadway with exclusive turn lanes. The posted speed limit along the length of CSAH 9 is 55 miles per hour (mph).
- **Highview Avenue.** Highview Avenue is a two-lane undivided “Major Collector” roadway with no exclusive turn lanes. Highview Avenue has a rural roadway design averages approximately two to four foot gravel shoulders. North of CSAH 9, Highview Avenue serves residential neighborhood street intersections, has exclusive right turn lanes at major intersections and has a posted 45 mph speed limit. South of CSAH 9, Highview Avenue serves rural land uses, has no exclusive turn lanes and a posted speed limit of 55 mph.
- **CSAH 60.** CSAH 60 is a four-lane divided roadway with an “A Minor Expander” classification and an urban roadway design. Local access control is managed along the corridor and exclusive left and right turn lanes are provided at all major intersections. The posted speed limit is 45 mph.

Currently, both the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections are all-way stop controlled. The existing intersection lane geometrics and traffic control are illustrated in **Figure 2**.

2.2 Right of Way

Right of way and parcel property information was provided by Dakota County. The purpose of the right of way is to document the cross-sectional width available for infrastructure improvements at each intersection. To the extent feasible, future design alternatives and conceptual layouts will be developed within the right of way to minimize environmental and land acquisition impacts. However, where this is not possible, the

comparison of the right of way needs between each alternative will serve as a useful objective.

The right of way provided at the CSAH 9/CSAH 60 intersection varies between sources – Dakota County GIS Property Records versus the recent CSAH 9/CSAH 60 reconstruction project. An accurate depiction of the existing right of way will require a full survey. However, for the purposes of the Intersection Traffic Control Feasibility Study, the existing right of way at the CSAH 9/CSAH 60 intersection is estimated based on as-built design drawings. It is not the intention this study be used as the sole basis for determining exact right of way acquisition needs, but rather to assess the estimated impacts and to itemize the potential needs.

2.3 Existing Traffic Volumes

Dakota County provided the existing AM and PM peak hour intersection turning movement volumes and the hourly approach volumes for both the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections. The CSAH 9 and Highview Avenue data was collected in June 2007 and the CSAH 9/CSAH 60 intersection data was collected in July 2007 (PM peak) and October 2007 (AM Peak). The existing AM and PM peak hour intersection turning movement volumes are shown in **Figure 3**.

The City of Lakeville and Dakota County record and tabulate the Average Daily Traffic (ADT) volumes at locations along CSAH 9, CSAH 60 and Highview Avenue. The ADT volumes consist of the seasonally adjusted total two-way 24-hour traffic volume. **Table 1** documents the existing year 2007 ADT for the key roadway segments within the study area.


Table 1. Existing Year 2007 ADT Volumes

| Roadway | Segment | Existing 2007 |
|------------------------|---|---------------|
| CSAH 9 | 195th Street to CSAH 60 | 8,700 |
| CSAH 9 | CSAH 60 to Highview Avenue | 11,200 |
| CSAH 9 | Highview Avenue to CSAH 23 (Cedar Avenue) | 11,800 |
| CSAH 60 | West of CSAH 9 | 7,600 |
| CSAH 60 | East of CSAH 9 | -- |
| Highview Avenue | North of CSAH 9 | 5,100 |
| Highview Avenue | South of CSAH 9 | 3,100 |

Source: Dakota County Transportation Department



CSAH 9 (Dodd Blvd) at CSAH 60 (185th St)



CSAH 9 (Dodd Blvd) at Highview Avenue





Figure 2
*Existing Lane Geometrics
and Traffic Control*



*Source: Year 2007 Raw Data, Dakota County Public Works

XX/XX AM Peak Hour Volume/PM Peak Hour Volume



2.4 Existing Crash Experience

Dakota County provided crash data for the dates between January 2005 and December 2007. Based on the crash data provided there have been zero reported crashes at the CSAH 9/CSAH 60 intersection. At the CSAH 9/Highview Avenue intersection there have been two reported crashes and one deer hit. The crashes included the following contributing factors:

- Crash 1. Crash 1 involved three motor vehicles. The southbound right turn motorist violated the traffic control device and right angled an eastbound and westbound vehicle.
- Crash 2. An eastbound vehicle lost control and struck a fixed object. Road conditions were dry and the crash occurred during daylight hours.
- Deer Hit. A northbound vehicle struck a deer. Road conditions were dry and the crash occurred during night-time hours.

The crash diagram for CSAH 9/Highview Avenue intersection is provided in **Appendix A**.

A key factor in the safety analysis is the crash rate. The crash rate for any intersection is defined as the number of crashes occurring per million entering vehicles (MEV). **Table 2** summarizes the existing crash rate for each intersection compared to the statewide average for similar traffic control types. Although three total crashes occurred at the CSAH 9/Highview Avenue intersection, only two are considered correctable crashes and included in the crash rate calculation. Dakota County does not consider deer hit crashes to be correctable through engineering resources; therefore, are not included.

Table 2. 2005 - 2007 Crash Rate Summary

| Intersection | Total Crashes ¹ | MEV | Crash Rate | Statewide Average ² |
|---------------------------|----------------------------|------------|------------|--------------------------------|
| CSAH 9 at CSAH 60 | 0 | 16,861,905 | 0.00 | 0.60 |
| CSAH 9 at Highview Avenue | 2 | 19,659,630 | 0.10 | 0.60 |

MEV - Million Entering Vehicles

¹ Source: Dakota County Transportation Department, 2005-2007

² Source: Traffic Safety Fundamentals Handbook p. A-15, August 2008

The review of the existing crash experience and intersection crash rates finds both the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections are operating significantly better than the statewide average. An existing safety hazard or crash pattern at either intersection currently does not exist.

2.5 Key Design Considerations

Based on a review of the existing intersection characteristics, the following summarizes several key geometric or design considerations needed to be evaluated as part of the alternatives analysis. The following existing geometric and design considerations at the CSAH 9/Highview Avenue intersection include:

- The CSAH 9/Highview Avenue intersection is currently located atop a crest vertical curve. All four approaches to the intersection approach with an uphill grade. The northbound and eastbound directions approach with a fairly moderate slope. The Highview Avenue approach grades may reduce sightline visibility of oncoming motorists.
- Eastbound CSAH 9 approaches Highview Avenue on a horizontal curve. The horizontal curve coupled with the vertical profile reduces sightlines for northbound Highview Avenue motorists looking to the west.
- CSAH 9 and Highview Avenue currently intersect at a skew. Significant right of way exists in the northwest quadrant of the intersection, which will allow for realignment.
- Significant grade change exists in the southeast quadrant and may be a factor in developing appropriate clear zone slopes.
- An existing single-family residential home exists in the southwest quadrant. Intersection design and alignments should look to minimize impact to the property. Reconstruction of the driveway access may need to be required.

The following existing geometric and design considerations at the CSAH 9/CSAH 60 intersection include:

- The CSAH 9/CSAH 60 intersection was reconstructed in 2005. The reconstruction rebuilt both roadways to a four-lane divided cross-section with exclusive turn lanes. CSAH 60 was built to be compatible with a future four-lane divided roadway extension to the east.
- The re-use of existing pavement and curbs should be maximized.

3.0 Future Conditions

As identified in Dakota County's 2008-2012 Capital Improvement Plan, Dakota County is currently preparing preliminary engineering documents for the reconstruction of CSAH 9 between 183rd Street and Hayes Avenue. In addition, the City of Lakeville is in the process of finalizing their 2030 Transportation Plan. Based on these documents and the 2025 Dakota County Transportation Plan, several infrastructure and demographic changes are anticipated over the next 20 years. A few key items include:

- Reconstruction of CSAH 9 to a four-lane divided roadway between 183rd Street and Hayes Avenue. Construction is anticipated to begin in 2010.
- Extension of CSAH 60 to the east. Although not currently programmed for construction, the extension project is expected to occur prior to 2030.
- Over the next 20 years, the City of Lakeville is estimating their population will increase by 50 percent² and the number of households and number of persons employed within the City will double².

The increase in vehicle traffic and re-distribution of traffic patterns resulting from the expected infrastructure projects and demographic changes will influence the long term operation of the existing CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections.

The Intersection Traffic Control Feasibility Study evaluates intersection geometric and traffic control needs based upon the forecast year 2010 and 2030 design horizons.

3.1 ADT and Background Traffic Forecasts

Several forecast ADT volumes have been developed for CSAH 9 and the key study intersections. Forecasts are available through the Metropolitan Council, the 2025 Dakota County Transportation Plan and the City of Lakeville Transportation Plan. The forecasts were developed based upon population, land use and employment assumptions. **Table 4** compares the available background forecast ADT volumes.

² City of Lakeville Transportation Plan, October 2008

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Table 3. Comparison of Background 2030 Forecast ADT Volumes

| Roadway | Segment | County/City Forecast Models | | | |
|------------------------|---|-----------------------------|-------------------------------------|-----------------------------------|---|
| | | Existing | Dakota County Forecast ¹ | Met Council Forecast ² | City of Lakeville Forecast ³ |
| | | 2007 | 2025 | 2030 | 2030 |
| CSAH 9 | 195th Street to CSAH 60 | 8,700 | 15,000 | 14,200 | -- |
| CSAH 9 | CSAH 60 to Highview Avenue | 11,200 | 17,100 | 15,600 | 27,000 |
| CSAH 9 | Highview Avenue to CSAH 23 (Cedar Avenue) | 11,800 | 17,800 | 12,400 | 21,000 |
| CSAH 60 | West of CSAH 9 | 7,600 | 24,500 | 17,100 | 29,000 |
| CSAH 60 | East of CSAH 9 | -- | 14,700 | 9,400 | 18,000 |
| Highview Avenue | North of CSAH 9 | 5,100 | -- | 8,800 | 6,700 |
| Highview Avenue | South of CSAH 9 | 3,100 | -- | 5,700 | 6,700 |

¹ 2025 Forecasts Provided by Dakota County Transportation Department. (2025 Transportation Plan)

² 2030 Forecasts provided by Metropolitan Council and assume a 2-lane undivided minor arterial for the CSAH 60 extension

³ 2030 Forecasts provided by City of Lakeville 2030 Transportation Plan, October 2008.

After review of the background traffic forecasts and discussion with the TAC, Dakota County directed Alliant Engineering to use the 2025 Dakota County Traffic forecasts. The annualized background growth rate was used in determination of the 2010 forecast ADT and the State Aid Project Factor (annualized growth rate of 2.3 percent per year) was used to extrapolate the 2025 ADT forecasts to year 2030. **Table 5** documents the forecast year 2010 and 2030 ADT volumes and the segment annualized background growth rates used in the Intersection Traffic Control Feasibility Study.

Table 4. Forecast Year 2010 and 2030 ADT Volumes

| Roadway | Segment | Forecast | | MnDOT State Aid 20 Year Projection Factor | Annual Growth Rate |
|------------------------|---|-----------------------|-----------------------|---|--------------------|
| | | Forecast ² | Forecast ³ | | |
| | | 2010 | 2030 | | |
| CSAH 9 | 195th Street to CSAH 60 | 9,500 | 16,870 | 1.6 | 2.9% |
| CSAH 9 | CSAH 60 to Highview Avenue | 12,100 | 19,230 | 1.6 | 2.4% |
| CSAH 9 | Highview Avenue to CSAH 23 (Cedar Avenue) | 12,700 | 20,000 | 1.6 | 2.3% |
| CSAH 60 | West of CSAH 9 ¹ | 8,300 | 27,500 | 1.6 | 2.8% |
| CSAH 60 | East of CSAH 9 | -- | 16,500 | -- | -- |
| Highview Avenue | North of CSAH 9 | 5,300 | 6,700 | 1.4 | 1.2% |
| Highview Avenue | South of CSAH 9 | 3,500 | 6,700 | 1.4 | 3.4% |

¹ Annual growth rate (pre-CSAH 60 extension) is based upon the average annual growth rate for CSAH 9

² Year 2010 ADT based upon annual growth rate between 2025 and year 2007.

³ Year 2030 ADT based upon 1.6 Project Factor (2.3% per year) growth applied between year 2025 and 2030.

3.2 Forecast Peak Hour Intersection Traffic Volumes

Forecast AM and PM peak hour intersection turning movement volumes were developed for the following conditions:

- Year 2010 (Without CSAH 60 Extension)
- Year 2030 (Without CSAH 60 Extension)
- Year 2030 (With CSAH 60 Extension)

At Highview Avenue, the forecast year 2010 and 2030 intersection traffic volumes were obtained by applying the intersections annualized growth rate to each of the movements. At CSAH 60, the forecast year 2010 and 2030 (without CSAH 60 extension) were developed in a similar manor. The intersections annualized growth rate was applied to each movement. To develop the year 2030 (with CSAH 60 extension) intersection volumes, the following general process was followed for both the AM and PM peak hours:

- The forecast 2030 segment ADT was converted to an hourly inbound/outbound flow by applying the existing peak hour factor (i.e., PM peak represents between 8 and 10 percent of the daily) and the existing directional factor.
- The individual turn movements were estimated by developing percentages for each movement based upon the proportions of each approaches inbound and outbound volumes (determined in previous step).
- Since the forecast ADT volumes do not balance at the intersection, the movement volumes were modified slightly to better balance the turn proportions. A key consideration included reducing illogical movements. For example, the southbound left turn and the westbound right turn are expected to be lower volumes, as both movements produce back tracking routes; therefore, they were reduced. The eastbound right turn movement was also reduced, as the current volume likely reflects motorists using 190th Street or 202nd Street, where the CSAH 60 extension may become a more attractive route for the east or southeast bound trips.

The forecast year 2010 AM and PM peak hour intersection turning movement volumes used in the traffic operation analysis are illustrated in **Figure 4**. The forecast year 2030 AM and PM peak hour intersection turning movement volumes without the CSAH 60 extension are illustrated in **Figure 5**. The forecast year 2030 AM and PM peak hour intersection turning movement volumes with the CSAH 60 extension are illustrated in **Figure 6**.


3.3 Forecast Hourly Approach Volumes

Forecast year 2010 and 2030 hourly approach volumes were developed for use with the signal warrant analysis. The following methodology was used to develop the hourly approach volumes:

- Existing hourly approach counts were obtained from Dakota County. The existing hourly volume distribution percentages were assumed constant for each approach under all forecast years.
- The annualized background growth rate (see Table 5) was applied to each approach and the existing hourly volume distribution to obtain the forecast year 2010 and 2030 volumes.
- The right turn volumes were factored out on minor street approaches with exclusive right turn lanes based upon the recommended procedures documented in *Mn/DOT Technical Memorandum 07-02-T-01*³. Reductions were made to the hourly volumes by applying the respective AM or PM peak hour right turn movement volume percentage.


The forecast year 2010 and 2030 hourly approach volumes for use in the signal warrant analysis are provided in **Appendix B**.

³ Technical Memorandum 07-02-T-01, Mn/DOT Engineering Services Division, Intersection Control Evaluation, March 2007




XX/XX AM Peak Hour Volume/PM Peak Hour Volume





XX/XX AM Peak Hour Volume/PM Peak Hour Volume





XX/XX AM Peak Hour Volume/PM Peak Hour Volume



4.0 Analysis of Alternatives

Traffic control alternatives and conceptual layouts were analyzed to coincide with the proposed CSAH 9 reconstruction project (year 2010) and a long term forecast horizon (year 2030). As part of the alternatives analysis, the following was completed:

- Signal warrant analysis completed to assess if a change in traffic control to a traffic signal system may be an appropriate alternative.
- Safety analysis was conducted to compare the relative safety difference between each traffic control alternative.
- Development of conceptual geometric layouts
- A traffic operation analysis to assess the performance of each conceptual alternative.
- Development of a comparison matrix to evaluate the concept layout alternatives.

4.1 Traffic Control Alternatives

The following documents the three traffic control alternatives considered for the study area.

- All-way Stop Control.
- Traffic Signal Control.
- Roundabout.

Other intersection control treatments or non-traditional intersection geometric design configurations (e.g., continuous flow, median U-turns or grade separation) were not considered. The installation of traditional intersection control and design (all-way stop, traffic signal or roundabout) are expected to provide sufficient capacity.

4.1.1 Signal Warrant Analysis

A traffic signal warrant analysis was performed to determine the feasibility of installing a traffic signal at the intersections of CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections. The warrant analysis is conducted in accordance with the *Minnesota*

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

*Manual on Uniform Traffic Control Devices (MMUTCD)*⁴. The following are the eight MMUTCD traffic signal warrants:

- Warrant 1 – Eight Hour Vehicle Volume
- Warrant 2 – Four-hour Vehicle Volume
- Warrant 3 – Peak Hour Volume
- Warrant 4 – Pedestrian Volume
- Warrant 5 – School Crossing
- Warrant 6 – Coordinated Signal System
- Warrant 7 – Crash Experience
- Warrant 8 – Roadway Network

Warrant 1, Warrant 2 and Warrant 3 were reviewed using the year 2010 and year 2030 forecast hourly approach volumes (see **Appendix B**). The remaining warrants (Warrant 4 to Warrant 8) were not reviewed, since most do not apply or insufficient data is available to conduct an appropriate analysis. **Table 5** and **Table 6** present a summary of the MMUTCD warrant analysis results for the forecast year 2010 and year 2030 at the CSAH 9/Highview and CSAH 9/CSAH 60 intersections, respectively. The detailed signal warrant analysis results are included in **Appendix C**.

Table 5. Signal Warrant Analysis Result Summary – CSAH 9 at Highview Avenue

| Scenario | Warrant 1 - Eight Hour Vehicle Volume | | | | Warrant 2 - Four Hour Volume | | Warrant 3 - Peak Hour Volume | | |
|--------------------|---------------------------------------|------------|------------|-----------------------|------------------------------|-----------------------|------------------------------|------------|-----------------------|
| | 1A (Hours) | 1B (Hours) | 1C (Hours) | Warrant Met / Not Met | Hours | Warrant Met / Not Met | 3A ¹ (Hours) | 3B (Hours) | Warrant Met / Not Met |
| Year 2010 Forecast | 2 Hours | 14 Hours | 3 Hours | Met (1B) | 4 Hours | Met | NA | 2 Hours | Met |
| Year 2030 Forecast | 13 Hours | 15 Hours | 14 Hours | Met (1A, 1B, 1C) | 15 Hours | Met | NA | 14 Hours | Met |

¹ Warrant 3A was not evaluated, since the requirement of Warrant 3B and other warrants were satisfied.

Source: 2005 Minnesota Manual on Uniform Traffic Control Devices

Table 6. Signal Warrant Analysis Result Summary – CSAH 9 at CSAH 60

| Scenario | Warrant 1 - Eight Hour Vehicle Volume | | | | Warrant 2 - Four Hour Volume | | Warrant 3 - Peak Hour Volume | | |
|--|---------------------------------------|------------|------------|-----------------------|------------------------------|-----------------------|------------------------------|------------|-----------------------|
| | 1A (Hours) | 1B (Hours) | 1C (Hours) | Warrant Met / Not Met | Hours | Warrant Met / Not Met | 3A ¹ (Hours) | 3B (Hours) | Warrant Met / Not Met |
| Year 2010 Forecast | 14 Hours | 12 Hours | 14 Hours | Met (1A, 1B, 1C) | 14 Hours | Met | NA | 4 Hours | Met |
| Year 2030 Forecast (Without CSAH 60 Extension) | 17 Hours | 16 Hours | 16 Hours | Met (1A, 1B, 1C) | 16 Hours | Met | NA | 16 Hours | Met |
| Year 2030 Forecast (With CSAH 60 Extension) | 17 Hours | 16 Hours | 16 Hours | Met (1A, 1B, 1C) | 16 Hours | Met | NA | 16 Hours | Met |

¹ Warrant 3A was not evaluated, since the requirement of Warrant 3B and other warrants were satisfied.

Source: 2005 Minnesota Manual on Uniform Traffic Control Devices

⁴ Minnesota Manual on Uniform Traffic Control Devices, May 2005.

As shown above, Warrant 1B, Warrant 2 and Warrant 3 are met at the CSAH 9/Highview Avenue intersection under forecast year 2010 approach volumes. Under the forecast year 2030 approach volumes, Warrant 1A, 1B, 1C, 2 and 3 are expected to be met. At the CSAH 9/CSAH 60 intersection Warrant 1A, 1B, 1C, 2 and 3 are expected to be met under both the forecast year 2010 and year 2030 approach volumes. Although signal warrants are met under the forecast 2010 approach volumes, this alone may not justify the immediate installation of a traffic signal system. Other considerations, including a capacity analysis, will be made to determine the appropriate control device and the estimated year a traffic signal installation would be required (see Section 4.1.1).

4.1.2 Safety Analysis

The forecast year 2030 ADT volumes and the standard average crash rates by control type were used to estimate the annual numbers of crashes for each traffic control alternative. Based on the *Traffic Safety Fundamentals Handbook*⁵, the statewide average crash rate is 0.6 crashes per MEV for an all-way stop control and 0.8 crashes per MEV for a traffic signal. The *Federal Highway Administration (FHWA) Roundabouts: An Information Guide*⁶ documents the safety experience of roundabout intersections through research and before and after studies. According to the FHWA Roundabout Information Guide a roundabout has been found to reduce the total intersection crashes by approximately 40 percent compared to traditional intersections and control. Therefore, a standard intersection crash rate of 0.48 crashes per MEV is used in the safety analysis. **Table 7** compares the estimated crashes per year expected with each traffic control device at the CSAH 9/Highview Avenue intersection. **Table 8** compares the estimated crashes per year expected with each traffic control device at the CSAH 9/CSAH 60 intersection.

Table 7. Forecast Annual Crash Comparison – CSAH 9 at Highview Avenue

| Alternative | Existing Average Crashes / Year ¹ | Existing Crash Rate | Statewide Average Crash Rate ² | Projected Crashes / Year (2030) |
|----------------|--|---------------------|---|---------------------------------|
| All-Way Stop | 1 | 0.10 | 0.60 | 1 - 6 ³ |
| Traffic Signal | -- | -- | 0.80 | 8 |
| Roundabout | -- | -- | 0.48 | 5 |

¹ Source: Dakota County Transportation Department, 2005-2007

² Source: Traffic Safety Fundamentals Handbook p. A-15, August 2008. Roundabout crash rates are approximately 40% of a traffic signal based on data provided in Roundabouts Informational Guide, FHWA Publication No. FHWA-RD-00-067

³ This intersection has had 2 correctable crashes for the years 2005-2007. The existing crash rate is 0.10 compared to the statewide average rate of 0.6. Using the existing crash rate of 0.10 and the statewide average rate of 0.6, the range of expected yearly crashes is 1 to 6.

⁵ Traffic Safety Fundamentals Handbook, August 2008

⁶ Roundabouts: An Information Guide, FHWA, Publication No. FHWA-RD-00-067, June 2000

Table 8. Forecast Annual Crash Comparison – CSAH 9 at CSAH 60

| Alternative | Existing Average Crashes / Year ¹ | Existing Crash Rate | Statewide Average Crash Rate ² | Projected Crashes / Year (2030) |
|------------------------------------|--|---------------------|---|---------------------------------|
| All-Way Stop (Without Extension) | 0 | 0.00 | 0.60 | 0 - 7 ³ |
| Traffic Signal (Without Extension) | -- | -- | 0.80 | 9 |
| Roundabout (Without Extension) | -- | -- | 0.48 | 6 |
| All-Way Stop (With Extension) | -- | -- | 0.60 | 0 - 9 ³ |
| Traffic Signal (With Extension) | -- | -- | 0.80 | 12 |
| Roundabout (With Extension) | -- | -- | 0.48 | 7 |

¹ Source: Dakota County Transportation Department, 2005-2007

² Source: Traffic Safety Fundamentals Handbook p. A-15, August 2008. Roundabout crash rates are approximately 40% of a traffic signal based on data provided in Roundabouts Informational Guide, FHWA Publication No. FHWA-RD-00-067

³ This intersection has had 0 reported crashes for the years 2005-2007. The existing crash rate is 0 compared to the statewide average rate of 0.6. Using the existing crash rate and the statewide average rate, the range of expected yearly crashes is 0 to 7 or 0 to 9.

Although the comparison of the projected crashes per year for each traffic control device are estimated based upon the statewide average rate, the actual intersection crash rate is expected to be less. The historical intersection crash experience, and the anticipated geometric design features (e.g., provision of turn lanes and acceptable sight lines) and using current design standards lends to this conclusion. **Table 9** provides a summary comparison of the key crash types and crash severity expected with each traffic control type.

Table 9. Crash Type and Crash Severity Comparison by Traffic Control Device

| | All-way Stop ¹ | Traffic Signal ¹ | Roundabout ² |
|-----------------------|--|--|--|
| Crash Types | <ul style="list-style-type: none"> Most common crash types are rear end and right angle | <ul style="list-style-type: none"> Predominant crash types are rear end, right angle and left turn collisions | <ul style="list-style-type: none"> Most common crash types include failure to yield at entry and single-vehicle run off road. |
| Crash Severity | <ul style="list-style-type: none"> Injury related crashes represent approximately 30% of the total reported intersection crashes. | <ul style="list-style-type: none"> Injury related crashes represent approximately 35% of the total reported intersection crashes. | <ul style="list-style-type: none"> Injury related crashes are typically reduced by 50% compared to traditional intersections. |

¹ Traffic Safety Fundamentals Handbook, August 2008.

² Roundabouts: An Information Guide, FHWA, Publication No. FHWA-RD-00-067, June 2000

The crash severity at roundabout intersections is often reduced due to the slower vehicle speeds forced by the yield at entry and geometric characteristics and the conflicts being changed from high-speed crossing maneuvers to low-speed merging conflicts.

4.2 Concept Layout Alternatives

Utilizing the forecast 2030 PM peak hour volumes, a screening analysis was completed to identify the required intersection lane geometrics and to assess the initial feasibility for each traffic control device. In addition to the traffic operation review, minimum intersection geometry guidelines were also employed based upon roadway speed and design characteristics (e.g., shoulders, turn bay lengths and minimum approach lanes). In developing the conceptual layouts a number of key considerations were made:

- Each conceptual layout was preliminary engineered in accordance with the requirements and guidelines specified in the *Mn/DOT Road Design Manual*⁷.
- An urban roadway design is assumed.
- Sidewalk and pedestrian curb ramps are to be located on each corner of each intersection.
- Intersections are designed to accommodate a WB-62 truck.
- The conceptual layouts and roadway alignments were developed to best balance operational performance, safety, right of way and construction costs.

A total of two concept layout alternatives were developed at the CSAH 9/Highview Avenue intersection:


- **Concept Layout 1a – Roundabout.** The minimum geometrics were found to require a multi-lane roundabout containing two circulatory lanes with two lanes of approach along CSAH 9 and one lane of approach on Highview Avenue. The CSAH 9/Highview Avenue Concept Layout 1a is illustrated in **Figure 7**.
- **Concept Layout 2a – Four-lane divided roadway with exclusive turn lanes.** Concept Layout 2a would employ either an all-way stop control or traffic signal system and is consistent with the Dakota County 2008-2012 Capital Improvement Plan project. Four lanes of approach (including left and right turn lanes) would be provided along CSAH 9 in each direction and three lanes of approach along Highview Avenue (including left and right turn lanes). Protected left turn signal phasing and eight-phase operation was evaluated under the traffic signal control. Typically protected left turn phases are provided with roadway approaches exceeding 50 mph. However, if sight lines are acceptable, protected/permissive phasing should be used. If this option were to move into final design and upon development of final roadway profiles, the sight lines should be further reviewed for phasing determination. The CSAH 9/Highview Avenue Concept Layout 2a is illustrated in **Figure 8**.

⁷ Mn/DOT Road Design Manual, Part I and Part II

A total of four concept layout alternatives were developed at the CSAH 9/CSAH 60 intersection:


- **Concept Layout 1b – Interim.** Concept Layout 1b would employ either an all-way stop control or traffic signal system during the interim period before CSAH 60 is extended. The eastbound approach would be re-stripped to provide a double left turn lane. No other geometric changes would occur at the intersection. The CSAH 9/CSAH 60 Concept Layout 1b is illustrated in **Figure 9**. It should be noted, a dual eastbound left turn would not be provided under all-way stop control. Dakota County Staff expressed concern with the potential safety and operation confusion that may be presented under such lane geometrics and the wide intersection.
- **Concept Layout 2b – Four-lane divided roadway with double eastbound left turn.** Concept Layout 2b would employ a traffic signal system following the extension of CSAH 60. CSAH 9 and CSAH 60 would be four-lane divided roadways with exclusive left and right turn lanes. The eastbound approach would include a double left turn lane. In accordance with the Mn/DOT Protected Only Left Turn Phasing Guidelines⁸, the dual left turn lane requires protected left turn signal phasing. Eight phase operation and protected left turn phasing is assumed in the traffic analysis. In addition, a southbound right turn overlap phase (operate concurrent with eastbound left turn phase) is included. The CSAH 9/CSAH 60 Concept Layout 2b is illustrated in **Figure 10**.
- **Concept Layout 3b – Four-lane divided roadway with single eastbound left turn.** Concept Layout 3b would employ either an all-way stop control or traffic signal system following the extension of CSAH 60. CSAH 9 and CSAH 60 would be four-lane divided roadways with exclusive left and right turn lanes. Eight phase signal operation is used in the traffic analysis. To efficiently operate a single left turn lane, eastbound/westbound protected/permissive left turn signal phasing would be used. In addition, a southbound right turn overlap phase (operate concurrent with eastbound left turn phase) is included. If sightlines are maintained with the CSAH 60 extension, the protected/permissive phasing will meet most requirements of the Mn/DOT Left Turn Phasing Guidelines. Based on the 2030 traffic volume forecasts, the combination of the left turn/opposing through volume and the 45 mph posted speed may violate the guidelines. The CSAH 9/CSAH 60 Concept Layout 3b is illustrated in **Figure 11**.
- **Concept Layout 4b – Roundabout.** The minimum geometrics were found to require a multi-lane roundabout containing two circulatory lanes with two lanes of approach along both CSAH 9 and CSAH 60. The CSAH 9/CSAH 60 Concept Layout 4b is illustrated in **Figure 12**.


⁸ Mn/DOT Signal Design Manual, Chapter 2. Traffic Signal Phasing and Operations, Section 2.3.2, June 2008.





INTERSECTION TRAFFIC CONTROL FEASIBILITY STUDY


FIGURE 7
CONCEPT LAYOUT 1a
CSAH 9 & HIGHVIEW AVENUE











Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

4.3 Traffic Operations Analysis

A traffic operation analysis was conducted to evaluate the operational performance of each concept layout versus the forecast 2010 and 2030 traffic volumes and the traffic control alternatives. **Table 10** and **Table 11** summarize the scenarios evaluated for the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections, respectively. The traffic operation analysis conducted for the CSAH 9/CSAH 60 intersection considered two primary conditions – without the CSAH 60 extension and with the CSAH 60 extension. The CSAH 60 extension was evaluated under only the forecast year 2030 traffic volumes.

Table 10. Analysis Scenarios Summary – CSAH 9 at Highview Avenue

| Analysis Scenario | Forecast Year | Intersection Geometry Condition | Traffic Control Device | Traffic Signal Operation | Concept Layout |
|-------------------|---------------|---|------------------------|--|-------------------|
| 1 | 2007 | Existing | All-way Stop | -- | -- |
| 2 | 2010 | Existing (no-build) | All-way Stop | -- | -- |
| 3 | 2030 | Existing (no-build) | All-way Stop | -- | -- |
| 4 | 2030 | See Concept Layout 2. CSAH 9 - 4-lane divided with turn bays Highview - 2-lane with turn bays | All-way Stop | -- | Concept Layout 2a |
| 5 | 2030 | See Concept Layout 2. CSAH 9 - 4-lane divided with turn bays Highview - 2-lane with turn bays | Traffic Signal | 8-Phase with protected left turn phasing | Concept Layout 2a |
| 6 | 2030 | See Concept Layout 1. Multi-lane roundabout | Roundabout | -- | Concept Layout 1a |
| 7 | 2010 | See Concept Layout 2. CSAH 9 - 4-lane divided with turn bays Highview - 2-lane with turn bays | All-way Stop | -- | Concept Layout 2a |
| 8 | 2010 | See Concept Layout 2. CSAH 9 - 4-lane divided with turn bays Highview - 2-lane with turn bays | Traffic Signal | 8-Phase with protected left turn phasing | Concept Layout 2a |
| 9 | 2010 | See Concept Layout 1. Multi-lane roundabout | Roundabout | -- | Concept Layout 1a |
| 10 | 2010 | Single-lane roundabout | Roundabout | -- | -- |

Table 11. Analysis Scenarios Summary – CSAH 9 at CSAH 60

| Analysis Scenario | Forecast Year | Intersection Geometry Condition | Traffic Control Device | Traffic Signal Operation | Concept Layout |
|---|---------------|---|------------------------|--|-------------------|
| CSAH 9 at CSAH 60 -- Without CSAH 60 Extension | | | | | |
| 1 | 2007 | Existing | All-way Stop | -- | -- |
| 2 | 2010 | Existing (no-build) | All-way Stop | -- | -- |
| 3 | 2010 | Existing (no-build) | Traffic Signal | 4-Phase with protected left turn phasing | -- |
| 4 | 2030 | Existing (no-build) | All-way Stop | -- | -- |
| 5 | 2030 | Existing (no-build) | Traffic Signal | 4-Phase with protected left turn phasing | -- |
| 6 | 2030 | See Concept Layout 1. Existing geometry. Modify eastbound pavement markings to provide a dual left turn. | Traffic Signal | 4-Phase with protected left turn phasing | Concept Layout 1b |

Table 11. Analysis Scenarios Summary – CSAH 9 at CSAH 60 Cont’d

| Analysis Scenario | Forecast Year | Intersection Geometry Condition | Traffic Control Device | Traffic Signal Operation | Concept Layout |
|--|---------------|---|------------------------|---|--------------------------|
| CSAH 9 at CSAH 60 -- With CSAH 60 Extension | | | | | |
| 1 | 2030 | See Concept Layout 3 Existing + westbound approach leg (two thru lanes and turn bays) | All-way Stop | -- | Concept Layout 3b |
| 2 | 2030 | See Concept Layout 2 Existing + Westbound approach leg (two thru lanes and turn bays) + Eastbound double left turn | Traffic Signal | 8-Phase with protected left turn phasing. Southbound right turn is overlap phase with eastbound left turn. | Concept Layout 2b |
| 3 | 2030 | See Concept Layout 3 Existing + westbound approach leg (two thru lanes and turn bays) | Traffic Signal | 8-Phase with eastbound/westbound protected-permissive left turn phasing. Northbound/southbound is protected left turn phasing. Southbound right turn is overlap phase with eastbound left turn. | Concept Layout 3b |
| 4 | 2030 | See Concept Layout 4. Multi-lane roundabout | Roundabout | -- | Concept Layout 4b |

4.3.1 Analysis Tools

The traffic operation analysis performed for the existing conditions and the traffic control/geometric alternatives was conducted using the following tools:







- SimTraffic7.0
- RODEL
- VISSIM5.1

SimTraffic7.0 is a microscopic simulation tool and was used to evaluate the operational performance of the stop controlled and traffic signal control options. SimTraffic7.0 was selected based upon its ability to better replicate the traffic peaking behavior and the operation of an unsignalized intersection. RODEL is the current accepted analysis tool for evaluating roundabouts. RODEL is based upon operational research of existing roundabouts from which empirical relationships between geometric parameters and entering/circulating traffic characteristics have been established to evaluate capacity, delay (LOS) and vehicle queue lengths. VISSIM is a more refined microscopic simulation tool and is gap theory based. VISSIM will be used only if a roundabout is considered a preferred alternative and will be used to validate the geometrics and operational performance.

4.3.2 Level of Service Definition

The term level of service (LOS), as taken from the, *Highway Capacity Manual, 2000 Edition (HCM)*⁹ refers to the ability of an intersection to process traffic volumes. It is defined as the delay to vehicles caused by the traffic control at the intersection. The results of this MOE are typically presented in the form of a letter grade (A-F) that provides a qualitative indication of the operational efficiency or effectiveness. By definition, LOS A conditions represents high-quality operations and LOS F conditions represent very poor operations. The general relationship between delay and LOS are graphically displayed in **Table 12**. The LOS D/E boundary is considered acceptable operating conditions in the Twin Cities Metro Area. Although traffic simulation models arrive at the seconds of delay per vehicle differently than the HCM procedures, the thresholds presented in **Table 12** are applicable.

Table 12. LOS Definition

| Level of Service | Description | Delay per Vehicle (Seconds) | |
|------------------|---|-----------------------------|----------------------------|
| | | Signalized Intersection | Un-signalized Intersection |
| A |  Free Flow. Low volumes and no delays. | 0 - 10 | 0 - 10 |
| B |  Stable Flow. Speeds restricted by travel conditions, minor delays. | >10 - 20 | >10 - 15 |
| C |  Stable Flow. Speeds and maneuverability closely controlled due to higher volumes. | >20 - 35 | >15 - 25 |
| D |  Stable Flow. Speeds considerably affected by change in operating conditions. High density traffic restricts maneuverability, volume near capacity. | >35 - 55 | >25 - 35 |
| E |  Unstable Flow. Low speeds, considerable delay, volume at or slightly over capacity. | >55 - 80 | >35 - 50 |
| F |  Forced Flow. Very low speeds, volumes exceed capacity, long delays with stop and go traffic. | >80 | >50 |

Source: Highway Capacity Manual, 2000 Edition, Transportation Research Board, Exhibit 16-2 for Signalized Intersections and Exhibit 17-2 for Unsignalized Intersections.

4.3.3 Analysis Results

The traffic operation analysis was completed for all scenarios (see **Table 10** and **Table 11**). Intersection movement delays and vehicle queue lengths reported using SimTraffic7.0 represent an average of five recorded random number seeds.

The key Measures of Effectiveness (MOE) evaluated include; movement and overall intersection delay, LOS, and the average and maximum vehicle queue length. The existing year 2007, forecast year 2010 and forecast year 2030 traffic operation analysis results for the CSAH 9/Highview Avenue intersection is shown in **Table 13**, **Table 14**

⁹ Highway Capacity Manual, 2000 Edition, Transportation Research Board

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

and **Table 15**, respectively. The RODEL output for the roundabout scenarios are attached for reference in **Appendix D**.

Table 13. Year 2007 Traffic Analysis Results Summary – CSAH 9 at Highview Avenue

AM Peak Hour

| Intersection | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|-------------------------------------|----------------|-------------|------|-----|-------------|------|-----|-------------|------|-----|-------------|-----|-----|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 1 (Existing Conditions) | LOS | A | B | A | A | B | A | A | B | A | A | A | A | B |
| | Delay (sec) | 8.1 | 13.1 | 6.5 | 8.6 | 13.5 | 6.9 | 5.9 | 10.5 | 4.6 | 5.8 | 9.6 | 3 | 10.4 |
| | Avg Queue (ft) | 50 | 50 | 50 | 52 | 52 | 52 | 29 | 29 | 29 | 22 | 22 | 22 | - |
| | Max Queue (ft) | 116 | 116 | 116 | 116 | 116 | 116 | 86 | 86 | 86 | 51 | 51 | 51 | - |
| | Storage (ft) | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |

PM Peak Hour

| Intersection | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|-------------------------------------|----------------|-------------|------|------|-------------|-----|------|-------------|------|-----|-------------|------|------|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 1 (Existing Conditions) | LOS | D | D | D | F | F | F | A | B | A | C | C | C | E |
| | Delay (sec) | 29.2 | 31.7 | 32.7 | 59.1 | 65 | 51.5 | 7.4 | 14.4 | 6.8 | 21.6 | 22.6 | 17.5 | 36.3 |
| | Avg Queue (ft) | 131 | 131 | 131 | 261 | 261 | 261 | 40 | 40 | 40 | 84 | 84 | 84 | - |
| | Max Queue (ft) | 362 | 362 | 362 | 597 | 597 | 597 | 102 | 102 | 102 | 236 | 236 | 236 | - |
| | Storage (ft) | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |

Note: Analysis results obtained using SimTraffic Software (Average of 5 random seeds)

Table 14. Year 2010 Traffic Analysis Results Summary – CSAH 9 at Highview Avenue

AM Peak Hour

| Alternative | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|---|-----------------|-------------|------|-----|-------------|------|-----|-------------|------|-----|-------------|------|-----|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 2 (No build) | LOS | B | C | A | B | B | A | A | B | A | A | B | A | B |
| | Delay (sec/veh) | 11.1 | 18 | 8.8 | 10.3 | 14.8 | 9.1 | 7.3 | 11.9 | 7.8 | 6.5 | 11 | 3.8 | 13 |
| | Avg Queue (ft) | 64 | 64 | 64 | 57 | 57 | 57 | 38 | 38 | 38 | 27 | 27 | 27 | - |
| | Max Queue (ft) | 216 | 216 | 216 | 162 | 162 | 162 | 130 | 130 | 130 | 80 | 80 | 80 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Scenario 7 (All-Way Stop) Concept Layout 2a | LOS | A | B | A | A | B | A | A | B | A | A | B | A | A |
| | Delay (sec) | 4.2 | 11 | 3.1 | 5.2 | 10.8 | 2.8 | 9 | 10.8 | 8.7 | 9.8 | 10.4 | 7.2 | 9.6 |
| | Avg Queue (ft) | 7 | 29 | 6 | 11 | 30 | 3 | 8 | 13 | 7 | 8 | 12 | 4 | - |
| | Max Queue (ft) | 29 | 59 | 32 | 46 | 62 | 24 | 22 | 53 | 43 | 20 | 39 | 26 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 300 | - | 300 | 150 | - | 150 | - |
| Scenario 8 (Traffic Signal) Concept Layout 2a | LOS | C | B | A | C | B | A | D | C | A | C | C | A | B |
| | Delay (sec/veh) | 30.2 | 11.3 | 1.7 | 27.5 | 10.1 | 1.7 | 35.5 | 25.4 | 9.1 | 34.4 | 28 | 7.9 | 14.9 |
| | Avg Queue (ft) | 12 | 39 | 2 | 25 | 40 | 2 | 10 | 24 | 6 | 11 | 20 | 4 | - |
| | Max Queue (ft) | 60 | 104 | 21 | 104 | 102 | 19 | 39 | 71 | 55 | 53 | 64 | 29 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 300 | - | 300 | 150 | - | 150 | - |
| Scenario 9 (Roundabout) Concept Layout 1a | LOS | A | A | A | A | A | A | A | A | A | A | A | A | A |
| | Delay (sec) | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 3.6 | 3.6 | 3.6 | 3 | 3 | 3 | 2.6 |
| | Avg Queue (ft) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - |
| | Max Queue (ft) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Scenario 10 (1-Lane Roundabout) | LOS | A | A | A | A | A | A | A | A | A | A | A | A | A |
| | Delay (sec) | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 4.2 | 4.3 |
| | Avg Queue (ft) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - |
| | Max Queue (ft) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Table 14. Year 2010 Traffic Analysis Results Summary – CSAH 9 at Highview Avenue – Cont'd

PM Peak Hour

| Alternative | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|---|-----------------|-------------|------|------|-------------|-------|-------|-------------|------|-----|-------------|------|------|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 2 (No build) | LOS | F | F | F | F | F | F | B | C | A | D | D | C | F |
| | Delay (sec/veh) | 54 | 55.4 | 55.9 | 135.2 | 144.6 | 125.3 | 13.2 | 16 | 9 | 28.7 | 29.1 | 22 | 70.5 |
| | Avg Queue (ft) | 231 | 231 | 231 | 569 | 569 | 569 | 45 | 45 | 45 | 107 | 107 | 107 | - |
| | Max Queue (ft) | 495 | 495 | 495 | 1040 | 1040 | 1040 | 127 | 127 | 127 | 287 | 287 | 287 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Scenario 7 (All-Way Stop) Concept Layout 2a | LOS | A | B | A | A | C | A | B | C | A | B | C | B | B |
| | Delay (sec) | 9 | 13.7 | 3.8 | 7.7 | 15.5 | 4.8 | 13.4 | 15.1 | 8.7 | 14.8 | 16 | 10.6 | 13.2 |
| | Avg Queue (ft) | 21 | 40 | 5 | 13 | 49 | 12 | 2 | 22 | 4 | 19 | 27 | 16 | - |
| | Max Queue (ft) | 57 | 87 | 25 | 46 | 107 | 33 | 22 | 64 | 26 | 50 | 84 | 63 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 300 | - | 300 | 150 | - | 150 | - |
| Scenario 8 (Traffic Signal) Concept Layout 2a | LOS | C | B | A | C | B | A | D | C | A | D | C | A | B |
| | Delay (sec/veh) | 33.6 | 15.5 | 2.2 | 33.9 | 19.6 | 3.6 | 43.8 | 27.5 | 8.8 | 40.7 | 23.8 | 9.7 | 20 |
| | Avg Queue (ft) | 51 | 57 | 2 | 27 | 75 | 7 | 3 | 42 | 4 | 28 | 42 | 16 | - |
| | Max Queue (ft) | 128 | 130 | 24 | 88 | 157 | 35 | 26 | 134 | 29 | 76 | 113 | 68 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 300 | - | 300 | 150 | - | 150 | - |
| Scenario 9 (Roundabout) Concept Layout 1a | LOS | A | A | A | A | A | A | A | A | A | A | A | A | A |
| | Delay (sec) | 2.4 | 2.4 | 2.4 | 3 | 3 | 3 | 4.2 | 4.2 | 4.2 | 4.8 | 4.8 | 4.8 | 3.3 |
| | Avg Queue (ft) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 25 | 25 | 25 | - |
| | Max Queue (ft) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 25 | 25 | 25 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Scenario 10 (1-Lane Roundabout) | LOS | A | A | A | A | A | A | A | A | A | A | A | A | A |
| | Delay (sec) | 6 | 6 | 6 | 6 | 6 | 6 | 4.8 | 4.8 | 4.8 | 6.6 | 6.6 | 6.6 | 6 |
| | Avg Queue (ft) | 25 | 25 | 25 | 25 | 25 | 25 | 0 | 0 | 0 | 25 | 25 | 25 | - |
| | Max Queue (ft) | 25 | 25 | 25 | 25 | 25 | 25 | 0 | 0 | 0 | 25 | 25 | 25 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |

¹ Average vehicle delay obtained using SimTraffic 7.0 (Results based upon average of 5 random seeds)

² Roundabout Measures of Effectiveness obtained using Rodet.

Table 15. Year 2030 Traffic Analysis Results Summary – CSAH 9 at Highview Avenue

AM Peak Hour

| Alternative | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|---|-----------------|-------------|-------|-------|-------------|-------|-------|-------------|------|------|-------------|------|-----|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 3 (No build) | LOS | F | F | F | F | F | F | E | F | F | B | C | A | F |
| | Delay (sec/veh) | 230.2 | 198.5 | 200.8 | 162.3 | 111.3 | 103.3 | 43.2 | 53 | 73.1 | 13.7 | 15.8 | 9.3 | 117.8 |
| | Avg Queue (ft) | 763 | 763 | 763 | 504 | 504 | 504 | 194 | 194 | 194 | 48 | 48 | 48 | - |
| | Max Queue (ft) | 1849 | 1849 | 1849 | 1746 | 1746 | 1746 | 681 | 681 | 681 | 100 | 100 | 100 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Scenario 4 (All-Way Stop) Concept Layout 2a | LOS | A | C | A | B | B | A | B | C | B | B | B | A | B |
| | Delay (sec) | 8 | 16 | 4.9 | 11.1 | 14.9 | 4 | 13.1 | 16.6 | 14.8 | 13.7 | 14.1 | 9.4 | 14.2 |
| | Avg Queue (ft) | 12 | 48 | 9 | 20 | 50 | 5 | 9 | 23 | 23 | 14 | 18 | 9 | - |
| | Max Queue (ft) | 44 | 102 | 37 | 92 | 114 | 26 | 23 | 88 | 123 | 45 | 51 | 31 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 300 | - | 300 | 150 | - | 150 | - |
| Scenario 5 (Traffic Signal) Concept Layout 2a | LOS | C | B | A | D | B | A | D | C | B | D | C | A | B |
| | Delay (sec/veh) | 34.9 | 17 | 3.1 | 37.2 | 15.5 | 2 | 46.2 | 27.2 | 12.3 | 37 | 29.9 | 9 | 19.6 |
| | Avg Queue (ft) | 29 | 71 | 5 | 45 | 73 | 2 | 16 | 38 | 21 | 20 | 32 | 8 | - |
| | Max Queue (ft) | 90 | 144 | 27 | 170 | 178 | 20 | 61 | 95 | 110 | 76 | 92 | 39 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 300 | - | 300 | 150 | - | 150 | - |
| Scenario 6 (Roundabout) Concept Layout 1a | LOS | A | A | A | A | A | A | A | A | A | A | A | A | A |
| | Delay (sec) | 2.4 | 2.4 | 2.4 | 3 | 3 | 3 | 4.8 | 4.8 | 4.8 | 4.2 | 4.2 | 4.2 | 3.3 |
| | Avg Queue (ft) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - |
| | Max Queue (ft) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 25 | 25 | 25 | 0 | 0 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Table 15. Year 2030 Traffic Analysis Results Summary – CSAH 9 at Highview Avenue – Cont'd

PM Peak Hour

| Alternative | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|---|-----------------|-------------|-------|-------|-------------|-------|-------|-------------|------|------|-------------|-------|-------|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 3 (No build) | LOS | F | F | F | F | F | F | E | E | E | F | F | F | F |
| | Delay (sec/veh) | 569.6 | 573.1 | 557.1 | 592.6 | 593.5 | 582.7 | 47.4 | 47 | 39.9 | 740.5 | 652.8 | 742.3 | 502.6 |
| | Avg Queue (ft) | 1837 | 1837 | 1837 | 1813 | 1813 | 1813 | 148 | 148 | 148 | 795 | 795 | 795 | - |
| | Max Queue (ft) | 1883 | 1883 | 1883 | 1840 | 1840 | 1840 | 430 | 430 | 430 | 858 | 858 | 858 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Scenario 4 (All-Way Stop) Concept Layout 2a | LOS | D | D | A | F | F | F | C | E | B | D | D | C | F |
| | Delay (sec) | 32.3 | 31 | 7.2 | 290.5 | 497.7 | 275.6 | 17.5 | 36.9 | 14.1 | 27.1 | 33.4 | 19.5 | 157.7 |
| | Avg Queue (ft) | 61 | 97 | 6 | 300 | 1153 | 202 | 4 | 64 | 17 | 33 | 70 | 48 | - |
| | Max Queue (ft) | 145 | 207 | 31 | 400 | 1812 | 400 | 19 | 184 | 79 | 108 | 211 | 146 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 300 | - | 300 | 150 | - | 150 | - |
| Scenario 5 (Traffic Signal) Concept Layout 2a | LOS | D | C | A | D | C | A | E | C | B | D | C | B | C |
| | Delay (sec/veh) | 43.2 | 22.2 | 6.8 | 44.7 | 31.4 | 5.4 | 56 | 34.4 | 11.2 | 51.7 | 30.1 | 15.6 | 28.1 |
| | Avg Queue (ft) | 95 | 112 | 4 | 45 | 166 | 12 | 5 | 78 | 13 | 57 | 90 | 49 | - |
| | Max Queue (ft) | 210 | 191 | 35 | 145 | 291 | 40 | 26 | 200 | 62 | 145 | 253 | 140 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 300 | - | 300 | 150 | - | 150 | 0 |
| Scenario 6 (Roundabout) Concept Layout 1a | LOS | A | A | A | A | A | A | A | A | A | B | B | B | A |
| | Delay (sec) | 3.6 | 3.6 | 3.6 | 3.6 | 3.6 | 3.6 | 6.6 | 6.6 | 6.6 | 10.2 | 10.2 | 10.2 | 5.7 |
| | Avg Queue (ft) | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 50 | 50 | 50 | - |
| | Max Queue (ft) | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 50 | 50 | 50 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |

¹ Average vehicle delay obtained using SimTraffic 7.0 (Results based upon average of 5 random seeds)

² Roundabout Measures of Effectiveness obtained using Rodel.

The following summarizes the results of the traffic operation analysis completed for the CSAH 9/Highview Avenue intersection:

- The existing intersection control (all-way stop) currently operates at an acceptable LOS B during the AM peak hour. During the PM peak hour, the westbound approach operates at a LOS F, with overall intersection operating at a LOS E.
- Under Concept Layout 1a (see **Figure 7**), a roundabout intersection is expected to provide LOS A operations under both the forecast year 2010 and 2030 traffic volumes.
- Under Concept Layout 2a (see **Figure 8**), an all-way stop control is expected to provide acceptable traffic operations under year 2010 volumes. However by year 2030, an all-way stop control is expected to be an insufficient level of traffic control.
- A traffic signal is expected to provide an acceptable LOS C or better under both 2010 and 2030 forecast traffic volumes and Concept Layout 2a.

The traffic operation analysis conducted for the CSAH 9/CSAH 60 intersection considered two primary conditions – without the CSAH 60 extension and with the CSAH 60 extension. The existing year 2007 traffic operation analysis results for the CSAH 9/CSAH 60 intersection are shown in **Table 16**. The forecast year 2010 and 2030 traffic operation results under the without CSAH 60 extension are shown in **Table 17** and **Table 18**, respectively. The forecast year 2030 traffic operation results under the with CSAH 60 extension are shown in **Table 19**. The RODEL output for the roundabout scenarios are attached for reference in **Appendix D**.

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Table 16. Year 2007 Traffic Analysis Results Summary – CSAH 9 at CSAH 60

AM Peak Hour

| Intersection | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|-------------------------------------|-----------------|-------------|-----|-----|-------------|-----|-----|-------------|-----|-----|-------------|------|-----|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 1 (Existing Conditions) | LOS | A | - | A | - | - | - | A | A | - | - | B | A | A |
| | Delay (sec/veh) | 8.4 | - | 2.1 | - | - | - | 6.1 | 9.1 | - | - | 14.3 | 5.1 | 9.0 |
| | Avg Queue (ft) | 54 | - | 24 | - | - | - | 25 | 32 | - | - | 58 | 40 | - |
| | Max Queue (ft) | 113 | - | 41 | - | - | - | 60 | 58 | - | - | 148 | 79 | - |
| | Storage (ft) | 300 | - | 300 | - | - | - | 250 | - | - | - | - | 420 | - |

PM Peak Hour

| Intersection | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|-------------------------------------|-----------------|-------------|-----|-----|-------------|-----|-----|-------------|------|-----|-------------|------|-----|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 1 (Existing Conditions) | LOS | C | - | A | - | - | - | A | B | - | - | C | A | B |
| | Delay (sec/veh) | 22.9 | - | 2.9 | - | - | - | 9.8 | 11.3 | - | - | 18.5 | 5.2 | 14.0 |
| | Avg Queue (ft) | 104 | - | 29 | - | - | - | 33 | 43 | - | - | 73 | 46 | - |
| | Max Queue (ft) | 266 | - | 65 | - | - | - | 76 | 72 | - | - | 168 | 82 | - |
| | Storage (ft) | 300 | - | 300 | - | - | - | 250 | - | - | - | - | 420 | - |

Note: Analysis results obtained using SimTraffic Software (Average of 5 random seeds)

Table 17. Year 2010 Traffic Analysis Results Summary – CSAH 9 at CSAH 60 (Without CSAH 60 Extension)

AM Peak Hour

| Alternative | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|--------------------------------|-----------------|-------------|-----|-----|-------------|-----|-----|-------------|-----|-----|-------------|------|-----|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 2 (No build) | LOS | B | - | A | - | - | - | A | A | - | - | C | A | B |
| | Delay (sec/veh) | 13.6 | - | 6.5 | - | - | - | 5.4 | 9.2 | - | - | 22.6 | 4.8 | 12.5 |
| | Avg Queue (ft) | 50 | - | 25 | - | - | - | 16 | 12 | - | - | 76 | 42 | - |
| | Max Queue (ft) | 115 | - | 47 | - | - | - | 41 | 40 | - | - | 253 | 81 | - |
| | Storage (ft) | 300 | - | 300 | - | - | - | 250 | - | - | - | - | 420 | - |
| Scenario 3 (Traffic Signal) | LOS | B | - | A | - | - | - | C | A | - | - | B | A | B |
| | Delay (sec) | 17.8 | - | 6 | - | - | - | 29.4 | 5.8 | - | - | 16.3 | 2.8 | 11.9 |
| | Avg Queue (ft) | 61 | - | 20 | - | - | - | 23 | 11 | - | - | 81 | 33 | - |
| | Max Queue (ft) | 111 | - | 38 | - | - | - | 70 | 48 | - | - | 206 | 73 | - |
| | Storage (ft) | 300 | - | 300 | - | - | - | 250 | - | - | - | - | 420 | - |

PM Peak Hour

| Alternative | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|--------------------------------|-----------------|-------------|-----|-----|-------------|-----|-----|-------------|------|-----|-------------|------|-----|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 2 (No build) | LOS | F | - | A | - | - | - | B | B | - | - | D | A | D |
| | Delay (sec/veh) | 56.8 | - | 7.9 | - | - | - | 10.9 | 11.5 | - | - | 26.6 | 6.3 | 25.9 |
| | Avg Queue (ft) | 178 | - | 30 | - | - | - | 25 | 20 | - | - | 84 | 49 | - |
| | Max Queue (ft) | 373 | - | 58 | - | - | - | 64 | 52 | - | - | 237 | 104 | - |
| | Storage (ft) | 300 | - | 300 | - | - | - | 250 | - | - | - | - | 420 | - |
| Scenario 3 (Traffic Signal) | LOS | B | - | A | - | - | - | C | A | - | - | B | A | B |
| | Delay (sec) | 18.9 | - | 6.1 | - | - | - | 30 | 7.5 | - | - | 19.2 | 3.6 | 13.5 |
| | Avg Queue (ft) | 86 | - | 25 | - | - | - | 40 | 23 | - | - | 92 | 41 | - |
| | Max Queue (ft) | 153 | - | 44 | - | - | - | 110 | 88 | - | - | 198 | 84 | - |
| | Storage (ft) | 300 | - | 300 | - | - | - | 250 | - | - | - | - | 420 | - |

* Average vehicle delay obtained using SimTraffic 7.0 (Results based upon average of 5 random seeds)

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Table 18. Year 2030 Traffic Analysis Results Summary – CSAH 9 at CSAH 60 (Without CSAH 60 Extension)

AM Peak Hour

| Alternative | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|---|-----------------|-------------|-----|------|-------------|-----|-----|-------------|------|-----|-------------|------|------|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 4 (No build) | LOS | F | - | D | - | - | - | C | B | - | - | F | C | F |
| | Delay (sec/veh) | 324.4 | - | 30.3 | - | - | - | 16.3 | 11.7 | - | - | 61.8 | 17.5 | 102.7 |
| | Avg Queue (ft) | 1092 | - | 35 | - | - | - | 28 | 21 | - | - | 198 | 117 | - |
| | Max Queue (ft) | 1604 | - | 69 | - | - | - | 81 | 51 | - | - | 547 | 435 | - |
| Scenario 5 (Traffic Signal) | LOS | C | - | B | - | - | - | D | D | - | - | D | A | C |
| | Delay (sec) | 34.4 | - | 13.4 | - | - | - | 40.6 | 51.4 | - | - | 51.4 | 8.3 | 29 |
| | Avg Queue (ft) | 211 | - | 29 | - | - | - | 44 | 34 | - | - | 210 | 72 | - |
| | Max Queue (ft) | 386 | - | 88 | - | - | - | 130 | 104 | - | - | 526 | 294 | - |
| Scenario 6 (Traffic Signal) Concept Layout 1b | LOS | C | - | A | - | - | - | C | A | - | - | C | A | B |
| | Delay (sec/veh) | 23 | - | 8.4 | - | - | - | 30.2 | 7.3 | - | - | 26 | 6.9 | 17.3 |
| | Avg Queue (ft) | 109 | - | 30 | - | - | - | 39 | 22 | - | - | 131 | 61 | - |
| | Max Queue (ft) | 182 | - | 71 | - | - | - | 106 | 72 | - | - | 337 | 150 | - |
| Scenario 6 (Traffic Signal) Concept Layout 1b | Storage (ft) | 300 | - | 300 | - | - | - | 250 | - | - | - | - | 420 | - |

PM Peak Hour

| Alternative | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|---|-----------------|-------------|-----|--------|-------------|-----|-----|-------------|------|-----|-------------|------|------|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 4 (No build) | LOS | F | - | F | - | - | - | F | D | - | - | E | D | F |
| | Delay (sec/veh) | 2278.8 | - | 1725.5 | - | - | - | 193.9 | 28.1 | - | - | 39.1 | 28.3 | 551.6 |
| | Avg Queue (ft) | 1607 | - | 37 | - | - | - | 129 | 135 | - | - | 140 | 163 | - |
| | Max Queue (ft) | 1630 | - | 74 | - | - | - | 232 | 217 | - | - | 402 | 380 | - |
| Scenario 5 (Traffic Signal) | LOS | F | - | E | - | - | - | D | D | - | - | D | A | D |
| | Delay (sec) | 109.2 | - | 69.8 | - | - | - | 45.4 | 49.6 | - | - | 49.6 | 9.7 | 52.8 |
| | Avg Queue (ft) | 357 | - | 44 | - | - | - | 95 | 83 | - | - | 208 | 90 | - |
| | Max Queue (ft) | 400 | - | 108 | - | - | - | 201 | 205 | - | - | 365 | 240 | - |
| Scenario 6 (Traffic Signal) Concept Layout 1b | Storage (ft) | 300 | - | 300 | - | - | - | 250 | - | - | - | - | 420 | - |
| | LOS | C | - | B | - | - | - | D | B | - | - | C | A | C |
| | Delay (sec/veh) | 27.1 | - | 10.1 | - | - | - | 38.9 | 11.5 | - | - | 32.1 | 9.3 | 21.1 |
| | Avg Queue (ft) | 158 | - | 41 | - | - | - | 82 | 64 | - | - | 156 | 88 | - |
| Scenario 6 (Traffic Signal) Concept Layout 1b | Max Queue (ft) | 237 | - | 81 | - | - | - | 184 | 152 | - | - | 305 | 215 | - |
| | Storage (ft) | 300 | - | 300 | - | - | - | 250 | - | - | - | - | 420 | - |

* Average vehicle delay obtained using SimTraffic 7.0 (Results based upon average of 5 random seeds)

Table 19. Year 2030 Traffic Analysis Results Summary – CSAH 9 at CSAH 60 (With CSAH 60 Extension)

AM Peak Hour

| Alternative | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|--|-----------------|-------------|------|------|-------------|------|-----|-------------|------|-----|-------------|------|------|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 1 (All-Way Stop) Concept Layout 3b | LOS | F | D | B | E | D | A | D | B | A | B | E | B | E |
| | Delay (sec/veh) | 141 | 27.4 | 11.9 | 36.8 | 27.3 | 8.4 | 31.2 | 15 | 4.6 | 14.1 | 43.2 | 10.3 | 41.2 |
| | Avg Queue (ft) | 279 | 236 | 39 | 86 | 67 | 14 | 39 | 17 | 12 | 14 | 77 | 46 | - |
| | Max Queue (ft) | 400 | 656 | 74 | 256 | 128 | 42 | 136 | 50 | 46 | 42 | 234 | 164 | - |
| Scenario 2 (Traffic Signal - Protected Lefts) Concept Layout 2b | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 250 | - | 250 | 300 | - | 420 | - |
| | LOS | D | C | B | D | C | A | D | C | A | D | C | A | C |
| | Delay (sec) | 37.6 | 29 | 10.6 | 40.2 | 27 | 9.4 | 36.2 | 22 | 3.1 | 39.7 | 31.4 | 5 | 25.8 |
| | Avg Queue (ft) | 85 | 73 | 33 | 110 | 76 | 11 | 48 | 25 | 9 | 20 | 83 | 30 | - |
| Scenario 3 (Traffic Signal - EB/WB Prot/Perm Left) Concept Layout 3b | Max Queue (ft) | 153 | 134 | 66 | 249 | 143 | 37 | 143 | 71 | 39 | 79 | 188 | 102 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 250 | - | 250 | 300 | - | 420 | - |
| | LOS | C | C | A | C | C | A | D | C | A | D | D | A | C |
| | Delay (sec/veh) | 27 | 24.6 | 9.9 | 23.6 | 28.9 | 8.2 | 39.4 | 27.8 | 2.9 | 47.1 | 38.8 | 5.3 | 24.0 |
| Scenario 4 (Roundabout) Concept Layout 4b | Avg Queue (ft) | 117 | 69 | 31 | 74 | 81 | 11 | 50 | 31 | 9 | 21 | 96 | 31 | - |
| | Max Queue (ft) | 267 | 134 | 61 | 161 | 155 | 38 | 154 | 92 | 66 | 75 | 236 | 88 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 250 | - | 250 | 300 | - | 420 | - |
| | LOS | A | A | A | A | A | A | A | A | A | A | A | A | A |
| Scenario 4 (Roundabout) Concept Layout 4b | Delay (sec) | 3 | 3 | 3 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.4 | 2.7 |
| | Avg Queue (ft) | 25 | 25 | 25 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - |
| | Max Queue (ft) | 25 | 25 | 25 | 0 | 0 | 0 | 0 | 0 | 0 | 25 | 25 | 25 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Table 19. Year 2030 Traffic Analysis Results Summary – CSAH 9 at CSAH 60 (With CSAH 60 Extension) – Cont'd

PM Peak Hour

| Alternative | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|---|-----------------|-------------|--------|--------|-------------|-------|------|-------------|------|------|-------------|------|-------|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| Scenario 1 (All-Way Stop) Concept Layout 3b | LOS | F | F | F | F | F | E | F | E | C | F | F | F | F |
| | Delay (sec/veh) | 1505.7 | 1315.1 | 1037.3 | 115.5 | 201.2 | 49.3 | 645.3 | 41.8 | 23.1 | 717.9 | 882 | 322.9 | 707.7 |
| | Avg Queue (ft) | 393 | 1603 | 301 | 211 | 379 | 83 | 349 | 513 | 32 | 160 | 1361 | 509 | - |
| | Max Queue (ft) | 400 | 1633 | 400 | 379 | 973 | 277 | 350 | 534 | 107 | 400 | 1641 | 520 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 250 | - | 250 | 300 | - | 420 | - |
| Scenario 2 (Traffic Signal - Protected Lefts) Concept Layout 2b | LOS | E | D | C | E | D | B | D | C | B | D | D | C | D |
| | Delay (sec) | 63.3 | 51 | 21.9 | 59.8 | 39.3 | 11.5 | 53.3 | 31.2 | 11.4 | 53.9 | 54.9 | 20.5 | 42.3 |
| | Avg Queue (ft) | 157 | 252 | 58 | 134 | 141 | 15 | 130 | 62 | 46 | 29 | 150 | 161 | - |
| | Max Queue (ft) | 252 | 429 | 268 | 253 | 230 | 46 | 287 | 175 | 148 | 82 | 270 | 371 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 250 | - | 250 | 300 | - | 420 | - |
| Scenario 3 (Traffic Signal - EB/WB Prot/Perm Left) Concept Layout 3b | LOS | E | D | C | D | D | A | E | C | B | E | E | B | D |
| | Delay (sec/veh) | 58.4 | 48.9 | 21.9 | 43.4 | 47 | 9.6 | 68.2 | 34.4 | 14.3 | 67.3 | 61.4 | 17.7 | 43.0 |
| | Avg Queue (ft) | 267 | 259 | 58 | 103 | 161 | 15 | 152 | 66 | 53 | 32 | 165 | 143 | - |
| | Max Queue (ft) | 399 | 484 | 272 | 222 | 274 | 34 | 310 | 210 | 178 | 104 | 306 | 346 | - |
| | Storage (ft) | 300 | - | 300 | 300 | - | 300 | 250 | - | 250 | 300 | - | 420 | - |
| Scenario 4 (Roundabout) Concept Layout 4b | LOS | B | B | B | A | A | A | A | A | A | A | A | A | A |
| | Delay (sec) | 11.4 | 11.4 | 11.4 | 3.6 | 3.6 | 3.6 | 6 | 6 | 6 | 4.2 | 4.2 | 4.2 | 7.4 |
| | Avg Queue (ft) | 125 | 125 | 125 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | - |
| | Max Queue (ft) | 150 | 150 | 150 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |

¹ Average vehicle delay obtained using SimTraffic 7.0 (Results based upon average of 5 random seeds)

² Roundabout Measures of Effectiveness obtained using Rodrel.

The following summarizes the results of the traffic operation analysis completed for the CSAH 9/CSAH 60 intersection:

- The existing intersection control (all-way stop) currently operates at an acceptable LOS B or better during both the AM and PM peak hours.
- Prior to the extension of CSAH 60, an all-way stop control is expected to provide acceptable traffic operations (LOS D or better) under the 2010 forecast traffic volumes. By 2030, an all-way stop control will be deficient without geometric improvements.
- The installation of a traffic signal is expected to provide acceptable traffic operations prior to the CSAH 60 extension. A dual eastbound left turn lane will be required to address potential queuing issues. (Concept Layout 1b, **Figure 9**).
- With the extension of CSAH 60 and considering forecast year 2030 traffic volumes, an all-way stop control is an insufficient level of traffic control.
- A traffic signal system is expected to improve the overall intersection operation to a LOS D or better. The type of signal phasing selected for eastbound/westbound CSAH 60 approaches will influence the required intersection geometrics. Protected/permissive left turn phasing is expected to provide acceptable traffic operations and maintains a single left turn lane design (Concept Layout 3b, **Figure 11**). If protected left turn phasing is to be considered, the construction of an eastbound dual left turn lane will be required (Concept Layout 2b, **Figure 10**)
- A multi-lane roundabout is expected to provide LOS A or better traffic operations under the forecast year 2030 traffic volumes.

4.4 Evaluation of Alternatives

The conceptual layouts developed for both the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections were evaluated based upon the following key objectives:

- Operational Efficiency
- Intersection Safety
- Preliminary Cost
- Right of Way Impact
- Utility Impact
- Environmental Impact
- Pedestrian/Bicycle Friendliness
- Other Design Considerations

To support the alternatives evaluation and selection of the preferred alternative, a comparison matrix was developed to quantitatively and qualitatively assess the above listed key objectives. The operational efficiency comparison is based upon 2030 PM peak hour analysis. However, an evaluation was conducted to determine the anticipated year a traffic control change may be needed (see Section 4.4.1). Preliminary costs for comparison purposes were developed for each alternative and are based upon the following key features:

- Removals
- Earthwork
- Roadway Surface Features
- Drainage

Right of way impacts are estimated based upon square foot area of required acquisition. The value per square foot is unknown at this time; therefore, a reasonable quantification of dollar cost cannot be made. However, the area of impact will provide a useful comparison between alternatives. Other design considerations, environmental, utility or pedestrian/bicycle impacts are discussed qualitatively and as appropriate for each alternative.

Table 20 and **Table 21** present the comparison evaluation matrix for each concept layout under consideration at the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections, respectively.

Table 20. Comparison Evaluation Matrix - CSAH 9 at Highview Avenue

| | Objective | 2030 | 2030 | 2030 |
|----------------------|---|--|--|---|
| | | Concept Layout 2a | Concept Layout 2a | Concept Layout 1a |
| | | (All-Way Stop) | (Traffic Signal) | (Roundabout) |
| Operations | Overall Intersection Delay (sec / veh) ¹ LOS | 157.7 F See Footnote (5) | 28.1 C | 5.7 A |
| Safety | Forecast Crashes ² (average total crashes / Crash Types / Severity | 1 - 6 ³ <ul style="list-style-type: none"> Most common crash types are rear end and right angle Injury related crashes represent approximately 30% of the total reported intersection crashes. | 8 <ul style="list-style-type: none"> Predominant crash types are rear end, right angle and left turn collisions Injury related crashes represent approximately 35% of the total reported intersection crashes. | 5 <ul style="list-style-type: none"> Most common crash types include failure to yield at entry and single-vehicle run off road. Injury related crashes are typically reduced by 50% compared to traditional intersections. |
| Cost | Construction ⁴ Hardware Total Cost | \$1,435,000 -- \$1,435,000 | \$1,435,000 \$175,000 \$1,610,000 | \$1,185,000 -- \$1,185,000 |
| Right of Way | Required Acquisition (square feet) | 6,804 | 6,804 | 5,229 |
| Utilities | Impacts | High (Requires longer construction limits and widening along Highview Avenue) | High (Requires longer construction limits and widening along Highview Avenue) | Medium (Highview Avenue construction limits/widening is reduced) |
| Environment | Emissions / Air Quality Other Impacts | High Low | Medium Low | Low Medium (Requires additional corner right of way and clearing of trees in the southeast quadrant) |
| Pedestrian / Bicycle | Safety Consideration | <ul style="list-style-type: none"> Pedestrian related crashes are generally low | <ul style="list-style-type: none"> Pedestrian related crashes are generally low | <ul style="list-style-type: none"> The incidence and severity of pedestrian related crashes are typically reduced versus other intersection control devices. The primary pedestrian disadvantage is due to the crosswalk location and approaching vehicles being required to yield right of way (typically beyond the crosswalk). The operation is similar to a mid-block crossing. |
| Other Considerations | Comments | <ul style="list-style-type: none"> All-way stop control is deficient. Large intersections with multiple lanes of approach can result in inefficient and confusing all-way stop operation. | <ul style="list-style-type: none"> The traffic operation analysis evaluated the traffic signal with 8-phase control and protected left turn phases (worst-case). This may result in unnecessary inefficiency during off-peak periods. Typically protected left turn phases are provided with roadway approaches exceeding 50 mph. However, if sight lines are acceptable, protected/permissive phasing should be used. As roadway profiles are developed, the sight lines should be evaluated. Protected/permissive phasing will increase the overall intersection efficiency. | <ul style="list-style-type: none"> Construction staging presents a much greater challenge and interim traffic impact. Could result in additional construction costs. Uphill approach grades require lowering the roadway profile. Intersection will operate isolated and is not expected to benefit from or be tied into a signalized coordinated zone. May provide for better 24-hour solution and overall intersection efficiency Retaining wall or additional ROW required on the southeast corner. |

¹ The PM peak hour represents the worst case scenario.

² Forecast crashes estimated based on statewide average rates (0.6 for all-way, 0.8 for traffic signal and 0.48 for roundabout).

³ This intersection has had 2 correctable crashes for the years 2005-2007. The existing crash rate is 0.10 compared to the statewide average rate of 0.6. Using the existing crash rate of 0.10 and the statewide average rate of 0.6, the range of expected yearly crashes is 1 to 6.

⁴ Construction costs are for comparison only and not intended to represent the total construction cost of each Alternative.

Items computed for comparison analysis include Removals, Earthwork, Roadway Surface Features, and Drainage.

⁵ All-way stop control is expected to operate at acceptable conditions until Year 2023. Year 2023 represents the point where the westbound approach exceeds its acceptable peak hour capacity.



Table 21. Comparison Evaluation Matrix - CSAH 9 at CSAH 60

| Objective | 2030 - Without Extension | 2030 - Without Extension | 2030 - With Extension | 2030 - With Extension | 2030 - With Extension | 2030 - With Extension |
|---|---|--|---|--|---|---|
| | No-Build (All-Way Stop) | Concept Layout 1b (Traffic Signal) | Concept Layout 3b (All-Way Stop) | Concept Layout 2b (Traffic Signal) | Concept Layout 3b (Traffic Signal) | Concept Layout 4b (Roundabout) |
| Operations Overall Intersection Delay (sec / veh) ¹ LOS | 551.6 F Intersection delay based on the existing 1-eastbound Left Turn Lane. See Footnotes (2) and (3) | 21.1 C | 707.7 F | 42.3 D | 43.0 D | 7.4 A |
| Safety Forecast Crashes ⁴ (crashes / year) Crash Types / Severity | 7 Most common crash types are rear end and right angle Injury related crashes represent approximately 30% of the total reported intersection crashes. | 9 Predominant crash types are rear end, right angle and left turn collisions Injury related crashes represent approximately 35% of the total reported intersection crashes. | 9 Most common crash types are rear end and right angle Injury related crashes represent approximately 30% of the total reported intersection crashes. | 12 Predominant crash types are rear end, right angle and left turn collisions Injury related crashes represent approximately 35% of the total reported intersection crashes. | 12 Predominant crash types are rear end, right angle and left turn collisions Injury related crashes represent approximately 35% of the total reported intersection crashes. | 7 Most common crash types include failure to yield at entry and single-vehicle run off road. Injury related crashes are typically reduced by 50% compared to traditional intersections. |
| Cost Construction ⁵ Hardware Miscellaneous Total Cost | -- -- \$0 | -- \$175,000 (Designed to accommodate future extension) \$175,000 | \$365,000 -- \$365,000 | \$460,000 \$25,000 \$485,000 (Signal Modification to add 4th Leg) | \$365,000 \$25,000 \$390,000 (Signal Modification to add 4th Leg) | \$900,000 -- \$900,000 |
| Right of Way Required Acquisition (square feet) | 0 | 0 | 525 | 525 | 525 | 525 |
| Utilities Impacts | None | None | Low (CSAH 9 southeast edge line) | Medium (CSAH 9 southeast edge line) (CSAH 60 southwest Edge line) | Low | Medium (Intersection Only) |
| Environmental Emissions / Air Quality Other Impacts | High None | Low / Medium None | High Medium (East Leg Extension will require clearing of trees and addition of pavement) | Medium Medium (East Leg Extension will require clearing of trees and addition of pavement) | Medium Medium (East Leg Extension will require clearing of trees and addition of pavement) | Low Low (East Leg Extension could avoid trees and requires less pavement width) |
| Pedestrian / Bicycle Safety Consideration | Pedestrian related crashes are generally low | Pedestrian related crashes are generally low | All-way stop control is deficient. Large intersections with multiple lanes of approach can result in inefficient and confusing all-way stop operation. | Pedestrian related crashes are generally low | Pedestrian related crashes are generally low | The incidence and severity of pedestrian related crashes are typically reduced versus other intersection control devices. The primary pedestrian disadvantage is due to the crosswalk location and approaching vehicles being required to yield right of way (typically beyond the crosswalk). The operation is similar to a mid-block crossing. |
| Other Considerations Comments | All-way stop control is deficient. Large intersections with multiple lanes of approach can result in inefficient and confusing all-way stop operation. | Due to roadway speeds, the traffic signal will be an 8-phase control with protected left turn phases. This may result in unnecessary inefficiency during off-peak periods. Cost-effective interim solution until CSAH 60 is extended. | All-way stop control is deficient. | The addition of a double left turn lane requires roadway widening and protected left turn phasing. Double left turn lane may not be necessary outside of the PM peak period. | Maximizes the use of the existing roadway infrastructure The eastbound and westbound roadway approaches are 45 mph. The roadway profile is not expected to change. Based on the expected horizontal alignment, sight lines are expected to be acceptable. Protected/permissive phasing should be used. | Implementation of a roundabout requires full reconstruction of all four approach legs Construction staging is expected to have a much greater impact to traffic conditions and be far more costly. (Cost not included in estimate) Will need further consideration of future land use and character of CSAH 60 to the east of CSAH 9 A traffic signal exists 1/4-mile to the west. CSAH 60 may be developing as a signalized arterial. |

¹ The PM peak hour represents the worst case scenario.

² The year 2030 PM peak hour intersection delay is reduced to 41.8 seconds (78 seconds for eastbound left turn) if the eastbound approach was re-striped to include a double left turn lane (Concept Layout 1).

³ The year 2010 eastbound left turn is expected to operate at its capacity during the PM peak hour (a LOS E/F with a maximum queue length approaching the available storage). Year 2012/2013 represents the threshold where the eastbound left turn is expected to begin to significantly exceed its peak hour capacity.

⁴ Forecast crashes estimated based on statewide average rates (0.6 for all-way, 0.8 for traffic signal and 0.48 for roundabout).

⁵ Construction costs are for comparison only and not intended to represent the total construction cost of each Alternative. Items computed for comparison analysis include Removals, Earthwork, Roadway Surface Features, and Drainage.

4.4.1 Traffic Control Change Timeline

The results of the signal warrant analysis, safety analysis and the traffic operation analysis were used to estimate the year a traffic control change may be required. The following summarizes the conclusions of the analysis conducted at the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections.

CSAH 9 at Highview Avenue

- The signal warrant analysis found signal Warrant 1B, Warrant 2 and Warrant 3 are expected to be satisfied under the forecast year 2010 approach volumes.
- Based on the existing crash experience and the estimated future annual crashes (see **Table 7**), a specific safety characteristic warranting a traffic control change is not expected.
- The traffic operation analysis found the existing all-way stop control and Concept Layout 2a (see **Figure 8**) is expected to provide acceptable LOS B or better operations under the forecast year 2010 traffic volumes.
- By year 2030, the all-way stop control and Concept Layout 2a (see **Figure 8**) is expected to be deficient.
- Using the annualized background growth rate, the all-way stop control is expected to provide acceptable peak period traffic operations until year 2023. By year 2023, the westbound approach is expected to experience LOS F operations.

Although signal warrants are met in 2010, the operations analysis does not find that signalized intersection control would be an appropriate alternative until year 2023.

CSAH 9 at CSAH 60

- The signal warrant analysis found signal Warrant 1A, 1B, 1C, Warrant 2 and Warrant 3 are expected to be satisfied under the forecast year 2010 approach volumes.
- Based on the existing crash experience and the estimated future annual crashes (see **Table 8**), a specific safety characteristic warranting a traffic control change is not expected.
- The traffic operation analysis found the existing all-way stop control and existing intersection geometrics is expected to provide acceptable LOS D or better operations under the forecast year 2010 traffic volumes. However, the

eastbound left turn is expected to begin experiencing longer delays and queue lengths during the PM peak hour.

- The re-striping of the eastbound approach to a double left turn lane, Concept Layout 1b (see **Figure 9**), and maintaining the existing all-way stop control is expected to provide acceptable traffic operations until year 2028, or likely until the CSAH 60 extension project occurs.
- However, the operation of a dual eastbound left turn movement and an all-way stop control may not be a practical alternative due to the safety and operation concerns of such lane geometrics at a large intersection. If the existing geometrics are maintained, the eastbound left turn movement and the all-way stop control are expected to become deficient by year 2012.

Traffic signal warrants are expected to be met in year 2010. The operation analysis finds a traffic control change is expected to be needed by the year 2012.

4.4.2 Selection of Preferred Alternative

The preferred alternative at the CSAH 9/Highview Avenue and CSAH 9/CSAH 60 intersections were selected based upon; discussions with the TAC, results of the traffic operation analysis and safety analysis, and consideration of the key objectives evaluated in the comparison matrix.

CSAH 9 at Highview Avenue

The preferred alternative selected at the CSAH 9/Highview Avenue intersection is the roundabout, Concept Layout 1a (refer to **Figure 7**). The roundabout intersection was selected based on the following:

- With the 2008-2012 Capital Improvement Plan project, the intersection is being re-aligned and fully reconstructed. This is the most cost-effective opportunity to build a roundabout. Based on the preliminary cost estimate, the roundabout is expected to result in a net comparable or even less initial cost than a traditional intersection. This is due to the overall less pavement area (approaching roadway segments are narrowed) and reduced right of way needs with the roundabout option. In addition, the long term cost of a roundabout is reduced as the annual maintenance and operation costs are less than a traffic signal.
- The roundabout option will require small triangles of additional right of way on the southwest, southeast and northwest quadrants. However, overall the right of way impact is less than a traditional intersection. Additional right of way along Highview Avenue, south of CSAH 9 will not be required to the same extent as Concept Layout 2a (see **Figure 8**).

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

- The roundabout alternative will require the lowering of the Highview Avenue and CSAH 9 alignment profiles (to reduce approach grades and to provide a level circle). However, since the intersection is being fully reconstructed, this same consideration would have been made for a traditional intersection.
- Emissions and air quality impacts are expected to be improved with the roundabout option. The traffic analysis found greatly reduced vehicle delays with the roundabout intersection over the traffic signal option. A reduction in motorist delay directly correlates with lowering vehicle emission and fuel consumption.
- The roundabout is expected to provide an immediate benefit and reduction in motorist delay. The roundabout also provides a an immediate and much improved 24-hour solution versus an all-way stop control or a traffic signal system, which was not found needed until year 2023.
- The CSAH 9/Highview Avenue intersection is isolated; therefore does not benefit from coordinated arterial operations. A system or network impact is not expected with the implementation of a roundabout.
- Based on the safety analysis, a roundabout is expected to result in less overall intersection crashes than a traffic signal.

To validate the preferred roundabout geometrics, a more detailed traffic operation analysis using VISSIM was conducted. The VISSIM analysis evaluated the forecast 2030 PM peak hour traffic volumes. **Table 22** illustrates the results.

Table 22. Preferred Alternative 2030 PM Peak Hour VISSIM Analysis – CSAH 9 at Highview Avenue

| | MOE | EB Approach | | | WB Approach | | | NB Approach | | | SB Approach | | | Intersection Total |
|--------|----------------|-------------|-----|-----|-------------|-----|-----|-------------|-----|-----|-------------|------|------|--------------------|
| | | EBL | EBT | EBR | WBL | WBT | WBR | NBL | NBT | NBR | SBL | SBT | SBR | |
| VISSIM | LOS | A | A | A | A | A | A | A | A | A | C | C | C | A |
| | Delay (sec) | 3.7 | 2.3 | 1.8 | 5.6 | 4.7 | 5.6 | 6.6 | 9.6 | 8.4 | 24.8 | 23.4 | 22.4 | 9.0 |
| | Avg Queue (ft) | 7 | 7 | 7 | 12 | 12 | 12 | 15 | 15 | 15 | 83 | 83 | 83 | - |
| | Max Queue (ft) | 135 | 135 | 135 | 180 | 180 | 180 | 219 | 219 | 219 | 639 | 639 | 639 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |
| RODEL | LOS | A | A | A | A | A | A | A | A | A | B | B | B | A |
| | Delay (sec) | 3.6 | 3.6 | 3.6 | 3.6 | 3.6 | 3.6 | 6.6 | 6.6 | 6.6 | 10.2 | 10.2 | 10.2 | 5.7 |
| | Avg Queue (ft) | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 50 | 50 | 50 | - |
| | Max Queue (ft) | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 25 | 50 | 50 | 50 | - |
| | Storage (ft) | - | - | - | - | - | - | - | - | - | - | - | - | - |

CSAH 9 at CSAH 60

At the CSAH 9/CSAH 60 intersection, the following alternatives were selected:

- **Short Term:** The preferred short-term alternative is signalized intersection control with a dual eastbound left turn, Concept Layout 1b (see **Figure 9**).

- **Long Term:** The preferred long-term alternative (with CSAH 60 extension) is the traditional signalized intersection control with single left turn lanes, Concept Layout 3b (see **Figure 11**).

The signalized intersection control was selected based on the following:

- The traffic operation analysis shows the intersection is expected to need a traffic control change by year 2012. The installation of signalized intersection control prior to the CSAH 60 extension can be implemented with little or no impact to right of way and carry only the cost of the capital to install the signal and the recurring maintenance and operation costs. No additional environmental or utility impacts are expected. A roundabout would require full intersection reconstruction and may not be a feasible option to fund in the interim.
- The signalized intersection control and traditional intersection design maximizes the use of existing infrastructure and previous project investments.
- An existing traffic signal is in operation at Ipava Avenue (a quarter-mile to the west). The development of the CSAH 60 extension to the east is anticipated to result in a signalized arterial corridor. The installation of a traffic signal system at CSAH 60 is most consistent and best fits with the arterial and network characteristics of the corridor.
- The completed four-leg traditional intersection design and traffic signal system is expected to cost approximately 75 percent less than the roundabout option.
- The overall estimated right of way need between the traditional intersection and a roundabout are expected to be the same. The roundabout option could result in less right of way dedication on the east side of CSAH 9, depending upon how the corridor develops. However, at this time the corridor right of way width of 150 feet would accommodate both designs.

5.0 Recommendations

Based on the information provided in this Intersection Traffic Control Feasibility Study and the alternative analysis detailed in Section 4.0, the following recommendations are made:

5.1 CSAH 9 at Highview Avenue

- Construct a multi-lane roundabout intersection. (See Concept Layout 1a, illustrated in **Figure 7**).
- Realign CSAH 9 to the north to develop 90 degree approach angles and appropriate approach deflection radii.
- Lower the roadway profile and approach grades on both CSAH 9 and Highview Avenue to reduce the vertical curves, balance earthwork and provide a level roundabout circle.
- Utilize the existing CSAH 9 pavement, abandoned with the realignment, to develop a short frontage road in re-establishing access to the private residential home on the southwest quadrant. The frontage road would access CSAH 9 (right-in/right-out) at a determined appropriate distance upstream from Highview Avenue.
- Acquire sufficient right of way on each intersection quadrant to allow for the flexibility to widen the Highview Avenue entrance/exit flares to two lanes each. This will provide potential and flexibility to extend the design life, if in the future, unforeseen land use changes or traffic patterns occur and additional capacity is found needed.

5.2 CSAH 9 at CSAH 60

- Prior to the extension of CSAH 60, program the installation of a traffic signal system. As part of the signal installation, the eastbound approach should be re-striped to include two eastbound left turn movements. (See Concept Layout 1b, illustrated in **Figure 9**).
- The traffic signal system should be designed and equipment located to require minimal hardware modifications when the future CSAH 60 extension is completed.
- Evaluate the need to obtain a small triangular piece of right of way on the southwest corner. The right of way need will be governed by the final pedestrian ramp and traffic signal pole locations.

- As part of the CSAH 60 extension project, the westbound leg should be constructed as a four-lane divided section with exclusive left and right turn lanes. A southbound left turn and northbound right turn lane should be constructed. (See Concept Layout 3b, illustrated in **Figure 11**).
- The final design should ensure acceptable approach sightlines are maintained.
- The intersection traffic signal phasing will be determined by Dakota County Staff through the final design process. It should be noted, Concept Layout 3b (see **Figure 11**) assumes eastbound/westbound protected/permissive left turn phasing. The installation of protected only left turn phasing is expected to necessitate a dual eastbound left turn lane, Concept Layout 2b (see **Figure 10**).

6.0 Appendices

Appendix A: Collision Diagram – CSAH 9 at Highview Avenue

Appendix B: 24-hour Hourly Approach Volumes

Appendix C: Traffic Signal Warrant Analysis

Appendix D: RODEL Output Files

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Appendix A: Collision Diagram

Dakota County Highway Department



NORTH

MSAS 107
Highview Ave
R.P.: 1.115


CSAH 9
Dood Blvd
R.P.: 8.567

Collision Diagram

ACCIDENT TOTALS

2005.....1
2006.....1
2007.....1

DATE PREPARED: 01-28-09
PREPARED BY: PV



ACCIDENTS SUMMARY

3 ACCIDENTS . . . 3 YEARS

1 . . . PERSONAL INJURY
2 . . . PROPERTY DAMAGE

| | | |
|------------|------------|---------------|
| 1 . . . NB | 2 . . . EB | 1 . . . DAY |
| 1 . . . SB | 1 . . . WB | 2 . . . NIGHT |

| | |
|---------------|--------------|
| 2 . . . CLEAR | 3 . . . DRY |
| 1 . . . FOG | 0 . . . WET |
| 0 . . . SNOW | 0 . . . ICE |
| 0 . . . FOG | 0 . . . SNOW |

ACCIDENTS SUMMARY

1 . . . RIGHT TURN
1 . . . RAN OFF ROAD
1 . . . COLLISION WITH DEER

Standard Symbols

| | | | | | | | | | |
|--|-----------------------|--|-----------------|------------------------------|-------------|----------|-----------------|--|-----------------|
| | M V BACKING UP | | SCHOOL BUS | | PEDESTRIAN | | BICYCLE | | MOTORCYCLE |
| | MOTOR VEHICLE STOPPED | | FATAL ACCIDENT | | PARKING | | FIXED OBJECT | | ANIMAL |
| | PARTY AT FAULT | | PERSONAL INJURY | <u>LIGHT:</u> | | | <u>WEATHER:</u> | | <u>SURFACE:</u> |
| | CUT OF CONTROL | | PERSONAL INJURY | L = DAYLIGHT | C = CLEAR | D = DRY | | | |
| | OVERTURN | | PROPERTY DAMAGE | D = DARK | R = RAINING | W = WET | | | |
| | REAR END | | | S = DARK W/ STREET LIGHTS | S = SNOWING | S = SNOW | | | |
| | RIGHT ANGLE | | | | F = FOG | I = ICE | | | |

INTERSECTION · CSAH 9 & HIGHVIEW AVE · IN LAKEVILLE
FROM 01-01-05 TO 12-31-07 SOURCE MNDOT PRINTOUT

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Appendix B: 24-hour Hourly Approach Volumes

**Table B-1
CSAH 9 at Highview Avenue
Existing 2007**

| Raw Approach Volume | | | | | | | | | | |
|---------------------------|--------------|--------------|-------------|-------------|--------------|------|-------|------|------|-------|
| Begin Time | NB | SB | EB | WB | Total | NB | SB | EB | WB | Total |
| 12:00 AM | 10 | 16 | 40 | 39 | 105 | 0.4% | 0.5% | 0.6% | 0.6% | 0.6% |
| 1:00 AM | 16 | 4 | 19 | 23 | 62 | 0.7% | 0.1% | 0.3% | 0.4% | 0.3% |
| 2:00 AM | 7 | 3 | 11 | 20 | 41 | 0.3% | 0.1% | 0.2% | 0.3% | 0.2% |
| 3:00 AM | 5 | 3 | 12 | 13 | 33 | 0.2% | 0.1% | 0.2% | 0.2% | 0.2% |
| 4:00 AM | 13 | 8 | 17 | 22 | 60 | 0.6% | 0.3% | 0.3% | 0.4% | 0.3% |
| 5:00 AM | 24 | 39 | 55 | 88 | 206 | 1.0% | 1.2% | 0.9% | 1.4% | 1.1% |
| 6:00 AM | 46 | 85 | 232 | 195 | 558 | 2.0% | 2.7% | 3.7% | 3.1% | 3.1% |
| 7:00 AM | 124 | 186 | 321 | 310 | 941 | 5.4% | 5.9% | 5.1% | 5.0% | 5.2% |
| 8:00 AM | 126 | 170 | 337 | 348 | 981 | 5.5% | 5.4% | 5.4% | 5.6% | 5.5% |
| 9:00 AM | 114 | 162 | 318 | 310 | 904 | 5.0% | 5.2% | 5.1% | 5.0% | 5.0% |
| 10:00 AM | 121 | 187 | 389 | 353 | 1050 | 5.3% | 6.0% | 6.2% | 5.7% | 5.8% |
| 11:00 AM | 144 | 170 | 344 | 356 | 1014 | 6.3% | 5.4% | 5.5% | 5.7% | 5.6% |
| 12:00 PM | 151 | 177 | 349 | 384 | 1061 | 6.6% | 5.6% | 5.6% | 6.2% | 5.9% |
| 1:00 PM | 132 | 179 | 366 | 371 | 1048 | 5.8% | 5.7% | 5.8% | 5.9% | 5.8% |
| 2:00 PM | 131 | 157 | 372 | 380 | 1040 | 5.7% | 5.0% | 5.9% | 6.1% | 5.8% |
| 3:00 PM | 156 | 190 | 419 | 433 | 1198 | 6.8% | 6.0% | 6.7% | 6.9% | 6.7% |
| 4:00 PM | 188 | 242 | 429 | 482 | 1341 | 8.2% | 7.7% | 6.8% | 7.7% | 7.5% |
| 5:00 PM | 218 | 378 | 471 | 539 | 1606 | 9.5% | 12.0% | 7.5% | 8.6% | 8.9% |
| 6:00 PM | 156 | 287 | 432 | 481 | 1356 | 6.8% | 9.1% | 6.9% | 7.7% | 7.6% |
| 7:00 PM | 124 | 171 | 387 | 339 | 1021 | 5.4% | 5.4% | 6.2% | 5.4% | 5.7% |
| 8:00 PM | 140 | 157 | 436 | 332 | 1065 | 6.1% | 5.0% | 6.9% | 5.3% | 5.9% |
| 9:00 PM | 85 | 94 | 276 | 216 | 671 | 3.7% | 3.0% | 4.4% | 3.5% | 3.7% |
| 10:00 PM | 39 | 50 | 159 | 137 | 385 | 1.7% | 1.6% | 2.5% | 2.2% | 2.1% |
| 11:00 PM | 20 | 27 | 90 | 70 | 207 | 0.9% | 0.9% | 1.4% | 1.1% | 1.2% |
| Total | 2290 | 3142 | 6281 | 6241 | 17954 | | | | | |
| Right Turn Percent | 44.3% | 45.7% | 2.0% | 4.6% | | | | | | |
| Remove RT | Yes | | | | | | | | | |

| Right Turn Capacity Check | | | | |
|---------------------------|-----|-------|-----|-------|
| Begin Time | EB | NB RT | WB | SB RT |
| 12:00 AM | 40 | 4 | 39 | 7 |
| 1:00 AM | 19 | 7 | 23 | 2 |
| 2:00 AM | 11 | 3 | 20 | 1 |
| 3:00 AM | 12 | 2 | 13 | 1 |
| 4:00 AM | 17 | 6 | 22 | 4 |
| 5:00 AM | 55 | 11 | 88 | 18 |
| 6:00 AM | 232 | 20 | 195 | 39 |
| 7:00 AM | 321 | 55 | 310 | 85 |
| 8:00 AM | 337 | 56 | 348 | 78 |
| 9:00 AM | 318 | 50 | 310 | 74 |
| 10:00 AM | 389 | 54 | 353 | 86 |
| 11:00 AM | 344 | 64 | 356 | 78 |
| 12:00 PM | 349 | 67 | 384 | 81 |
| 1:00 PM | 366 | 58 | 371 | 82 |
| 2:00 PM | 372 | 58 | 380 | 72 |
| 3:00 PM | 419 | 69 | 433 | 87 |
| 4:00 PM | 429 | 83 | 482 | 111 |
| 5:00 PM | 471 | 96 | 539 | 173 |
| 6:00 PM | 432 | 69 | 481 | 131 |
| 7:00 PM | 387 | 55 | 339 | 78 |
| 8:00 PM | 436 | 62 | 332 | 72 |
| 9:00 PM | 276 | 38 | 216 | 43 |
| 10:00 PM | 159 | 17 | 137 | 23 |
| 11:00 PM | 90 | 9 | 70 | 12 |

CSAH 9 at Highview Avenue Approach Volumes - Signal Warrant Analysis

| Begin Time | NB | SB | EB | WB |
|------------|-----|-----|-----|-----|
| 12:00 AM | 6 | 9 | 40 | 39 |
| 1:00 AM | 9 | 2 | 19 | 23 |
| 2:00 AM | 4 | 2 | 11 | 20 |
| 3:00 AM | 3 | 2 | 12 | 13 |
| 4:00 AM | 7 | 4 | 17 | 22 |
| 5:00 AM | 13 | 21 | 55 | 88 |
| 6:00 AM | 26 | 46 | 232 | 195 |
| 7:00 AM | 69 | 101 | 321 | 310 |
| 8:00 AM | 70 | 92 | 337 | 348 |
| 9:00 AM | 64 | 88 | 318 | 310 |
| 10:00 AM | 67 | 101 | 389 | 353 |
| 11:00 AM | 80 | 92 | 344 | 356 |
| 12:00 PM | 84 | 96 | 349 | 384 |
| 1:00 PM | 74 | 97 | 366 | 371 |
| 2:00 PM | 73 | 85 | 372 | 380 |
| 3:00 PM | 87 | 103 | 419 | 433 |
| 4:00 PM | 105 | 131 | 429 | 482 |
| 5:00 PM | 122 | 205 | 471 | 539 |
| 6:00 PM | 87 | 156 | 432 | 481 |
| 7:00 PM | 69 | 93 | 387 | 339 |
| 8:00 PM | 78 | 85 | 436 | 332 |
| 9:00 PM | 47 | 51 | 276 | 216 |
| 10:00 PM | 22 | 27 | 159 | 137 |
| 11:00 PM | 11 | 15 | 90 | 70 |

**Table B-2
CSAH 9 at Highview Avenue
Forecast 2010**

| 2010 Approach Volume | | | | | | | | | | |
|---------------------------|-----------------|------------------|------------------|-----------------|-------------------|------|-------|------|------|-------|
| Growth Rate | 3.4% | 1.2% | 2.4% | 2.3% | | | | | | |
| Begin Time | NB | SB | EB | WB | Total | NB | SB | EB | WB | Total |
| 12:00 AM | 11 | 17 | 43 | 42 | 112 | 0.4% | 0.5% | 0.6% | 0.6% | 0.6% |
| 1:00 AM | 18 | 4 | 20 | 25 | 67 | 0.7% | 0.1% | 0.3% | 0.4% | 0.3% |
| 2:00 AM | 8 | 3 | 12 | 21 | 44 | 0.3% | 0.1% | 0.2% | 0.3% | 0.2% |
| 3:00 AM | 6 | 3 | 13 | 14 | 35 | 0.2% | 0.1% | 0.2% | 0.2% | 0.2% |
| 4:00 AM | 14 | 8 | 18 | 24 | 64 | 0.6% | 0.3% | 0.3% | 0.4% | 0.3% |
| 5:00 AM | 27 | 40 | 59 | 94 | 220 | 1.0% | 1.2% | 0.9% | 1.4% | 1.1% |
| 6:00 AM | 51 | 88 | 249 | 209 | 597 | 2.0% | 2.7% | 3.7% | 3.1% | 3.1% |
| 7:00 AM | 137 | 193 | 344 | 332 | 1006 | 5.4% | 5.9% | 5.1% | 5.0% | 5.2% |
| 8:00 AM | 139 | 176 | 362 | 373 | 1050 | 5.5% | 5.4% | 5.4% | 5.6% | 5.5% |
| 9:00 AM | 126 | 168 | 341 | 332 | 967 | 5.0% | 5.2% | 5.1% | 5.0% | 5.0% |
| 10:00 AM | 134 | 194 | 417 | 378 | 1123 | 5.3% | 6.0% | 6.2% | 5.7% | 5.8% |
| 11:00 AM | 159 | 176 | 369 | 381 | 1086 | 6.3% | 5.4% | 5.5% | 5.7% | 5.7% |
| 12:00 PM | 167 | 183 | 374 | 411 | 1136 | 6.6% | 5.6% | 5.6% | 6.2% | 5.9% |
| 1:00 PM | 146 | 185 | 393 | 397 | 1122 | 5.8% | 5.7% | 5.8% | 5.9% | 5.8% |
| 2:00 PM | 145 | 163 | 399 | 407 | 1114 | 5.7% | 5.0% | 5.9% | 6.1% | 5.8% |
| 3:00 PM | 172 | 197 | 450 | 464 | 1283 | 6.8% | 6.0% | 6.7% | 6.9% | 6.7% |
| 4:00 PM | 208 | 251 | 460 | 516 | 1435 | 8.2% | 7.7% | 6.8% | 7.7% | 7.5% |
| 5:00 PM | 241 | 392 | 505 | 577 | 1716 | 9.5% | 12.0% | 7.5% | 8.6% | 8.9% |
| 6:00 PM | 172 | 297 | 464 | 515 | 1449 | 6.8% | 9.1% | 6.9% | 7.7% | 7.5% |
| 7:00 PM | 137 | 177 | 415 | 363 | 1093 | 5.4% | 5.4% | 6.2% | 5.4% | 5.7% |
| 8:00 PM | 155 | 163 | 468 | 356 | 1141 | 6.1% | 5.0% | 6.9% | 5.3% | 5.9% |
| 9:00 PM | 94 | 97 | 296 | 231 | 719 | 3.7% | 3.0% | 4.4% | 3.5% | 3.7% |
| 10:00 PM | 43 | 52 | 171 | 147 | 412 | 1.7% | 1.6% | 2.5% | 2.2% | 2.1% |
| 11:00 PM | 22 | 28 | 97 | 75 | 222 | 0.9% | 0.9% | 1.4% | 1.1% | 1.2% |
| Total | 2532.175 | 3255.8419 | 6739.8437 | 6685.641 | 19213.5016 | | | | | |
| Right Turn Percent | 44.3% | 45.7% | 2.0% | 4.6% | | | | | | |
| Remove RT | Yes | | | | | | | | | |

| Right Turn Capacity Check | | | | |
|---------------------------|-----|-------|-----|-------|
| Begin Time | EB | NB RT | WB | SB RT |
| 12:00 AM | 43 | 5 | 42 | 8 |
| 1:00 AM | 20 | 8 | 25 | 2 |
| 2:00 AM | 12 | 3 | 21 | 1 |
| 3:00 AM | 13 | 2 | 14 | 1 |
| 4:00 AM | 18 | 6 | 24 | 4 |
| 5:00 AM | 59 | 12 | 94 | 18 |
| 6:00 AM | 249 | 23 | 209 | 40 |
| 7:00 AM | 344 | 61 | 332 | 88 |
| 8:00 AM | 362 | 62 | 373 | 81 |
| 9:00 AM | 341 | 56 | 332 | 77 |
| 10:00 AM | 417 | 59 | 378 | 89 |
| 11:00 AM | 369 | 70 | 381 | 81 |
| 12:00 PM | 374 | 74 | 411 | 84 |
| 1:00 PM | 393 | 65 | 397 | 85 |
| 2:00 PM | 399 | 64 | 407 | 74 |
| 3:00 PM | 450 | 76 | 464 | 90 |
| 4:00 PM | 460 | 92 | 516 | 115 |
| 5:00 PM | 505 | 107 | 577 | 179 |
| 6:00 PM | 464 | 76 | 515 | 136 |
| 7:00 PM | 415 | 61 | 363 | 81 |
| 8:00 PM | 468 | 69 | 356 | 74 |
| 9:00 PM | 296 | 42 | 231 | 45 |
| 10:00 PM | 171 | 19 | 147 | 24 |
| 11:00 PM | 97 | 10 | 75 | 13 |

Less than 70% Capacity

CSAH 9 at Highview Avenue Approach Volumes - Signal Warrant Analysis

| Begin Time | NB | SB | EB | WB |
|------------|-----|-----|-----|-----|
| 12:00 AM | 6 | 9 | 43 | 42 |
| 1:00 AM | 10 | 2 | 20 | 25 |
| 2:00 AM | 4 | 2 | 12 | 21 |
| 3:00 AM | 3 | 2 | 13 | 14 |
| 4:00 AM | 8 | 4 | 18 | 24 |
| 5:00 AM | 15 | 22 | 59 | 94 |
| 6:00 AM | 28 | 48 | 249 | 209 |
| 7:00 AM | 76 | 105 | 344 | 332 |
| 8:00 AM | 78 | 96 | 362 | 373 |
| 9:00 AM | 70 | 91 | 341 | 332 |
| 10:00 AM | 75 | 105 | 417 | 378 |
| 11:00 AM | 89 | 96 | 369 | 381 |
| 12:00 PM | 93 | 100 | 374 | 411 |
| 1:00 PM | 81 | 101 | 393 | 397 |
| 2:00 PM | 81 | 88 | 399 | 407 |
| 3:00 PM | 96 | 107 | 450 | 464 |
| 4:00 PM | 116 | 136 | 460 | 516 |
| 5:00 PM | 134 | 213 | 505 | 577 |
| 6:00 PM | 96 | 161 | 464 | 515 |
| 7:00 PM | 76 | 96 | 415 | 363 |
| 8:00 PM | 86 | 88 | 468 | 356 |
| 9:00 PM | 52 | 53 | 296 | 231 |
| 10:00 PM | 24 | 28 | 171 | 147 |
| 11:00 PM | 12 | 15 | 97 | 75 |

Note: Northbound/southbound right turn volume is excluded

**Table B-3
CSAH 9 at Highview Avenue
Forecast 2030**

| 2010 Approach Volume | | | | | | | | | | |
|---------------------------|------------------|------------------|------------------|------------------|--------------|------|-------|------|------|-------|
| Growth Rate | 3.4% | 1.2% | 2.4% | 2.3% | | | | | | |
| Begin Time | NB | SB | EB | WB | Total | NB | SB | EB | WB | Total |
| 12:00 AM | 22 | 21 | 69 | 66 | 105 | 0.4% | 0.5% | 0.6% | 0.6% | 0.6% |
| 1:00 AM | 35 | 5 | 33 | 39 | 62 | 0.7% | 0.1% | 0.3% | 0.4% | 0.3% |
| 2:00 AM | 15 | 4 | 19 | 34 | 41 | 0.3% | 0.1% | 0.2% | 0.3% | 0.2% |
| 3:00 AM | 11 | 4 | 21 | 22 | 33 | 0.2% | 0.1% | 0.2% | 0.2% | 0.2% |
| 4:00 AM | 28 | 11 | 29 | 37 | 60 | 0.6% | 0.3% | 0.3% | 0.4% | 0.3% |
| 5:00 AM | 52 | 51 | 94 | 149 | 206 | 1.0% | 1.2% | 0.9% | 1.4% | 1.1% |
| 6:00 AM | 99 | 112 | 398 | 331 | 558 | 2.0% | 2.7% | 3.7% | 3.1% | 3.1% |
| 7:00 AM | 268 | 244 | 551 | 525 | 941 | 5.4% | 5.9% | 5.1% | 5.0% | 5.2% |
| 8:00 AM | 272 | 223 | 579 | 590 | 981 | 5.5% | 5.4% | 5.4% | 5.6% | 5.5% |
| 9:00 AM | 246 | 213 | 546 | 525 | 904 | 5.0% | 5.2% | 5.1% | 5.0% | 5.0% |
| 10:00 AM | 262 | 246 | 668 | 598 | 1050 | 5.3% | 6.0% | 6.2% | 5.7% | 5.8% |
| 11:00 AM | 311 | 223 | 591 | 603 | 1014 | 6.3% | 5.4% | 5.5% | 5.7% | 5.6% |
| 12:00 PM | 326 | 233 | 599 | 651 | 1061 | 6.6% | 5.6% | 5.6% | 6.2% | 5.9% |
| 1:00 PM | 285 | 235 | 628 | 629 | 1048 | 5.8% | 5.7% | 5.8% | 5.9% | 5.8% |
| 2:00 PM | 283 | 206 | 639 | 644 | 1040 | 5.7% | 5.0% | 5.9% | 6.1% | 5.8% |
| 3:00 PM | 337 | 250 | 719 | 734 | 1198 | 6.8% | 6.0% | 6.7% | 6.9% | 6.7% |
| 4:00 PM | 406 | 318 | 737 | 817 | 1341 | 8.2% | 7.7% | 6.8% | 7.7% | 7.5% |
| 5:00 PM | 471 | 497 | 809 | 914 | 1606 | 9.5% | 12.0% | 7.5% | 8.6% | 8.9% |
| 6:00 PM | 337 | 377 | 742 | 815 | 1356 | 6.8% | 9.1% | 6.9% | 7.7% | 7.6% |
| 7:00 PM | 268 | 225 | 664 | 575 | 1021 | 5.4% | 5.4% | 6.2% | 5.4% | 5.7% |
| 8:00 PM | 303 | 206 | 749 | 563 | 1065 | 6.1% | 5.0% | 6.9% | 5.3% | 5.9% |
| 9:00 PM | 184 | 123 | 474 | 366 | 671 | 3.7% | 3.0% | 4.4% | 3.5% | 3.7% |
| 10:00 PM | 84 | 66 | 273 | 232 | 385 | 1.7% | 1.6% | 2.5% | 2.2% | 2.1% |
| 11:00 PM | 43 | 35 | 155 | 119 | 207 | 0.9% | 0.9% | 1.4% | 1.1% | 1.2% |
| Total | 4949.3548 | 4127.7255 | 10784.253 | 10577.966 | 17954 | | | | | |
| Right Turn Percent | 44.3% | 45.7% | 2.0% | 4.6% | | | | | | |
| Remove RT | Yes | | | | | | | | | |

| Right Turn Capacity Check | | | | |
|---------------------------|-----|-------|-----|-------|
| Begin Time | EB | NB RT | WB | SB RT |
| 12:00 AM | 69 | 10 | 66 | 10 |
| 1:00 AM | 33 | 15 | 39 | 2 |
| 2:00 AM | 19 | 7 | 34 | 2 |
| 3:00 AM | 21 | 5 | 22 | 2 |
| 4:00 AM | 29 | 12 | 37 | 5 |
| 5:00 AM | 94 | 23 | 149 | 23 |
| 6:00 AM | 398 | 44 | 331 | 51 |
| 7:00 AM | 551 | 119 | 525 | 112 |
| 8:00 AM | 579 | 121 | 590 | 102 |
| 9:00 AM | 546 | 109 | 525 | 97 |
| 10:00 AM | 668 | 116 | 598 | 112 |
| 11:00 AM | 591 | 138 | 603 | 102 |
| 12:00 PM | 599 | 144 | 651 | 106 |
| 1:00 PM | 628 | 126 | 629 | 108 |
| 2:00 PM | 639 | 125 | 644 | 94 |
| 3:00 PM | 719 | 149 | 734 | 114 |
| 4:00 PM | 737 | 180 | 817 | 145 |
| 5:00 PM | 809 | 209 | 914 | 227 |
| 6:00 PM | 742 | 149 | 815 | 172 |
| 7:00 PM | 664 | 119 | 575 | 103 |
| 8:00 PM | 749 | 134 | 563 | 94 |
| 9:00 PM | 474 | 81 | 366 | 56 |
| 10:00 PM | 273 | 37 | 232 | 30 |
| 11:00 PM | 155 | 19 | 119 | 16 |

CSAH 9 at Highview Avenue Approach Volumes - Signal Warrant Analysis

| Begin Time | NB | SB | EB | WB |
|------------|-----|-----|-----|-----|
| 12:00 AM | 12 | 11 | 69 | 66 |
| 1:00 AM | 19 | 3 | 33 | 39 |
| 2:00 AM | 8 | 2 | 19 | 34 |
| 3:00 AM | 6 | 2 | 21 | 22 |
| 4:00 AM | 16 | 6 | 29 | 37 |
| 5:00 AM | 29 | 28 | 94 | 149 |
| 6:00 AM | 55 | 61 | 398 | 331 |
| 7:00 AM | 149 | 133 | 551 | 525 |
| 8:00 AM | 152 | 121 | 579 | 590 |
| 9:00 AM | 137 | 115 | 546 | 525 |
| 10:00 AM | 146 | 133 | 668 | 598 |
| 11:00 AM | 173 | 121 | 591 | 603 |
| 12:00 PM | 182 | 126 | 599 | 651 |
| 1:00 PM | 159 | 128 | 628 | 629 |
| 2:00 PM | 158 | 112 | 639 | 644 |
| 3:00 PM | 188 | 135 | 719 | 734 |
| 4:00 PM | 226 | 173 | 737 | 817 |
| 5:00 PM | 263 | 269 | 809 | 914 |
| 6:00 PM | 188 | 205 | 742 | 815 |
| 7:00 PM | 149 | 122 | 664 | 575 |
| 8:00 PM | 169 | 112 | 749 | 563 |
| 9:00 PM | 102 | 67 | 474 | 366 |
| 10:00 PM | 47 | 36 | 273 | 232 |
| 11:00 PM | 24 | 19 | 155 | 119 |

Note: Northbound/southbound right turn volume is excluded

**Table B-4
CSAH 9 at CSAH 60
Existing 2007**

| Raw Approach Volume | | | | | | | | | | |
|---------------------------|-------------|--------------|--------------|-------------|--------------|------|------|------|------|------|
| Begin Time | NB | SB | EB | WB | Total | NB | SB | EB | WB | |
| 12:00 AM | 20 | 47 | 23 | 0 | 90 | 0.5% | 0.7% | 0.5% | 0.0% | 0.6% |
| 1:00 AM | 8 | 14 | 7 | 0 | 29 | 0.2% | 0.2% | 0.2% | 0.0% | 0.2% |
| 2:00 AM | 15 | 19 | 19 | 0 | 53 | 0.4% | 0.3% | 0.4% | 0.0% | 0.3% |
| 3:00 AM | 7 | 11 | 4 | 0 | 22 | 0.2% | 0.2% | 0.1% | 0.0% | 0.1% |
| 4:00 AM | 18 | 13 | 15 | 0 | 46 | 0.5% | 0.2% | 0.3% | 0.0% | 0.3% |
| 5:00 AM | 70 | 62 | 81 | 0 | 213 | 1.8% | 0.9% | 1.8% | 0.0% | 1.4% |
| 6:00 AM | 147 | 240 | 146 | 0 | 533 | 3.7% | 3.4% | 3.3% | 0.0% | 3.5% |
| 7:00 AM | 222 | 384 | 230 | 0 | 836 | 5.6% | 5.5% | 5.1% | 0.0% | 5.4% |
| 8:00 AM | 230 | 330 | 255 | 0 | 815 | 5.9% | 4.7% | 5.7% | 0.0% | 5.3% |
| 9:00 AM | 247 | 297 | 279 | 0 | 823 | 6.3% | 4.2% | 6.2% | 0.0% | 5.3% |
| 10:00 AM | 231 | 386 | 202 | 0 | 819 | 5.9% | 5.5% | 4.5% | 0.0% | 5.3% |
| 11:00 AM | 223 | 392 | 261 | 0 | 876 | 5.7% | 5.6% | 5.8% | 0.0% | 5.7% |
| 12:00 PM | 247 | 427 | 250 | 0 | 924 | 6.3% | 6.1% | 5.6% | 0.0% | 6.0% |
| 1:00 PM | 217 | 422 | 224 | 0 | 863 | 5.5% | 6.0% | 5.0% | 0.0% | 5.6% |
| 2:00 PM | 200 | 399 | 257 | 0 | 856 | 5.1% | 5.7% | 5.7% | 0.0% | 5.6% |
| 3:00 PM | 240 | 455 | 285 | 0 | 980 | 6.1% | 6.5% | 6.4% | 0.0% | 6.4% |
| 4:00 PM | 278 | 488 | 358 | 0 | 1124 | 7.1% | 7.0% | 8.0% | 0.0% | 7.3% |
| 5:00 PM | 335 | 586 | 433 | 0 | 1354 | 8.5% | 8.4% | 9.7% | 0.0% | 8.8% |
| 6:00 PM | 303 | 528 | 386 | 0 | 1217 | 7.7% | 7.5% | 8.6% | 0.0% | 7.9% |
| 7:00 PM | 212 | 429 | 235 | 0 | 876 | 5.4% | 6.1% | 5.3% | 0.0% | 5.7% |
| 8:00 PM | 230 | 520 | 220 | 0 | 970 | 5.9% | 7.4% | 4.9% | 0.0% | 6.3% |
| 9:00 PM | 118 | 276 | 158 | 0 | 552 | 3.0% | 3.9% | 3.5% | 0.0% | 3.6% |
| 10:00 PM | 75 | 168 | 98 | 0 | 341 | 1.9% | 2.4% | 2.2% | 0.0% | 2.2% |
| 11:00 PM | 38 | 105 | 44 | 0 | 187 | 1.0% | 1.5% | 1.0% | 0.0% | 1.2% |
| Total | 3931 | 6998 | 4470 | 0 | 15399 | | | | | |
| Right Turn Percent | 0.0% | 47.0% | 21.8% | 0.0% | | | | | | |
| Remove RT | Yes | | | | | | | | | |

| Right Turn Capacity Check | | | | |
|---------------------------|-----|-------|-----|-------|
| Begin Time | NB | WB RT | SB | EB RT |
| 12:00 AM | 20 | 0 | 47 | 5 |
| 1:00 AM | 8 | 0 | 14 | 2 |
| 2:00 AM | 15 | 0 | 19 | 4 |
| 3:00 AM | 7 | 0 | 11 | 1 |
| 4:00 AM | 18 | 0 | 13 | 3 |
| 5:00 AM | 70 | 0 | 62 | 18 |
| 6:00 AM | 147 | 0 | 240 | 32 |
| 7:00 AM | 222 | 0 | 384 | 50 |
| 8:00 AM | 230 | 0 | 330 | 56 |
| 9:00 AM | 247 | 0 | 297 | 61 |
| 10:00 AM | 231 | 0 | 386 | 44 |
| 11:00 AM | 223 | 0 | 392 | 57 |
| 12:00 PM | 247 | 0 | 427 | 54 |
| 1:00 PM | 217 | 0 | 422 | 49 |
| 2:00 PM | 200 | 0 | 399 | 56 |
| 3:00 PM | 240 | 0 | 455 | 62 |
| 4:00 PM | 278 | 0 | 488 | 78 |
| 5:00 PM | 335 | 0 | 586 | 94 |
| 6:00 PM | 303 | 0 | 528 | 84 |
| 7:00 PM | 212 | 0 | 429 | 51 |
| 8:00 PM | 230 | 0 | 520 | 48 |
| 9:00 PM | 118 | 0 | 276 | 34 |
| 10:00 PM | 75 | 0 | 168 | 21 |
| 11:00 PM | 38 | 0 | 105 | 10 |

Less than 70% Capacity

CSAH 9 at CSAH 60 Approach Volumes - Signal Warrant Analysis

| Begin Time | NB | SB | EB | WB |
|------------|-----|-----|-----|----|
| 12:00 AM | 20 | 47 | 18 | 0 |
| 1:00 AM | 8 | 14 | 5 | 0 |
| 2:00 AM | 15 | 19 | 15 | 0 |
| 3:00 AM | 7 | 11 | 3 | 0 |
| 4:00 AM | 18 | 13 | 12 | 0 |
| 5:00 AM | 70 | 62 | 63 | 0 |
| 6:00 AM | 147 | 240 | 114 | 0 |
| 7:00 AM | 222 | 384 | 180 | 0 |
| 8:00 AM | 230 | 330 | 199 | 0 |
| 9:00 AM | 247 | 297 | 218 | 0 |
| 10:00 AM | 231 | 386 | 158 | 0 |
| 11:00 AM | 223 | 392 | 204 | 0 |
| 12:00 PM | 247 | 427 | 196 | 0 |
| 1:00 PM | 217 | 422 | 175 | 0 |
| 2:00 PM | 200 | 399 | 201 | 0 |
| 3:00 PM | 240 | 455 | 223 | 0 |
| 4:00 PM | 278 | 488 | 280 | 0 |
| 5:00 PM | 335 | 586 | 339 | 0 |
| 6:00 PM | 303 | 528 | 302 | 0 |
| 7:00 PM | 212 | 429 | 184 | 0 |
| 8:00 PM | 230 | 520 | 172 | 0 |
| 9:00 PM | 118 | 276 | 124 | 0 |
| 10:00 PM | 75 | 168 | 77 | 0 |
| 11:00 PM | 38 | 105 | 34 | 0 |

**Table B-5
CSAH 9 at CSAH 60
Forecast 2010 - Without CSAH 60 Extension**

| Raw Approach Volume | | | | | | | | | | |
|---------------------------|--------------|--------------|--------------|-------------|---------------|------|------|------|------|------|
| Growth Rate | 3.0% | 2.6% | 3.0% | | | | | | | |
| Begin Time | NB | SB | EB | WB | Total | NB | SB | EB | WB | |
| 12:00 AM | 22 | 51 | 25 | 0 | 98 | 0.5% | 0.7% | 0.5% | 0.0% | 0.6% |
| 1:00 AM | 9 | 15 | 8 | 0 | 32 | 0.2% | 0.2% | 0.2% | 0.0% | 0.2% |
| 2:00 AM | 16 | 21 | 21 | 0 | 58 | 0.4% | 0.3% | 0.4% | 0.0% | 0.3% |
| 3:00 AM | 8 | 12 | 4 | 0 | 24 | 0.2% | 0.2% | 0.1% | 0.0% | 0.1% |
| 4:00 AM | 20 | 14 | 16 | 0 | 50 | 0.5% | 0.2% | 0.3% | 0.0% | 0.3% |
| 5:00 AM | 76 | 67 | 88 | 0 | 232 | 1.8% | 0.9% | 1.8% | 0.0% | 1.4% |
| 6:00 AM | 161 | 259 | 159 | 0 | 579 | 3.7% | 3.4% | 3.3% | 0.0% | 3.5% |
| 7:00 AM | 242 | 415 | 251 | 0 | 908 | 5.6% | 5.5% | 5.1% | 0.0% | 5.4% |
| 8:00 AM | 251 | 357 | 278 | 0 | 886 | 5.9% | 4.7% | 5.7% | 0.0% | 5.3% |
| 9:00 AM | 270 | 321 | 305 | 0 | 895 | 6.3% | 4.2% | 6.2% | 0.0% | 5.3% |
| 10:00 AM | 252 | 417 | 221 | 0 | 890 | 5.9% | 5.5% | 4.5% | 0.0% | 5.3% |
| 11:00 AM | 244 | 424 | 285 | 0 | 952 | 5.7% | 5.6% | 5.8% | 0.0% | 5.7% |
| 12:00 PM | 270 | 461 | 273 | 0 | 1,004 | 6.3% | 6.1% | 5.6% | 0.0% | 6.0% |
| 1:00 PM | 237 | 456 | 245 | 0 | 937 | 5.5% | 6.0% | 5.0% | 0.0% | 5.6% |
| 2:00 PM | 218 | 431 | 281 | 0 | 930 | 5.1% | 5.7% | 5.7% | 0.0% | 5.6% |
| 3:00 PM | 262 | 492 | 311 | 0 | 1,065 | 6.1% | 6.5% | 6.4% | 0.0% | 6.4% |
| 4:00 PM | 304 | 527 | 391 | 0 | 1,222 | 7.1% | 7.0% | 8.0% | 0.0% | 7.3% |
| 5:00 PM | 366 | 633 | 473 | 0 | 1,472 | 8.5% | 8.4% | 9.7% | 0.0% | 8.8% |
| 6:00 PM | 331 | 570 | 422 | 0 | 1,323 | 7.7% | 7.5% | 8.6% | 0.0% | 7.9% |
| 7:00 PM | 231 | 463 | 257 | 0 | 952 | 5.4% | 6.1% | 5.3% | 0.0% | 5.7% |
| 8:00 PM | 251 | 562 | 240 | 0 | 1,053 | 5.9% | 7.4% | 4.9% | 0.0% | 6.3% |
| 9:00 PM | 129 | 298 | 173 | 0 | 600 | 3.0% | 3.9% | 3.5% | 0.0% | 3.6% |
| 10:00 PM | 82 | 182 | 107 | 0 | 370 | 1.9% | 2.4% | 2.2% | 0.0% | 2.2% |
| 11:00 PM | 41 | 113 | 48 | 0 | 203 | 1.0% | 1.5% | 1.0% | 0.0% | 1.2% |
| Total | 4,292 | 7,560 | 4,882 | 0 | 16,735 | | | | | |
| Right Turn Percent | 0.0% | 47.0% | 21.8% | 0.0% | | | | | | |
| Remove RT | Yes | | | | | | | | | |

| Right Turn Capacity Check | | | | | |
|---------------------------|-----|-------|-----|-------|------------------------|
| Begin Time | NB | WB RT | SB | EB RT | |
| 12:00 AM | 22 | 0 | 51 | 5 | |
| 1:00 AM | 9 | 0 | 15 | 2 | |
| 2:00 AM | 16 | 0 | 21 | 5 | |
| 3:00 AM | 8 | 0 | 12 | 1 | |
| 4:00 AM | 20 | 0 | 14 | 4 | |
| 5:00 AM | 76 | 0 | 67 | 19 | |
| 6:00 AM | 161 | 0 | 259 | 35 | |
| 7:00 AM | 242 | 0 | 415 | 55 | |
| 8:00 AM | 251 | 0 | 357 | 61 | |
| 9:00 AM | 270 | 0 | 321 | 66 | |
| 10:00 AM | 252 | 0 | 417 | 48 | |
| 11:00 AM | 244 | 0 | 424 | 62 | |
| 12:00 PM | 270 | 0 | 461 | 60 | |
| 1:00 PM | 237 | 0 | 456 | 53 | |
| 2:00 PM | 218 | 0 | 431 | 61 | |
| 3:00 PM | 262 | 0 | 492 | 68 | |
| 4:00 PM | 304 | 0 | 527 | 85 | |
| 5:00 PM | 366 | 0 | 633 | 103 | Less than 70% Capacity |
| 6:00 PM | 331 | 0 | 570 | 92 | |
| 7:00 PM | 231 | 0 | 463 | 56 | |
| 8:00 PM | 251 | 0 | 562 | 52 | |
| 9:00 PM | 129 | 0 | 298 | 38 | |
| 10:00 PM | 82 | 0 | 182 | 23 | |
| 11:00 PM | 41 | 0 | 113 | 10 | |

CSAH 9 at CSAH 60 Approach Volumes - Signal Warrant Analysis

| Begin Time | NB | SB | EB | WB |
|------------|-----|-----|-----|----|
| 12:00 AM | 22 | 51 | 20 | 0 |
| 1:00 AM | 9 | 15 | 6 | 0 |
| 2:00 AM | 16 | 21 | 16 | 0 |
| 3:00 AM | 8 | 12 | 3 | 0 |
| 4:00 AM | 20 | 14 | 13 | 0 |
| 5:00 AM | 76 | 67 | 69 | 0 |
| 6:00 AM | 161 | 259 | 125 | 0 |
| 7:00 AM | 242 | 415 | 196 | 0 |
| 8:00 AM | 251 | 357 | 218 | 0 |
| 9:00 AM | 270 | 321 | 238 | 0 |
| 10:00 AM | 252 | 417 | 173 | 0 |
| 11:00 AM | 244 | 424 | 223 | 0 |
| 12:00 PM | 270 | 461 | 214 | 0 |
| 1:00 PM | 237 | 456 | 191 | 0 |
| 2:00 PM | 218 | 431 | 220 | 0 |
| 3:00 PM | 262 | 492 | 243 | 0 |
| 4:00 PM | 304 | 527 | 306 | 0 |
| 5:00 PM | 366 | 633 | 370 | 0 |
| 6:00 PM | 331 | 570 | 330 | 0 |
| 7:00 PM | 231 | 463 | 201 | 0 |
| 8:00 PM | 251 | 562 | 188 | 0 |
| 9:00 PM | 129 | 298 | 135 | 0 |
| 10:00 PM | 82 | 182 | 84 | 0 |
| 11:00 PM | 41 | 113 | 38 | 0 |

Note: Eastbound right turn volume is excluded

Table B-6
CSAH 9 at CSAH 60
Forecast 2030 - Without CSAH 60 Extension

| Raw Approach Volume | | | | | | | | | | |
|---------------------------|--------------|---------------|--------------|-------------|---------------|------|------|------|------|------|
| Growth Rate | 3.0% | 2.6% | 3.0% | | | | | | | |
| Begin Time | NB | SB | EB | WB | Total | NB | SB | EB | WB | |
| 12:00 AM | 39 | 85 | 45 | 0 | 169 | 0.5% | 0.7% | 0.5% | 0.0% | 0.6% |
| 1:00 AM | 16 | 25 | 14 | 0 | 55 | 0.2% | 0.2% | 0.2% | 0.0% | 0.2% |
| 2:00 AM | 29 | 34 | 37 | 0 | 101 | 0.4% | 0.3% | 0.4% | 0.0% | 0.3% |
| 3:00 AM | 14 | 20 | 8 | 0 | 41 | 0.2% | 0.2% | 0.1% | 0.0% | 0.1% |
| 4:00 AM | 35 | 24 | 29 | 0 | 88 | 0.5% | 0.2% | 0.3% | 0.0% | 0.3% |
| 5:00 AM | 137 | 112 | 159 | 0 | 409 | 1.8% | 0.9% | 1.8% | 0.0% | 1.4% |
| 6:00 AM | 289 | 434 | 287 | 0 | 1,010 | 3.7% | 3.4% | 3.3% | 0.0% | 3.5% |
| 7:00 AM | 436 | 695 | 452 | 0 | 1,582 | 5.6% | 5.5% | 5.1% | 0.0% | 5.4% |
| 8:00 AM | 451 | 597 | 501 | 0 | 1,549 | 5.9% | 4.7% | 5.7% | 0.0% | 5.3% |
| 9:00 AM | 485 | 537 | 548 | 0 | 1,570 | 6.3% | 4.2% | 6.2% | 0.0% | 5.4% |
| 10:00 AM | 453 | 698 | 397 | 0 | 1,548 | 5.9% | 5.5% | 4.5% | 0.0% | 5.3% |
| 11:00 AM | 438 | 709 | 513 | 0 | 1,660 | 5.7% | 5.6% | 5.8% | 0.0% | 5.7% |
| 12:00 PM | 485 | 772 | 491 | 0 | 1,748 | 6.3% | 6.1% | 5.6% | 0.0% | 6.0% |
| 1:00 PM | 426 | 763 | 440 | 0 | 1,629 | 5.5% | 6.0% | 5.0% | 0.0% | 5.6% |
| 2:00 PM | 393 | 722 | 505 | 0 | 1,619 | 5.1% | 5.7% | 5.7% | 0.0% | 5.6% |
| 3:00 PM | 471 | 823 | 560 | 0 | 1,854 | 6.1% | 6.5% | 6.4% | 0.0% | 6.4% |
| 4:00 PM | 546 | 883 | 703 | 0 | 2,132 | 7.1% | 7.0% | 8.0% | 0.0% | 7.3% |
| 5:00 PM | 658 | 1,060 | 851 | 0 | 2,568 | 8.5% | 8.4% | 9.7% | 0.0% | 8.8% |
| 6:00 PM | 595 | 955 | 758 | 0 | 2,308 | 7.7% | 7.5% | 8.6% | 0.0% | 7.9% |
| 7:00 PM | 416 | 776 | 462 | 0 | 1,654 | 5.4% | 6.1% | 5.3% | 0.0% | 5.7% |
| 8:00 PM | 451 | 940 | 432 | 0 | 1,824 | 5.9% | 7.4% | 4.9% | 0.0% | 6.3% |
| 9:00 PM | 232 | 499 | 310 | 0 | 1,041 | 3.0% | 3.9% | 3.5% | 0.0% | 3.6% |
| 10:00 PM | 147 | 304 | 193 | 0 | 644 | 1.9% | 2.4% | 2.2% | 0.0% | 2.2% |
| 11:00 PM | 75 | 190 | 86 | 0 | 351 | 1.0% | 1.5% | 1.0% | 0.0% | 1.2% |
| Total | 7,716 | 12,657 | 8,784 | 0 | 29,157 | | | | | |
| Right Turn Percent | 0.0% | 47.0% | 21.8% | 0.0% | | | | | | |
| Remove RT | Yes | | | | | | | | | |

| Right Turn Capacity Check | | | | | |
|---------------------------|-----|-------|------|-------|------------------------|
| Begin Time | NB | WB RT | SB | EB RT | |
| 12:00 AM | 39 | 0 | 85 | 10 | |
| 1:00 AM | 16 | 0 | 25 | 3 | |
| 2:00 AM | 29 | 0 | 34 | 8 | |
| 3:00 AM | 14 | 0 | 20 | 2 | |
| 4:00 AM | 35 | 0 | 24 | 6 | |
| 5:00 AM | 137 | 0 | 112 | 35 | |
| 6:00 AM | 289 | 0 | 434 | 63 | |
| 7:00 AM | 436 | 0 | 695 | 98 | |
| 8:00 AM | 451 | 0 | 597 | 109 | |
| 9:00 AM | 485 | 0 | 537 | 119 | |
| 10:00 AM | 453 | 0 | 698 | 87 | |
| 11:00 AM | 438 | 0 | 709 | 112 | |
| 12:00 PM | 485 | 0 | 772 | 107 | |
| 1:00 PM | 426 | 0 | 763 | 96 | |
| 2:00 PM | 393 | 0 | 722 | 110 | |
| 3:00 PM | 471 | 0 | 823 | 122 | |
| 4:00 PM | 546 | 0 | 883 | 153 | |
| 5:00 PM | 658 | 0 | 1060 | 185 | More than 70% Capacity |
| 6:00 PM | 595 | 0 | 955 | 165 | |
| 7:00 PM | 416 | 0 | 776 | 101 | |
| 8:00 PM | 451 | 0 | 940 | 94 | |
| 9:00 PM | 232 | 0 | 499 | 68 | |
| 10:00 PM | 147 | 0 | 304 | 42 | |
| 11:00 PM | 75 | 0 | 190 | 19 | |

CSAH 9 at CSAH 60 Approach Volumes - Signal Warrant Analysis

| Begin Time | NB | SB | EB | WB |
|------------|-----|------|-----|----|
| 12:00 AM | 39 | 85 | 40 | 0 |
| 1:00 AM | 16 | 25 | 12 | 0 |
| 2:00 AM | 29 | 34 | 33 | 0 |
| 3:00 AM | 14 | 20 | 7 | 0 |
| 4:00 AM | 35 | 24 | 26 | 0 |
| 5:00 AM | 137 | 112 | 142 | 0 |
| 6:00 AM | 289 | 434 | 256 | 0 |
| 7:00 AM | 436 | 695 | 403 | 0 |
| 8:00 AM | 451 | 597 | 446 | 0 |
| 9:00 AM | 485 | 537 | 488 | 0 |
| 10:00 AM | 453 | 698 | 354 | 0 |
| 11:00 AM | 438 | 709 | 457 | 0 |
| 12:00 PM | 485 | 772 | 438 | 0 |
| 1:00 PM | 426 | 763 | 392 | 0 |
| 2:00 PM | 393 | 722 | 450 | 0 |
| 3:00 PM | 471 | 823 | 499 | 0 |
| 4:00 PM | 546 | 883 | 627 | 0 |
| 5:00 PM | 658 | 1060 | 758 | 0 |
| 6:00 PM | 595 | 955 | 676 | 0 |
| 7:00 PM | 416 | 776 | 411 | 0 |
| 8:00 PM | 451 | 940 | 385 | 0 |
| 9:00 PM | 232 | 499 | 277 | 0 |
| 10:00 PM | 147 | 304 | 172 | 0 |
| 11:00 PM | 75 | 190 | 77 | 0 |

Note: 50% of the eastbound right turn volume is included

Table B-7
CSAH 9 at CSAH 60
Forecast 2030 - With CSAH 60 Extension

| Raw Approach Volume | | | | | | | | | | |
|----------------------------|--------------|--------------|---------------|--------------|---------------|------|------|------|------|------|
| Forecast App. ADT | 8,435 | 9,615 | 13,750 | 9,100 | | | | | | |
| Begin Time | NB | SB | EB | WB | Total | NB | SB | EB | WB | |
| 12:00 AM | 43 | 65 | 71 | 47 | 225 | 0.5% | 0.7% | 0.5% | 0.5% | 0.6% |
| 1:00 AM | 17 | 19 | 22 | 14 | 72 | 0.2% | 0.2% | 0.2% | 0.2% | 0.2% |
| 2:00 AM | 32 | 26 | 58 | 39 | 155 | 0.4% | 0.3% | 0.4% | 0.4% | 0.4% |
| 3:00 AM | 15 | 15 | 12 | 8 | 51 | 0.2% | 0.2% | 0.1% | 0.1% | 0.1% |
| 4:00 AM | 39 | 18 | 46 | 31 | 133 | 0.5% | 0.2% | 0.3% | 0.3% | 0.3% |
| 5:00 AM | 150 | 85 | 249 | 165 | 649 | 1.8% | 0.9% | 1.8% | 1.8% | 1.6% |
| 6:00 AM | 315 | 330 | 449 | 297 | 1,392 | 3.7% | 3.4% | 3.3% | 3.3% | 3.4% |
| 7:00 AM | 476 | 528 | 707 | 468 | 2,180 | 5.6% | 5.5% | 5.1% | 5.1% | 5.3% |
| 8:00 AM | 494 | 453 | 784 | 519 | 2,250 | 5.9% | 4.7% | 5.7% | 5.7% | 5.5% |
| 9:00 AM | 530 | 408 | 858 | 568 | 2,364 | 6.3% | 4.2% | 6.2% | 6.2% | 5.8% |
| 10:00 AM | 496 | 530 | 621 | 411 | 2,059 | 5.9% | 5.5% | 4.5% | 4.5% | 5.0% |
| 11:00 AM | 479 | 539 | 803 | 531 | 2,351 | 5.7% | 5.6% | 5.8% | 5.8% | 5.7% |
| 12:00 PM | 530 | 587 | 769 | 509 | 2,395 | 6.3% | 6.1% | 5.6% | 5.6% | 5.9% |
| 1:00 PM | 466 | 580 | 689 | 456 | 2,191 | 5.5% | 6.0% | 5.0% | 5.0% | 5.4% |
| 2:00 PM | 429 | 548 | 791 | 523 | 2,291 | 5.1% | 5.7% | 5.7% | 5.7% | 5.6% |
| 3:00 PM | 515 | 625 | 877 | 580 | 2,597 | 6.1% | 6.5% | 6.4% | 6.4% | 6.3% |
| 4:00 PM | 597 | 670 | 1,101 | 729 | 3,097 | 7.1% | 7.0% | 8.0% | 8.0% | 7.6% |
| 5:00 PM | 719 | 805 | 1,332 | 882 | 3,737 | 8.5% | 8.4% | 9.7% | 9.7% | 9.1% |
| 6:00 PM | 650 | 725 | 1,187 | 786 | 3,349 | 7.7% | 7.5% | 8.6% | 8.6% | 8.2% |
| 7:00 PM | 455 | 589 | 723 | 478 | 2,246 | 5.4% | 6.1% | 5.3% | 5.3% | 5.5% |
| 8:00 PM | 494 | 714 | 677 | 448 | 2,333 | 5.9% | 7.4% | 4.9% | 4.9% | 5.7% |
| 9:00 PM | 253 | 379 | 486 | 322 | 1,440 | 3.0% | 3.9% | 3.5% | 3.5% | 3.5% |
| 10:00 PM | 161 | 231 | 301 | 200 | 893 | 1.9% | 2.4% | 2.2% | 2.2% | 2.2% |
| 11:00 PM | 82 | 144 | 135 | 90 | 451 | 1.0% | 1.5% | 1.0% | 1.0% | 1.1% |
| Total | 8,435 | 9,615 | 13,750 | 9,100 | 40,900 | | | | | |
| Right Turn Percent | 29.1% | 51.7% | 16.4% | 4.5% | | | | | | |
| Remove RT | Yes | | | | | | | | | |

| Right Turn Capacity Check | | | | |
|----------------------------------|------|-------|-----|-------|
| Begin Time | EB | NB RT | WB | SB RT |
| 12:00 AM | 71 | 12 | 47 | 33 |
| 1:00 AM | 22 | 5 | 14 | 10 |
| 2:00 AM | 58 | 9 | 39 | 14 |
| 3:00 AM | 12 | 4 | 8 | 8 |
| 4:00 AM | 46 | 11 | 31 | 9 |
| 5:00 AM | 249 | 44 | 165 | 44 |
| 6:00 AM | 449 | 92 | 297 | 171 |
| 7:00 AM | 707 | 139 | 468 | 273 |
| 8:00 AM | 784 | 144 | 519 | 235 |
| 9:00 AM | 858 | 154 | 568 | 211 |
| 10:00 AM | 621 | 144 | 411 | 274 |
| 11:00 AM | 803 | 139 | 531 | 279 |
| 12:00 PM | 769 | 154 | 509 | 303 |
| 1:00 PM | 689 | 135 | 456 | 300 |
| 2:00 PM | 791 | 125 | 523 | 284 |
| 3:00 PM | 877 | 150 | 580 | 323 |
| 4:00 PM | 1101 | 173 | 729 | 347 |
| 5:00 PM | 1332 | 209 | 882 | 416 |
| 6:00 PM | 1187 | 189 | 786 | 375 |
| 7:00 PM | 723 | 132 | 478 | 305 |
| 8:00 PM | 677 | 144 | 448 | 370 |
| 9:00 PM | 486 | 74 | 322 | 196 |
| 10:00 PM | 301 | 47 | 200 | 119 |
| 11:00 PM | 135 | 24 | 90 | 75 |

CSAH 9 at CSAH 60 Approach Volumes - Signal Warrant Analysis

| Begin Time | NB | SB | EB | WB |
|------------|-----|-----|------|-----|
| 12:00 AM | 37 | 48 | 71 | 47 |
| 1:00 AM | 15 | 14 | 22 | 14 |
| 2:00 AM | 28 | 19 | 58 | 39 |
| 3:00 AM | 13 | 11 | 12 | 8 |
| 4:00 AM | 33 | 13 | 46 | 31 |
| 5:00 AM | 128 | 63 | 249 | 165 |
| 6:00 AM | 270 | 244 | 449 | 297 |
| 7:00 AM | 407 | 391 | 707 | 468 |
| 8:00 AM | 422 | 336 | 784 | 519 |
| 9:00 AM | 453 | 303 | 858 | 568 |
| 10:00 AM | 424 | 393 | 621 | 411 |
| 11:00 AM | 409 | 399 | 803 | 531 |
| 12:00 PM | 453 | 435 | 769 | 509 |
| 1:00 PM | 398 | 430 | 689 | 456 |
| 2:00 PM | 367 | 406 | 791 | 523 |
| 3:00 PM | 440 | 463 | 877 | 580 |
| 4:00 PM | 510 | 497 | 1101 | 729 |
| 5:00 PM | 614 | 597 | 1332 | 882 |
| 6:00 PM | 556 | 538 | 1187 | 786 |
| 7:00 PM | 389 | 437 | 723 | 478 |
| 8:00 PM | 422 | 530 | 677 | 448 |
| 9:00 PM | 216 | 281 | 486 | 322 |
| 10:00 PM | 138 | 171 | 301 | 200 |
| 11:00 PM | 70 | 107 | 135 | 90 |

Note: 50% of the northbound and southbound right turn volume is included

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Appendix C: Traffic Signal Warrant Analysis

**TABLE C-1
SIGNAL WARRANT ANALYSIS - 2010 FORECAST
WARRANT 1
LOCATION: CSAH 9 at Highview Avenue**

Count Date: **2010 Forecast**
 Source: **See Footnote**
 Factor: **1.00**
 Population < 10,000? **NO**
 Speed over 40 mph? **YES**

| APPROACH | DESCRIPTION | NUMBER OF LANES | SPEED (MPH) |
|------------------|-------------------------------------|-----------------|-------------|
| Major Approach 1 | CSAH 9, West Approach, EB | 4 | 55 |
| Major Approach 3 | CSAH 9, East Approach, WB | 4 | 55 |
| Minor Approach 2 | Highview Avenue, South Approach, NB | 2 | 55 |
| Minor Approach 4 | Highview Avenue, North Approach, SB | 2 | 45 |

If population is less than 10,000; or the major street speed is over 40 mph, seventy percent factor can be applied. Apply seventy percent factor? **YES**

| HOUR | MAJOR STREET | | | | | | MINOR STREET | | | | | | | | WARRANT MET SAME HOURS ON MAJOR AND MINOR STREETS | | | | | | |
|---------------|-----------------|-----|-----------|---------------|---------|-----------------|-----------------|-----|--------------------------|---------|-----------------|--------------|--------------------------|-----------------|---|--------------|-----------------|----------|-----------------|----------|----------|
| | APPROACH VOLUME | | | WARRANT MET * | | | APPROACH VOLUME | | WARRANT MET APPROACH 2 * | | | | WARRANT MET APPROACH 4 * | | | | Cond. A | | 7 & (A&B) Comb. | | |
| | 1 | 3 | TOTAL 1+3 | Cond. A | Cond. B | 7 & (A&B) Comb. | 2 | 4 | Cond. A | Cond. B | 7 & (A&B) Comb. | Cond. A | Cond. B | 7 & (A&B) Comb. | Cond. A | Cond. B | 7 & (A&B) Comb. | 80% of A | 80% of B | | |
| | | | | 420 | 630 | 80% of A 336 | 80% of B 504 | | | 140 | 70 | 80% of A 112 | 80% of B 56 | 140 | 70 | 80% of A 112 | 80% of B 56 | Cond. A | Cond. B | 80% of A | 80% of B |
| 12 - 1 AM | 43 | 42 | 85 | | | | | 6 | 9 | | | | | | | | | | | | |
| 1 - 2 AM | 20 | 25 | 45 | | | | | 10 | 2 | | | | | | | | | | | | |
| 2 - 3 AM | 12 | 21 | 33 | | | | | 4 | 2 | | | | | | | | | | | | |
| 3 - 4 AM | 13 | 14 | 27 | | | | | 3 | 2 | | | | | | | | | | | | |
| 4 - 5 AM | 18 | 24 | 42 | | | | | 8 | 4 | | | | | | | | | | | | |
| 5 - 6 AM | 59 | 94 | 153 | | | | | 15 | 22 | | | | | | | | | | | | |
| 6 - 7 AM | 249 | 209 | 458 | X | | X | | 28 | 48 | | | | | | | | | | | | |
| 7 - 8 AM | 344 | 332 | 677 | X | X | X | X | 76 | 105 | | X | X | | X | X | | X | X | | X | X |
| 8 - 9 AM | 362 | 373 | 734 | X | X | X | X | 78 | 96 | | X | X | | X | X | | X | X | | X | X |
| 9 - 10 AM | 341 | 332 | 673 | X | X | X | X | 70 | 91 | | X | X | | X | X | | X | X | | X | X |
| 10 - 11 AM | 417 | 378 | 796 | X | X | X | X | 75 | 105 | | X | X | | X | X | | X | X | | X | X |
| 11 - Noon | 369 | 381 | 750 | X | X | X | X | 89 | 96 | | X | X | | X | X | | X | X | | X | X |
| 12 - 1 PM | 374 | 411 | 786 | X | X | X | X | 93 | 100 | | X | X | | X | X | | X | X | | X | X |
| 1 - 2 PM | 393 | 397 | 790 | X | X | X | X | 81 | 101 | | X | X | | X | X | | X | X | | X | X |
| 2 - 3 PM | 399 | 407 | 806 | X | X | X | X | 81 | 88 | | X | X | | X | X | | X | X | | X | X |
| 3 - 4 PM | 450 | 464 | 913 | X | X | X | X | 96 | 107 | | X | X | | X | X | | X | X | | X | X |
| 4 - 5 PM | 460 | 516 | 977 | X | X | X | X | 116 | 136 | | X | X | X | X | X | | X | X | X | X | X |
| 5 - 6 PM | 505 | 577 | 1,083 | X | X | X | X | 134 | 213 | | X | X | X | X | X | X | X | X | X | X | X |
| 6 - 7 PM | 464 | 515 | 979 | X | X | X | X | 96 | 161 | | X | X | X | X | X | X | X | X | X | X | X |
| 7 - 8 PM | 415 | 363 | 778 | X | X | X | X | 76 | 96 | | X | X | X | X | X | X | X | X | X | X | X |
| 8 - 9 PM | 468 | 356 | 824 | X | X | X | X | 86 | 88 | | X | X | X | X | X | X | X | X | X | X | X |
| 9 - 10 PM | 296 | 231 | 528 | X | | X | X | 52 | 53 | | | | | | | | | | | | |
| 10 - 11 PM | 171 | 147 | 317 | | | | | 24 | 28 | | | | | | | | | | | | |
| 11 - Midnight | 97 | 75 | 172 | | | | | 12 | 15 | | | | | | | | | | | | |


SUMMARY OF RESULTS:

Warrant 1 - Cond. A was not met: 2 hours satisfied requirements
 Warrant 1 - Cond. B was met: 14 hours satisfied requirements
 Warrant 1 - Combine A & B was not met: 3 hours satisfied requirements

Note:

* Warrant volume requirements are from the 2005 Minnesota Manual on Uniform Traffic Control Devices.

Source: Alliant Engineering, Inc. and using background growth rates provided by Dakota County.




Warrant Met for 4 Hours

* NOTE: 80 vph applies as the lower threshold volume for a minor street approach with two or more lanes.

** The first number refers to the number of lanes of approach on the major street and the second number refers to the number of lanes of approach on the minor street.

**CSAH 9 at Highview Avenue
SIGNAL WARRANT ANALYSIS
Forecast 2010 Weekday Volume**

**TABLE C-2
WARRANT 2
(Speed Above 40 MPH on Major Street)**



Warrant Met for 2 Hours

* NOTE: 100 vph applies as the lower threshold volume for a minor street approach with two or more lanes.

** The first number refers to the number of lanes of approach on the major street and the second number refers to the number of lanes of approach on the minor street.

**CSAH 9 at Highview Avenue
SIGNAL WARRANT ANALYSIS
Forecast 2010 Weekday Volume**

**TABLE C-3
WARRANT 3
(Speed Above 40 MPH on Major Street)**

TABLE C-4
SIGNAL WARRANT ANALYSIS - 2030 FORECAST
WARRANT 1
LOCATION: CSAH 9 at Highview Avenue

Count Date: **2030 Forecast**
 Source: **See Footnote**
 Factor: **1.00**
 Population < 10,000? **NO**
 Speed over 40 mph? **YES**

| APPROACH | DESCRIPTION | NUMBER OF LANES | SPEED (MPH) |
|------------------|-------------------------------------|-----------------|-------------|
| Major Approach 1 | CSAH 9, West Approach, EB | 4 | 55 |
| Major Approach 3 | CSAH 9, East Approach, WB | 4 | 55 |
| Minor Approach 2 | Highview Avenue, South Approach, NB | 2 | 55 |
| Minor Approach 4 | Highview Avenue, North Approach, SB | 2 | 45 |

If population is less than 10,000; or the major street speed is over 40 mph, seventy percent factor can be applied. Apply seventy percent factor? **YES**

| HOUR | MAJOR STREET | | | | | | MINOR STREET | | | | | | | | WARRANT MET SAME HOURS ON MAJOR AND MINOR STREETS | | | | | | | | |
|---------------|-----------------|-----|-----------|---------------|---------|------------------------------|-----------------|-----|--------------------------|---------|-----------------|----------|--------------------------|---------|---|-----------------|----------|----------|-----------------|---------|----------|----------|---|
| | APPROACH VOLUME | | | WARRANT MET * | | | APPROACH VOLUME | | WARRANT MET APPROACH 2 * | | | | WARRANT MET APPROACH 4 * | | | | Cond. A | | 7 & (A&B) Comb. | | | | |
| | 1 | 3 | TOTAL 1+3 | Cond. A | Cond. B | 7 & (A&B) Comb. | 2 | 4 | Cond. A | Cond. B | 7 & (A&B) Comb. | 80% of A | 80% of B | Cond. A | Cond. B | 7 & (A&B) Comb. | 80% of A | 80% of B | | | | | |
| | | | | 420 | 630 | 336 80% of A 504 80% of B | | | 140 | 70 | 7 & (A&B) Comb. | 112 | 56 | 140 | 70 | 7 & (A&B) Comb. | 112 | 56 | Cond. A | Cond. B | 80% of A | 80% of B | |
| 12 - 1 AM | 69 | 66 | 135 | | | | 12 | 11 | | | | | | | | | | | | | | | |
| 1 - 2 AM | 33 | 39 | 72 | | | | 19 | 3 | | | | | | | | | | | | | | | |
| 2 - 3 AM | 19 | 34 | 53 | | | | 8 | 2 | | | | | | | | | | | | | | | |
| 3 - 4 AM | 21 | 22 | 43 | | | | 6 | 2 | | | | | | | | | | | | | | | |
| 4 - 5 AM | 29 | 37 | 66 | | | | 16 | 6 | | | | | | | | | | | | | | | |
| 5 - 6 AM | 94 | 149 | 244 | | | | 29 | 28 | | | | | | | | | | | | | | | |
| 6 - 7 AM | 398 | 331 | 729 | X | X | X | 55 | 61 | | | | | | | | | | X | | | | | X |
| 7 - 8 AM | 551 | 525 | 1,077 | X | X | X | 149 | 133 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 8 - 9 AM | 579 | 590 | 1,168 | X | X | X | 152 | 121 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 9 - 10 AM | 546 | 525 | 1,071 | X | X | X | 137 | 115 | | X | X | X | | | X | X | X | | X | X | X | X | X |
| 10 - 11 AM | 668 | 598 | 1,266 | X | X | X | 146 | 133 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 11 - Noon | 591 | 603 | 1,194 | X | X | X | 173 | 121 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 12 - 1 PM | 599 | 651 | 1,250 | X | X | X | 182 | 126 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 1 - 2 PM | 628 | 629 | 1,257 | X | X | X | 159 | 128 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 2 - 3 PM | 639 | 644 | 1,283 | X | X | X | 158 | 112 | X | X | X | X | | | X | | X | X | X | X | X | X | X |
| 3 - 4 PM | 719 | 734 | 1,453 | X | X | X | 188 | 135 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 4 - 5 PM | 737 | 817 | 1,554 | X | X | X | 226 | 173 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 5 - 6 PM | 809 | 914 | 1,722 | X | X | X | 263 | 269 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 6 - 7 PM | 742 | 815 | 1,557 | X | X | X | 188 | 205 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 7 - 8 PM | 664 | 575 | 1,239 | X | X | X | 149 | 122 | X | X | X | X | | | X | X | X | X | X | X | X | X | X |
| 8 - 9 PM | 749 | 563 | 1,311 | X | X | X | 169 | 112 | X | X | X | X | | | X | | X | X | X | X | X | X | X |
| 9 - 10 PM | 474 | 366 | 840 | X | X | X | 102 | 67 | | X | | X | | | | | X | | X | | X | | X |
| 10 - 11 PM | 273 | 232 | 505 | X | | X | 47 | 36 | | | | | | | | | | | | | | | |
| 11 - Midnight | 155 | 119 | 273 | | | | 24 | 19 | | | | | | | | | | | | | | | |


SUMMARY OF RESULTS:

Warrant 1 - Cond. A was met: 13 hours satisfied requirements
 Warrant 1 - Cond. B was met: 15 hours satisfied requirements
 Warrant 1 - Combine A & B was met: 14 hours satisfied requirements

Note:

* Warrant volume requirements are from the 2005 Minnesota Manual on Uniform Traffic Control Devices.

Source: Alliant Engineering, Inc. and using background growth rates provided by Dakota County.




Warrant Met for 15 Hours

* NOTE: 80 vph applies as the lower threshold volume for a minor street approach with two or more lanes.

** The first number refers to the number of lanes of approach on the major street and the second number refers to the number of lanes of approach on the minor street.

**CSAH 9 at Highview Avenue
SIGNAL WARRANT ANALYSIS
Forecast 2030 Weekday Volume**

**TABLE C-5
WARRANT 2
(Speed Above 40 MPH on Major Street)**



Warrant Met for 14 Hours

* NOTE: 100 vph applies as the lower threshold volume for a minor street approach with two or more lanes.

** The first number refers to the number of lanes of approach on the major street and the second number refers to the number of lanes of approach on the minor street.

**CSAH 9 at Highview Avenue
SIGNAL WARRANT ANALYSIS
Forecast 2030 Weekday Volume**

**TABLE C-6
WARRANT 3
(Speed Above 40 MPH on Major Street)**

TABLE C-7
SIGNAL WARRANT ANALYSIS - 2010 FORECAST WITHOUT EXTENSION
WARRANT 1
LOCATION: CSAH 9 at CSAH 60

Count Date: **2010 Forecast - Without Extension**
 Source: **See Footnote**
 Factor: **1.00**
 Population < 10,000? **NO**
 Speed over 40 mph? **YES**

| APPROACH | DESCRIPTION | NUMBER OF LANES | SPEED (MPH) |
|------------------|----------------------------|-----------------|-------------|
| Major Approach 1 | CSAH 9, South Approach, NB | 3 | 55 |
| Major Approach 3 | CSAH 9, North Approach, SB | 3 | 55 |
| Minor Approach 2 | CSAH 60, West Approach, EB | 2 | 45 |
| Minor Approach 4 | -- | | |

If population is less than 10,000; or the major street speed is over 40 mph, seventy percent factor can be applied. Apply seventy percent factor? **YES**

| HOUR | MAJOR STREET | | | | | | MINOR STREET | | | | | | | | WARRANT MET SAME HOURS ON MAJOR AND MINOR STREETS | | | | | | | | |
|---------------|-----------------|-----|-----------|---------------|---------|-----------------|-----------------|---|--------------------------|---------|-----------------|----------|--------------------------|---------|---|-----------------|----------|----------|-----------------|---------|----------|----------|---|
| | APPROACH VOLUME | | | WARRANT MET * | | | APPROACH VOLUME | | WARRANT MET APPROACH 2 * | | | | WARRANT MET APPROACH 4 * | | | | Cond. A | | 7 & (A&B) Comb. | | | | |
| | 1 | 3 | TOTAL 1+3 | Cond. A | Cond. B | 7 & (A&B) Comb. | 2 | 4 | Cond. A | Cond. B | 7 & (A&B) Comb. | 80% of A | 80% of B | Cond. A | Cond. B | 7 & (A&B) Comb. | 80% of A | 80% of B | Cond. A | Cond. B | 80% of A | 80% of B | |
| | | | | 420 | 630 | 336 504 | | | 140 | 70 | 112 56 | | | 105 | 53 | 84 42.4 | | | | | | | |
| 12 - 1 AM | 22 | 51 | 73 | | | | 20 | 0 | | | | | | | | | | | | | | | |
| 1 - 2 AM | 9 | 15 | 24 | | | | 6 | 0 | | | | | | | | | | | | | | | |
| 2 - 3 AM | 16 | 21 | 37 | | | | 16 | 0 | | | | | | | | | | | | | | | |
| 3 - 4 AM | 8 | 12 | 20 | | | | 3 | 0 | | | | | | | | | | | | | | | |
| 4 - 5 AM | 20 | 14 | 34 | | | | 13 | 0 | | | | | | | | | | | | | | | |
| 5 - 6 AM | 76 | 67 | 143 | | | | 69 | 0 | | | | | X | | | | | | | | | | |
| 6 - 7 AM | 161 | 259 | 420 | | | X | 125 | 0 | | X | X | X | X | | | | | | | | | X | |
| 7 - 8 AM | 242 | 415 | 657 | X | X | X | 196 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 8 - 9 AM | 251 | 357 | 608 | X | | X | 218 | 0 | X | X | X | X | X | | | | | | X | | X | X | X |
| 9 - 10 AM | 270 | 321 | 591 | X | | X | 238 | 0 | X | X | X | X | X | | | | | | X | | X | X | X |
| 10 - 11 AM | 252 | 417 | 669 | X | X | X | 173 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 11 - Noon | 244 | 424 | 667 | X | X | X | 223 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 12 - 1 PM | 270 | 461 | 731 | X | X | X | 214 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 1 - 2 PM | 237 | 456 | 693 | X | X | X | 191 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 2 - 3 PM | 218 | 431 | 649 | X | X | X | 220 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 3 - 4 PM | 262 | 492 | 754 | X | X | X | 243 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 4 - 5 PM | 304 | 527 | 831 | X | X | X | 306 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 5 - 6 PM | 366 | 633 | 999 | X | X | X | 370 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 6 - 7 PM | 331 | 570 | 901 | X | X | X | 330 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 7 - 8 PM | 231 | 463 | 695 | X | X | X | 201 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 8 - 9 PM | 251 | 562 | 813 | X | X | X | 188 | 0 | X | X | X | X | X | | | | | | X | X | X | X | X |
| 9 - 10 PM | 129 | 298 | 427 | X | | X | 135 | 0 | | X | X | X | X | | | | | | | | X | | |
| 10 - 11 PM | 82 | 182 | 263 | | | | 84 | 0 | | X | | | X | | | | | | | | | | |
| 11 - Midnight | 41 | 113 | 155 | | | | 38 | 0 | | | | | X | | | | | | | | | | |


SUMMARY OF RESULTS:

Warrant 1 - Cond. A was met: 14 hours satisfied requirements
 Warrant 1 - Cond. B was met: 12 hours satisfied requirements
 Warrant 1 - Combine A & B was met: 14 hours satisfied requirements

Note:

* Warrant volume requirements are from the 2005 Minnesota Manual on Uniform Traffic Control Devices.

Source: Alliant Engineering, Inc. and using background growth rates provided by Dakota County.




Warrant Met for 14 Hours

* NOTE: 80 vph applies as the lower threshold volume for a minor street approach with two or more lanes.

** The first number refers to the number of lanes of approach on the major street and the second number refers to the number of lanes of approach on the minor street.

**CSAH 9 at CSAH 60
SIGNAL WARRANT ANALYSIS
Forecast 2010 Weekday Volume**

**TABLE C-8
WARRANT 2
(Speed Above 40 MPH on Major Street)**



Warrant Met for 4 Hours

* NOTE: 100 vph applies as the lower threshold volume for a minor street approach with two or more lanes.

** The first number refers to the number of lanes of approach on the major street and the second number refers to the number of lanes of approach on the minor street.

**CSAH 9 at CSAH 60
SIGNAL WARRANT ANALYSIS
Forecast 2010 Weekday Volume**

**TABLE C-9
WARRANT 3
(Speed Above 40 MPH on Major Street)**

TABLE C-10
SIGNAL WARRANT ANALYSIS - 2030 FORECAST WITHOUT EXTENSION
WARRANT 1
LOCATION: CSAH 9 at CSAH 60

Count Date: **2030 Forecast - Without Extension**
Source: **See Footnote**
Factor: **1.00**
Population < 10,000? **NO**
Speed over 40 mph? **YES**

| APPROACH | DESCRIPTION | NUMBER OF LANES | SPEED (MPH) |
|------------------|----------------------------|-----------------|-------------|
| Major Approach 1 | CSAH 9, South Approach, NB | 3 | 55 |
| Major Approach 3 | CSAH 9, North Approach, SB | 3 | 55 |
| Minor Approach 2 | CSAH 60, West Approach, EB | 2 | 45 |
| Minor Approach 4 | -- | | |

If population is less than 10,000; or the major street speed is over 40 mph, seventy percent factor can be applied. Apply seventy percent factor? **YES**

| HOUR | MAJOR STREET | | | | | | MINOR STREET | | | | | | | | WARRANT MET SAME HOURS ON MAJOR AND MINOR STREETS | | | | | |
|---------------|-----------------|-------|-----------|---------------|---------|-----------------|-----------------|-----|--------------------------|---------|-----------------|----------|--------------------------|---------|---|-----------------|----------|----------|-----------------|----------|
| | APPROACH VOLUME | | | WARRANT MET * | | | APPROACH VOLUME | | WARRANT MET APPROACH 2 * | | | | WARRANT MET APPROACH 4 * | | | | Cond. A | | 7 & (A&B) Comb. | |
| | 1 | 3 | TOTAL 1+3 | Cond. A | Cond. B | 7 & (A&B) Comb. | 2 | 4 | Cond. A | Cond. B | 7 & (A&B) Comb. | 80% of A | 80% of B | Cond. A | Cond. B | 7 & (A&B) Comb. | 80% of A | 80% of B | | |
| | | | | 420 | 630 | 336 504 | | | 140 | 70 | 112 | 56 | 105 | 53 | 84 | 42.4 | Cond. A | Cond. B | 80% of A | 80% of B |
| 12 - 1 AM | 39 | 85 | 124 | | | | 40 | 0 | | | | | | | | | | | | |
| 1 - 2 AM | 16 | 25 | 41 | | | | 12 | 0 | | | | | | | | | | | | |
| 2 - 3 AM | 29 | 34 | 64 | | | | 33 | 0 | | | | | | | | | | | | |
| 3 - 4 AM | 14 | 20 | 34 | | | | 7 | 0 | | | | | | | | | | | | |
| 4 - 5 AM | 35 | 24 | 59 | | | | 26 | 0 | | | | | | | | | | | | |
| 5 - 6 AM | 137 | 112 | 250 | | | | 142 | 0 | X | X | X | X | | | | | | | | |
| 6 - 7 AM | 289 | 434 | 723 | X | X | X | X | 256 | 0 | X | X | X | X | | | X | X | X | X | X |
| 7 - 8 AM | 436 | 695 | 1,130 | X | X | X | X | 403 | 0 | X | X | X | X | | | X | X | X | X | X |
| 8 - 9 AM | 451 | 597 | 1,048 | X | X | X | X | 446 | 0 | X | X | X | X | | | X | X | X | X | X |
| 9 - 10 AM | 485 | 537 | 1,022 | X | X | X | X | 488 | 0 | X | X | X | X | | | X | X | X | X | X |
| 10 - 11 AM | 453 | 698 | 1,152 | X | X | X | X | 354 | 0 | X | X | X | X | | | X | X | X | X | X |
| 11 - Noon | 438 | 709 | 1,147 | X | X | X | X | 457 | 0 | X | X | X | X | | | X | X | X | X | X |
| 12 - 1 PM | 485 | 772 | 1,257 | X | X | X | X | 438 | 0 | X | X | X | X | | | X | X | X | X | X |
| 1 - 2 PM | 426 | 763 | 1,189 | X | X | X | X | 392 | 0 | X | X | X | X | | | X | X | X | X | X |
| 2 - 3 PM | 393 | 722 | 1,114 | X | X | X | X | 450 | 0 | X | X | X | X | | | X | X | X | X | X |
| 3 - 4 PM | 471 | 823 | 1,294 | X | X | X | X | 499 | 0 | X | X | X | X | | | X | X | X | X | X |
| 4 - 5 PM | 546 | 883 | 1,428 | X | X | X | X | 627 | 0 | X | X | X | X | | | X | X | X | X | X |
| 5 - 6 PM | 658 | 1,060 | 1,717 | X | X | X | X | 758 | 0 | X | X | X | X | | | X | X | X | X | X |
| 6 - 7 PM | 595 | 955 | 1,550 | X | X | X | X | 676 | 0 | X | X | X | X | | | X | X | X | X | X |
| 7 - 8 PM | 416 | 776 | 1,192 | X | X | X | X | 411 | 0 | X | X | X | X | | | X | X | X | X | X |
| 8 - 9 PM | 451 | 940 | 1,392 | X | X | X | X | 385 | 0 | X | X | X | X | | | X | X | X | X | X |
| 9 - 10 PM | 232 | 499 | 731 | X | X | X | X | 277 | 0 | X | X | X | X | | | X | X | X | X | X |
| 10 - 11 PM | 147 | 304 | 451 | X | | X | | 172 | 0 | X | X | X | X | | | X | | X | | |
| 11 - Midnight | 75 | 190 | 264 | | | | | 77 | 0 | | X | | X | | | | | | | |


SUMMARY OF RESULTS:

Warrant 1 - Cond. A was met: 17 hours satisfied requirements
Warrant 1 - Cond. B was met: 16 hours satisfied requirements
Warrant 1 - Combine A & B was met: 16 hours satisfied requirements

Note:

* Warrant volume requirements are from the 2005 Minnesota Manual on Uniform Traffic Control Devices.

Source: Alliant Engineering, Inc. and using background growth rates provided by Dakota County.




Warrant Met for 16 Hours

* NOTE: 80 vph applies as the lower threshold volume for a minor street approach with two or more lanes.

** The first number refers to the number of lanes of approach on the major street and the second number refers to the number of lanes of approach on the minor street.

**CSAH 9 at CSAH 60
SIGNAL WARRANT ANALYSIS
Forecast 2030 Weekday Volume**

**TABLE C-11
WARRANT 2
(Speed Above 40 MPH on Major Street)**



Warrant Met for 16 Hours

* NOTE: 100 vph applies as the lower threshold volume for a minor street approach with two or more lanes.

** The first number refers to the number of lanes of approach on the major street and the second number refers to the number of lanes of approach on the minor street.

**CSAH 9 at CSAH 60
SIGNAL WARRANT ANALYSIS
Forecast 2030 Weekday Volume**

**TABLE C-12
WARRANT 3
(Speed Above 40 MPH on Major Street)**

TABLE C-13
SIGNAL WARRANT ANALYSIS - 2030 FORECAST WITH EXTENSION
WARRANT 1
LOCATION: CSAH 9 at CSAH 60

Count Date: **2030 Forecast - With Extension**
 Source: **See Footnote**
 Factor: **1.00**
 Population < 10,000? **NO**
 Speed over 40 mph? **YES**

| APPROACH | DESCRIPTION | NUMBER OF LANES | SPEED (MPH) |
|------------------|----------------------------|-----------------|-------------|
| Major Approach 1 | CSAH 60, West Approach, EB | 4 | 55 |
| Major Approach 3 | CSAH 60, East Approach, WB | 4 | 55 |
| Minor Approach 2 | CSAH 9, South Approach, NB | 4 | 45 |
| Minor Approach 4 | CSAH 9, North Approach, SB | 4 | 45 |

If population is less than 10,000; or the major street speed is over 40 mph, seventy percent factor can be applied. Apply seventy percent factor? **YES**

| HOUR | MAJOR STREET | | | | | | MINOR STREET | | | | | | | | WARRANT MET SAME HOURS ON MAJOR AND MINOR STREETS | | | | | |
|---------------|-----------------|-----|-----------|---------------|---------|------------------------------|-----------------|-----|--------------------------|---------|-----------------------------|----------|--------------------------|---------|---|-----------------------------|----------|----------|-----------------|--|
| | APPROACH VOLUME | | | WARRANT MET * | | | APPROACH VOLUME | | WARRANT MET APPROACH 2 * | | | | WARRANT MET APPROACH 4 * | | | | Cond. A | | 7 & (A&B) Comb. | |
| | 1 | 3 | TOTAL 1+3 | Cond. A | Cond. B | 7 & (A&B) Comb. | 2 | 4 | Cond. A | Cond. B | 7 & (A&B) Comb. | 80% of A | 80% of B | Cond. A | Cond. B | 7 & (A&B) Comb. | 80% of A | 80% of B | | |
| | | | | 420 | 630 | 336 80% of A 504 80% of B | | | 140 | 70 | 112 80% of A 56 80% of B | | | 140 | 70 | 112 80% of A 56 80% of B | | | | |
| 12 - 1 AM | 71 | 47 | 118 | | | | 37 | 48 | | | | | | | | | | | | |
| 1 - 2 AM | 22 | 14 | 36 | | | | 15 | 14 | | | | | | | | | | | | |
| 2 - 3 AM | 58 | 39 | 97 | | | | 28 | 19 | | | | | | | | | | | | |
| 3 - 4 AM | 12 | 8 | 20 | | | | 13 | 11 | | | | | | | | | | | | |
| 4 - 5 AM | 46 | 31 | 77 | | | | 33 | 13 | | | | | | | | | | | | |
| 5 - 6 AM | 249 | 165 | 414 | | | X | 128 | 63 | | X | X | X | X | | | X | | | | |
| 6 - 7 AM | 449 | 297 | 746 | X | X | X | 270 | 244 | X | X | X | X | X | X | X | X | X | X | | |
| 7 - 8 AM | 707 | 468 | 1,176 | X | X | X | 407 | 391 | X | X | X | X | X | X | X | X | X | X | | |
| 8 - 9 AM | 784 | 519 | 1,304 | X | X | X | 422 | 336 | X | X | X | X | X | X | X | X | X | X | | |
| 9 - 10 AM | 858 | 568 | 1,426 | X | X | X | 453 | 303 | X | X | X | X | X | X | X | X | X | X | | |
| 10 - 11 AM | 621 | 411 | 1,033 | X | X | X | 424 | 393 | X | X | X | X | X | X | X | X | X | X | | |
| 11 - Noon | 803 | 531 | 1,334 | X | X | X | 409 | 399 | X | X | X | X | X | X | X | X | X | X | | |
| 12 - 1 PM | 769 | 509 | 1,278 | X | X | X | 453 | 435 | X | X | X | X | X | X | X | X | X | X | | |
| 1 - 2 PM | 689 | 456 | 1,145 | X | X | X | 398 | 430 | X | X | X | X | X | X | X | X | X | X | | |
| 2 - 3 PM | 791 | 523 | 1,314 | X | X | X | 367 | 406 | X | X | X | X | X | X | X | X | X | X | | |
| 3 - 4 PM | 877 | 580 | 1,457 | X | X | X | 440 | 463 | X | X | X | X | X | X | X | X | X | X | | |
| 4 - 5 PM | 1,101 | 729 | 1,830 | X | X | X | 510 | 497 | X | X | X | X | X | X | X | X | X | X | | |
| 5 - 6 PM | 1,332 | 882 | 2,213 | X | X | X | 614 | 597 | X | X | X | X | X | X | X | X | X | X | | |
| 6 - 7 PM | 1,187 | 786 | 1,973 | X | X | X | 556 | 538 | X | X | X | X | X | X | X | X | X | X | | |
| 7 - 8 PM | 723 | 478 | 1,201 | X | X | X | 389 | 437 | X | X | X | X | X | X | X | X | X | X | | |
| 8 - 9 PM | 677 | 448 | 1,125 | X | X | X | 422 | 530 | X | X | X | X | X | X | X | X | X | X | | |
| 9 - 10 PM | 486 | 322 | 808 | X | X | X | 216 | 281 | X | X | X | X | X | X | X | X | X | X | | |
| 10 - 11 PM | 301 | 200 | 501 | X | | X | 138 | 171 | | X | X | X | X | X | X | X | X | | | |
| 11 - Midnight | 135 | 90 | 225 | | | | 70 | 107 | | | | X | X | X | X | X | X | | | |


SUMMARY OF RESULTS:

Warrant 1 - Cond. A was met: 17 hours satisfied requirements
 Warrant 1 - Cond. B was met: 16 hours satisfied requirements
 Warrant 1 - Combine A & B was met: 16 hours satisfied requirements

Note:

* Warrant volume requirements are from the 2005 Minnesota Manual on Uniform Traffic Control Devices.

Source: Alliant Engineering, Inc. and using 2030 forecast ADT values provided by Dakota County.




Warrant Met for 16 Hours

* NOTE: 80 vph applies as the lower threshold volume for a minor street approach with two or more lanes.

** The first number refers to the number of lanes of approach on the major street and the second number refers to the number of lanes of approach on the minor street.

**CSAH 9 at CSAH 60
SIGNAL WARRANT ANALYSIS
Forecast 2030 Weekday Volume**

**TABLE C-14
WARRANT 2
(Speed Above 40 MPH on Major Street)**



Warrant Met for 16 Hours

* NOTE: 100 vph applies as the lower threshold volume for a minor street approach with two or more lanes.

** The first number refers to the number of lanes of approach on the major street and the second number refers to the number of lanes of approach on the minor street.

**CSAH 9 at CSAH 60
SIGNAL WARRANT ANALYSIS
Forecast 2030 Weekday Volume**

**TABLE C-15
WARRANT 3
(Speed Above 40 MPH on Major Street)**

Intersection Traffic Control Feasibility Study

CSAH 9 at Highview Avenue
CSAH 9 at CSAH 60 (185th Avenue)

Appendix D: RODEL Output Files

Table D-1. Scenario 6 - 2030 Roundabout AM Peak (CSAH 9 at Highview Avenue)

```

*****
*
* 31:3:09                2030 RAB OPT HI AM                56
*
*****
*
* E      (m)    5.50    7.30    5.50    7.30
* L'     (m)   27.30    0.00   27.40    0.00
* V      (m)    3.70    7.30    3.70    7.30
* RAD    (m)   57.90   24.38   57.90   24.38
* PHI    (d)   11.20   20.70   10.60   20.60
* DIA    (m)   48.77   48.77   48.77   48.77
* GRAD SEP      0      0      0      0
*
*
*****
* LEG NAME *PCU *VEH TURNS (1st exit, 2nd..U)*FLOF*CL* FLOW RATIO *FLOW TIME*
*          *   *
* HI SB   *1.02* 100  83  40  0 *1.00*90*0.65 1.143 0.65*15 45 75 *
* HI EB   *1.02*  19 440  63  0 *1.00*90*0.87 1.257 0.87*15 45 75 *
* HI NB   *1.02* 182 114  32  0 *1.00*90*0.82 1.235 0.82*15 45 75 *
* HI WB   *1.02*   8 451  98  0 *1.00*90*0.84 1.075 0.84*15 45 75 *
*
*          *   *
*          *   *
*          *   *
*****
*
* FLOW      veh      223    522    328    557
* CAPACITY  veh     1064   1843   1091   1853
* AVE DELAY mins    0.07   0.04   0.08   0.05
* MAX DELAY mins    0.10   0.06   0.11   0.05
* AVE QUEUE  veh      0      0      0      0
* MAX QUEUE  veh      0      0      1      0
*
*
*****

```

Table D-2. Scenario 6 - 2030 Roundabout PM Peak (CSAH 9 at Highview Avenue)

```

*****
*
* 31:3:09                2030 RAB OPT HI PM                47 *
*
*****
*
* E      (m)      5.50   7.30   5.50   7.30           * TIME PERIOD      min   90 *
* L'     (m)     27.30   0.00  27.40   0.00           * TIME SLICE       min   15 *
* V      (m)      3.70   7.30   3.70   7.30           * RESULTS PERIOD   min  15 75 *
* RAD    (m)     57.90  24.38  57.90  24.38         * TIME COST        $/hr 15.00 *
* PHI    (d)     11.20  20.70  10.60  20.60         * FLOW PERIOD      min  15 75 *
* DIA    (m)     48.77  48.77  48.77  48.77         * FLOW TYPE        pcu/veh  VEH *
* GRAD SEP      0      0      0      0           * FLOW PEAK        am/op/pm  PM *
*
*****
* LEG NAME *PCU *VEH TURNS (1st exit, 2nd..U)*FLOF*CL* FLOW RATIO *FLOW TIME*
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *
* HI SB    *1.02* 281 217 88 0           *1.00*90*0.90 1.240 0.90*15 45 75 *
* HI EB    *1.02* 10 554 185 0          *1.00*90*0.92 1.082 0.92*15 45 75 *
* HI NB    *1.02* 146 187 10 0          *1.00*90*0.68 1.261 0.68*15 45 75 *
* HI WB    *1.02* 34 701 77 0           *1.00*90*0.91 1.060 0.91*15 45 75 *
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *
* FLOW      veh      586   749   343   812           * AVEDEL    s      5.7 *
* CAPACITY  veh      930  1724   907  1724           * LOS      SIG    A *
* AVE DELAY mins     0.17  0.06   0.11  0.06           * LOS UNSIG   A *
* MAX DELAY mins     0.25  0.07   0.17  0.08           * * * * * * * * * * * * *
* AVE QUEUE veh        2     1     1     1           * VEHIC HRS    3.9 *
* MAX QUEUE veh        2     1     1     1           * COST        $     59 *
*
*****

```

Table D-3. Scenario 8 - 2010 Roundabout AM Peak (CSAH 9 at Highview Avenue)

```

*****
*
* 31:3:09                2010 RAB OPT HI AM                38 *
*
*****
*
* E      (m)    5.50   7.30   5.50   7.30                * TIME PERIOD      min   90 *
* L'    (m)    27.30   0.00  27.40   0.00                * TIME SLICE       min   15 *
* V      (m)    3.70   7.30   3.70   7.30                * RESULTS PERIOD   min  15 75 *
* RAD    (m)    57.90  24.38  57.90  24.38                * TIME COST        $/hr 15.00 *
* PHI    (d)    11.20  20.70  10.60  20.60                * FLOW PERIOD      min  15 75 *
* DIA    (m)    48.77  48.77  48.77  48.77                * FLOW TYPE        pcu/veh  VEH *
* GRAD SEP      0      0      0      0                * FLOW PEAK        am/op/pm  PM *
*
*****
* LEG NAME *PCU *VEH TURNS (1st exit, 2nd..U)*FLOF*CL* FLOW RATIO *FLOW TIME*
*          *   *
* HI SB    *1.02*  64   53   25   0                *1.00*90*0.65 1.143 0.65*15 45 75 *
* HI EB    *1.02*  11  279  40   0                *1.00*90*0.87 1.257 0.87*15 45 75 *
* HI NB    *1.02* 116   72   19   0                *1.00*90*0.82 1.235 0.82*15 45 75 *
* HI WB    *1.02*   5  287  61   0                *1.00*90*0.84 1.075 0.84*15 45 75 *
*          *   *
*          *   *
*          *   *
*          *   *
*****
*
* FLOW      veh      142   330   207   353                * AVEDEL    s     2.6 *
* CAPACITY  veh      1202  1904  1220  1910                * LOS      SIG     A *
* AVE DELAY mins     0.05   0.04   0.06   0.04                * LOS UNSIG   A *
* MAX DELAY mins     0.08   0.05   0.08   0.04                *
* AVE QUEUE  veh         0     0     0     0                * VEHIC HRS   0.8 *
* MAX QUEUE  veh         0     0     0     0                * COST      $     11 *
*
*****

```

Table D-4. Scenario 8 - 2010 Roundabout PM Peak (CSAH 9 at Highview Avenue)

```

*****
*
* 31:3:09                2010 RAB OPT HI PM                36 *
*
*****
*
* E      (m)    5.50   7.30   5.50   7.30          * TIME PERIOD      min   90 *
* L'     (m)    27.30  0.00  27.40  0.00          * TIME SLICE       min   15 *
* V      (m)    3.70   7.30   3.70   7.30          * RESULTS PERIOD   min  15 75 *
* RAD    (m)    57.90  24.38  57.90  24.38          * TIME COST        $/hr 15.00 *
* PHI    (d)    11.20  20.70  10.60  20.60          * FLOW PERIOD      min  15 75 *
* DIA    (m)    48.77  48.77  48.77  48.77          * FLOW TYPE        pcu/veh  VEH *
* GRAD SEP      0      0      0      0          * FLOW PEAK        am/op/pm  PM *
*
*****
* LEG NAME *PCU *VEH TURNS (1st exit, 2nd..U)*FLOF*CL* FLOW RATIO *FLOW TIME*
*          *   *
* HI SB    *1.02* 179 138 56 0          *1.00*90*0.90 1.240 0.90*15 45 75 *
* HI EB    *1.02* 6 352 117 0          *1.00*90*0.92 1.082 0.92*15 45 75 *
* HI NB    *1.02* 93 118 6 0           *1.00*90*0.68 1.261 0.68*15 45 75 *
* HI WB    *1.02* 22 444 50 0          *1.00*90*0.91 1.060 0.91*15 45 75 *
*          *   *
*          *   *
*          *   *
*****
*
* FLOW      veh      373   475   217   516          * AVEDEL   s      3.3 *
* CAPACITY  veh     1116  1826  1103  1829          * LOS     SIG     A *
* AVE DELAY mins    0.08  0.04  0.07  0.05          * LOS UNSIG   A *
* MAX DELAY mins    0.10  0.05  0.10  0.05          *
* AVE QUEUE  veh      1     0     0     0          * VEHIC HRS   1.5 *
* MAX QUEUE  veh      1     0     0     0          * COST      $     22 *
*
*****

```

Table D-5. Scenario 10 - 2010 Roundabout AM Peak (CSAH 9 at Highview Avenue)

```

*****
*
* 31:3:09                2010 SL RAB HI AM                39
*
*****
*
* E      (m)    4.90    4.90    4.90    4.90
* L'     (m)    6.00    6.00    6.00    6.00
* V      (m)    4.30    4.30    4.30    4.30
* RAD    (m)    25.00   25.00   25.00   25.00
* PHI    (d)    20.00   20.00   20.00   20.00
* DIA    (m)    50.00   50.00   50.00   50.00
* GRAD SEP      0      0      0      0
*
*****
* LEG NAME *PCU *VEH TURNS (1st exit, 2nd..U)*FLOF*CL* FLOW RATIO *FLOW TIME*
*          *   *
* HI SB    *1.02* 64 53 25 0 *1.00*90*0.65 1.143 0.65*15 45 75 *
* HI EB    *1.02* 11 279 40 0 *1.00*90*0.87 1.257 0.87*15 45 75 *
* HI NB    *1.02* 116 72 19 0 *1.00*90*0.82 1.235 0.82*15 45 75 *
* HI WB    *1.02* 5 287 61 0 *1.00*90*0.84 1.075 0.84*15 45 75 *
*          *   *
*          *   *
*          *   *
*****
*
* FLOW      veh      142    330    207    353
* CAPACITY  veh      1010   1143   1023   1148
* AVE DELAY mins    0.07    0.07    0.07    0.07
* MAX DELAY mins    0.09    0.09    0.09    0.09
* AVE QUEUE  veh      0      0      0      0
* MAX QUEUE  veh      0      0      0      0
*
*****
*
* AVEDEL    s      4.3
* LOS      SIG    A
* LOS UNSIG A
*
* VEHIC HRS 1.2
* COST      $     19
*
*****

```

Table D-6. Scenario 10 - 2010 Roundabout PM Peak (CSAH 9 at Highview Avenue)

```

*****
*
* 31:3:09                2010 SL RAB HI PM                37
*
*****
*
* E      (m)    4.90    4.90    4.90    4.90
* L'     (m)    6.00    6.00    6.00    6.00
* V      (m)    4.30    4.30    4.30    4.30
* RAD    (m)    25.00   25.00   25.00   25.00
* PHI    (d)    20.00   20.00   20.00   20.00
* DIA    (m)    50.00   50.00   50.00   50.00
* GRAD SEP      0      0      0      0
*
*****
* LEG NAME *PCU *VEH TURNS (1st exit, 2nd..U)*FLOF*CL* FLOW RATIO *FLOW TIME*
*          *   *
* HI SB    *1.02* 179 138 56 0 *1.00*90*0.90 1.240 0.90*15 45 75 *
* HI EB    *1.02* 6 352 117 0 *1.00*90*0.92 1.082 0.92*15 45 75 *
* HI NB    *1.02* 93 118 6 0 *1.00*90*0.68 1.261 0.68*15 45 75 *
* HI WB    *1.02* 22 444 50 0 *1.00*90*0.91 1.060 0.91*15 45 75 *
*          *   *
*          *   *
*          *   *
*****
*
* FLOW      veh      373    475    217    516
* CAPACITY  veh      932   1082    918   1083
* AVE DELAY mins    0.11   0.10   0.08   0.10
* MAX DELAY mins    0.13   0.11   0.12   0.12
* AVE QUEUE  veh      1      1      0      1
* MAX QUEUE  veh      1      1      0      1
*
*****

```


Table D-7. Scenario 4 - 2030 Roundabout AM Peak (CSAH 9 at CSAH 60)

```

*****
*
* 31:3:09                2030 RAB OPT 60 AM                56 *
*
*****
*
* E      (m)      8.53   8.53   8.53   8.53                * TIME PERIOD      min   90 *
* L'     (m)      0.00   0.00   0.00   0.00                * TIME SLICE       min   15 *
* V      (m)      8.53   8.53   8.53   8.53                * RESULTS PERIOD   min  15 75 *
* RAD    (m)     24.38  24.38  24.38  24.38                * TIME COST        $/hr 15.00 *
* PHI    (d)     16.50  30.50  24.50  23.50                * FLOW PERIOD      min  15 75 *
* DIA    (m)     48.77  48.77  48.77  48.77                * FLOW TYPE        pcu/veh  VEH *
* GRAD SEP      0      0      0      0                * FLOW PEAK        am/op/pm  PM *
*
*****
* LEG NAME *PCU *VEH TURNS (1st exit, 2nd..U)*FLOF*CL* FLOW RATIO *FLOW TIME*
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * *
* 60 SB    *1.02* 262 269 28 0                *1.00*90*0.55 1.418 0.55*15 45 75 *
* 60 EB    *1.02* 150 273 320 0               *1.00*90*0.85 1.174 0.85*15 45 75 *
* 60 NB    *1.02* 88 154 90 0                 *1.00*90*0.63 1.279 0.63*15 45 75 *
* 60 WB    *1.02* 26 302 206 0                *1.00*90*0.85 1.174 0.85*15 45 75 *
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * *
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * *
* FLOW      veh      559   743   332   534                * AVEDEL    s      2.7 *
* CAPACITY  veh     1930  1904  1854  1907                * LOS      SIG      A *
* AVE DELAY mins     0.04  0.05  0.04  0.04                * LOS UNSIG      A *
* MAX DELAY mins     0.08  0.07  0.06  0.06                *
* AVE QUEUE veh        0     1     0     0                * VEHIC HRS     1.6 *
* MAX QUEUE veh        1     1     0     0                * COST      $      25 *
*
*****

```

Table D-8.Scenario 4 - 2030 Roundabout PM Peak (CSAH 9 at CSAH 60)

```

*****
*
* 31:3:09                2030 RAB OPT 60 PM                51 *
*
*****
*
* E      (m)      8.53   8.53   8.53   8.53                * TIME PERIOD      min    90 *
* L'     (m)      0.00   0.00   0.00   0.00                * TIME SLICE       min    15 *
* V      (m)      8.53   8.53   8.53   8.53                * RESULTS PERIOD   min   15 75 *
* RAD    (m)     24.38  24.38  24.38  24.38                * TIME COST        $/hr  15.00 *
* PHI    (d)     16.50  30.50  24.50  23.50                * FLOW PERIOD      min   15 75 *
* DIA    (m)     48.77  48.77  48.77  48.77                * FLOW TYPE        pcu/veh  VEH *
* GRAD SEP      0      0      0      0                * FLOW PEAK        am/op/pm  PM *
*
*****
* LEG NAME *PCU *VEH TURNS (1st exit, 2nd..U)*FLOF*CL* FLOW RATIO *FLOW TIME*
*          *   *
* 60 SB    *1.02* 501 370 45 0 *1.00*90*0.89 1.077 0.89*15 45 75 *
* 60 EB    *1.02* 219 832 460 0 *1.00*90*0.92 1.080 0.92*15 45 75 *
* 60 NB    *1.02* 198 272 187 0 *1.00*90*0.79 1.333 0.79*15 45 75 *
* 60 WB    *1.02* 31 465 192 0 *1.00*90*0.92 1.080 0.92*15 45 75 *
*          *   *
*          *   *
*          *   *
*****
*
* FLOW      veh      916  1511  657  688                * AVEDEL    s      7.4 *
* CAPACITY  veh     1727  1822  1279  1621                * LOS      SIG    A *
* AVE DELAY mins     0.07  0.19  0.10  0.06                * LOS UNSIG  A *
* MAX DELAY mins     0.09  0.26  0.16  0.08                *
* AVE QUEUE veh       1      5      1      1                * VEHIC HRS   7.7 *
* MAX QUEUE veh       1      6      1      1                * COST      $    116 *
*
*****

```